

April 30, 2008

Mr. Gerardo Rios U.S. EPA, Region IX 75 Hawthorne Street San Francisco, CA 94105

SUBJECT:

Transmittal of Proposed Title V Renewal Permit

Los Angeles Department of Water and Power, Haynes Facility

6801 2nd Street

Long Beach, CA 90803 Facility ID 800074

Dear Mr. Rios: Heronfo

Enclosed is the above-referenced proposed renewal of a Title V permit along with the facility permit application, a Statement of Basis and public notice. With your receipt of this proposed Title V permit, we will note that the EPA 45-day review period has begun.

Questions on the proposed permit should be directed to Mr. Chris Perri, Air Quality Engineer, at (909) 396-2696 or cperri@aqmd.gov.

Sincerely.

Mohsen Nazemi, P.E. Deputy Executive Officer Engineering and Compliance

MN:MDM:RGC:CDP

Enclosures:

Facility Permit (Proposed Renewal) Public Notice Statement of Basis Facility Permit Application

Title Page

Facility I.D.#: 800074
Revision #: DRAFT
Date: April 24, 2008

FACILITY PERMIT TO OPERATE

LA CITY, DWP HAYNES GENERATING STATION 6801 2ND ST LONG BEACH, CA 90803

NOTICE

IN ACCORDANCE WITH RULE 206, THIS PERMIT TO OPERATE OR A COPY THEREOF MUST BE KEPT AT THE LOCATION FOR WHICH IT IS ISSUED.

THIS PERMIT DOES NOT AUTHORIZE THE EMISSION OF AIR CONTAMINANTS IN EXCESS OF THOSE ALLOWED BY DIVISION 26 OF THE HEALTH AND SAFETY CODE OF THE STATE OF CALIFORNIA OR THE RULES OF THE SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT. THIS PERMIT SHALL NOT BE CONSTRUED AS PERMISSION TO VIOLATE EXISTING LAWS, ORDINANCES, REGULATIONS OR STATUTES OF ANY OTHER FEDERAL, STATE OR LOCAL GOVERNMENTAL AGENCIES.

barry R. wanerstein, D. Env.
EXECUTIVE OFFICER
Ву
Mohsen Nazemi, P.E.
Deputy Executive Officer

Engineering & Compliance

Table of Content
Facility I.D.#: 800074
Revision #: DRAFT
Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

TABLE OF CONTENTS

Section	Description	Revision #	Date Issued
A	Facility Information	DRAFT	04/24/2008
В	RECLAIM Annual Emission Allocation	DRAFT	04/24/2008
C	Facility Plot Plan	TO BE DEVELO	PED
D	Facility Description and Equipment Specific Conditions	DRAFT	04/24/2008
E	Administrative Conditions	DRAFT	04/24/2008
F	RECLAIM Monitoring and Source Testing Requirements	DRAFT	04/24/2008
G	Recordkeeping and Reporting Requirements for RECLAIM Sources	DRAFT	04/24/2008
Н	Permit To Construct and Temporary Permit to Operate	DRAFT	04/24/2008
I	Compliance Plans & Schedules	DRAFT	04/24/2008
J	Air Toxics	DRAFT	04/24/2008
K	Title V Administration	DRAFT	04/24/2008
Appendix			
A	NOx and SOx Emitting Equipment Exempt From Written Permit Pursuant to Rule 219	DRAFT	04/24/2008
В	Rule Emission Limits	DRAFT	04/24/2008

Section A Page 1
Facility I.D.#: 800074
Revision #: DRAFT
Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION A: FACILITY INFORMATION

LEGAL OWNER &/OR OPERATOR:

LA CITY, DWP HAYNES GENERATING STATION

LEGAL OPERATOR (if different than owner):

EQUIPMENT LOCATION:

6801 2ND ST

LONG BEACH, CA 90803-4324

MAILING ADDRESS:

P.O. BOX 51111 RM# 1050

LOS ANGELES, CA 90051-5700

RESPONSIBLE OFFICIAL:

ARAM BENYAMIN

TITLE:

ACTING SENIOR ASSISTANT GENERAL MANAGER

TELEPHONE NUMBER:

(213) 367-4435

CONTACT PERSON:

MARK SEDLACEK

TITLE:

DIRECTOR OF ENVIRONMENTAL SERVICES

TELEPHONE NUMBER:

(213) 367-0403

TITLE V PERMIT ISSUED:

TITLE V PERMIT EXPIRATION DATE:

thight uut

TITLE V	RECLAIM	
YES	NOx:	YES
	SOx:	NO
	CYCLE:	1
	ZONE:	COASTAL

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION B: RECLAIM ANNUAL EMISSION ALLOCATION

The annual allocation of NOx RECLAIM Trading Credits (RTCs) for this facility is calculated pursuant to Rule 2002. Total NOx emission shall not exceed such annual allocations unless the operator obtains RTCs corresponding to the facility's increased emissions in compliance with Rules 2005 and 2007.

The level of Starting Allocation plus Non-Tradable Credits used to determine compliance with Rule 2005(c)(4) and applicability of Rule 2005(e) - Trading Zone Restrictions is listed on the last page of this Section.

The following table lists the annual allocations that were issued to this facility and the amounts of RTCs held by this facility on the day of printing this Section.

RECLAIM POLLUTANT ANNUAL ALLOCATION (POUNDS)

Year Begin End (month/year)	Zone	NOx RTC Initially Allocated	NOx RTC ¹ Holding as of 04/24/08 (pounds)	Non-Tradable ² Non-Usable RTCs (pounds)
7/2005 6 /2006	Coastal	0	30002	0
1/2006 12/2006	Coastal	489016	390031	0
7/2006 6 /2007	Coastal	0	0	0
1/2007 12/2007	Coastal	489016	119696	0
1/2008 12/2008	Coastal	489016	418598	13203
1/2009 12/2009	Coastal	489016	405394	26407
1/2010 12/2010	Coastal	489016	392191	39610
1/2011 12/2011	Coastal	489016	378987	52814
1/2012 12/2012	Coastal	489016	378987	52814
1/2013 12/2013	Coastal	489016	378987	52814
1/2014 12/2014	Coastal	489016	378987	52814
1/2015 12/2015	Coastal	489016	378987	52814
1/2016 12/2016	Coastal	489016	378987	52814
1/2017 12/2017	Coastal	489016	378987	52814
1/2018 12/2018	Coastal	489016	378987	52814
1/2019 12/2019	Coastal	489016	378987	52814
1/2020 12/2020	Coastal	489016	378987	52814

Footnotes:

- 1. This number may change due to pending trades, emissions reported under Quarterly Certification of Emissions Report (QCER) and Annual Permit Emission Program (APEP) Report required pursuant to Rule 2004, or deductions made pursuant to Rule 2010(b). The most recent total RTC information can be obtained from the District's RTC Listing.
- 2. The use of such credits is subject to restrictions set forth in paragraph (f)(1) of Rule 2002.

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION B: RECLAIM ANNUAL EMISSION ALLOCATION

The annual allocation of NOx RECLAIM Trading Credits (RTCs) for this facility is calculated pursuant to Rule 2002. Total NOx emission shall not exceed such annual allocations unless the operator obtains RTCs corresponding to the facility's increased emissions in compliance with Rules 2005 and 2007.

The level of Starting Allocation plus Non-Tradable Credits used to determine compliance with Rule 2005(c)(4) and applicability of Rule 2005(e) - Trading Zone Restrictions is listed on the last page of this Section.

The following table lists the annual allocations that were issued to this facility and the amounts of RTCs held by this facility on the day of printing this Section.

RECLAIM POLLUTANT ANNUAL ALLOCATION (POUNDS)

Yea Begin (month/y	End	Zone	NOx RTC Initially Allocated	NOx RTC ¹ Holding as of 04/24/08 (pounds)	Non-Tradable ² Non-Usable RTCs (pounds)
1/2021 1/2022	12/2021 12/2022	Coastal Coastal	489016 489016	378987 378987	52814 52814
1/2023	12/2023	Coastal	489016	378987	52814

Footnotes:

- 1. This number may change due to pending trades, emissions reported under Quarterly Certification of Emissions Report (QCER) and Annual Permit Emission Program (APEP) Report required pursuant to Rule 2004, or deductions made pursuant to Rule 2010(b). The most recent total RTC information can be obtained from the District's RTC Listing.
- 2. The use of such credits is subject to restrictions set forth in paragraph (f)(1) of Rule 2002.

Section B Page 3
Facility I.D.#: 800074
Revision #: DRAFT
Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION B: RECLAIM ANNUAL EMISSION ALLOCATION

The annual allocation of RECLAIM Trading Credits (RTCs) for this facility is calculated pursuant to Rule 2002. If the facility submits a permit application to increase an annual allocation to a level greater than the facility's Starting Allocation plus Non-Tradable Credits as listed below, the application will be evaluated for compliance with Rule 2005(c)(4). Rule 2005(e)-Trading Zone Restrictions applies if an annual allocation is increased to a level greater than the facility's Starting Allocation plus Non-Tradable Credits:

· Yea Begin	ır End	Zone	NOx RTC Starting Allocation (pounds)	Non-Tradable Credits(NTCs) (pounds)
1/1994	12/1994	Coastal	3666443	0

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION C: FACILITY PLOT PLAN

(TO BE DEVELOPED)

Section D Page: 1
Facility I.D.: 800074
Revision #: DRAFT
Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : POWER GENER System 1 : BOILERS	ATION				
BOILER, UNIT NO. 1, FUEL OIL, NATURAL GAS, COMBUSTION ENGINEERING, FRONT FIRED, AIR PREHEATED, WITH OXYGEN CONTENT CONTROL, 2240 MMBTU/HR WITH A/N: 410730 GENERATOR, 230 MW INJECTOR, MAGNESIUM COMPOUNDS, FUEL OIL	DI	C73 S96	NOX: MAJOR SOURCE**	CO: 2000 PPMV (5) [RULE 407,4-2-1982]; NOX: 12.37 LBS/1000 GAL FUEL OIL (1) [RULE 2012,5-6-2005]; NOX: 5 PPMV (5A) [RULE 2009,5-11-2001] PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]; SO2: (9) [40CFR 72 - Acid Rain Provisions,11-24-1997]; SOX: 500 PPMV FUEL OIL (5) [RULE 407,4-2-1982]	A195.5, B59.1, D182.1, D371.1, E202.1, E204.1, E204.2, K171.1
ADDITIVE SYSTEM					
SELECTIVE CATALYTIC REDUCTION, UNIT NO. 1, TWO BABCOCK & WILCOX REACTORS, 1760 CUBIC FEET OF TOTAL CATALYST VOLUME, WIDTH: 19 FT 3 IN; HEIGHT: 23 FT 9 IN; LENGTH: 12 FT 10 IN WITH A/N: 259533	C73	DI		NH3: 20 PPMV NATURAL GAS (4) [RULE 1303(a)(1)- BACT,5-10-1996; RULE 1303(a)(1)-BACT,12-6-2002]; NH3: 10 PPMV FUEL OIL (4) [RULE 1303(a)(1)-BACT,5-10- 1996 RULE 1303(a)(1)-BACT,12-6- 2002]	A99.1, C1.2, D12.2, D12.3, D28.2, D28.3, E73.1, E179.1, E179.2

*	f(1)f(1A)f	1B) Denotes	RECLAIM	emission	factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

Section D Page: 2 Facility I.D.: 800074 Revision #: DRAFT Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : POWER GENER	ATION				
AMMONIA INJECTION, UNIT NO. 1, TWO AMMONIA/AIR INJECTION GRIDS, EACH HAVING 1104 INJECTION NOZZLES	C74	•			
STACK, BOILER NO. 1 A/N: 410730	S96	Di			
BOILER, UNIT NO. 2, FUEL OIL, NATURAL GAS, COMBUSTION ENGINEERING, FRONT FIRING, AIR PREHEATED, WITH OXYGEN CONTENT CONTROL, 2240 MMBTU/HR WITH A/N: 410732	D4	C75 S97	NOX: MAJOR SOURCE**	CO: 2000 PPMV (5) [RULE 407,4-2-1982]; NOX: 12.37 LBS/1000 GAL FUEL OIL (1) [RULE 2012,5-6-2005]; NOX: 5 PPMV (5A) [RULE 2009,5-11-2001] . PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]; SO2: (9) [40CFR 72 - Acid Rain Provisions,11-24-1997]; SOX: 500 PPMV FUEL OIL (5) [RULE 407,4-2-1982]	A195.5, B59.1, D182.1, D371.1, E202.1, E204.1, E204.2, K171.1
INJECTOR, MAGNESIUM COMPOUNDS, FUEL OIL ADDITIVE SYSTEM					
GENERATOR, 230 MW					

*	(1)(1A)(11	B) Denotes RECLAIM emission factor	(2)(2A)(2E)	B) Denotes RECLAIM emission rate
	(3)	Denotes RECLAIM concentration limit	(4)	Denotes BACT emission limit
	(5)(5A)(5I	B) Denotes command and control emission limit	(6)	Denotes air toxic control rule limit
	(7)	Denotes NSR applicability limit	(8)(8A)(8E	B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)
	(9)	See App B for Emission Limits	(10)	See Section I for NESHAP/MACT requirements

^{**} Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

Section D Page: 3
Facility I.D.: 800074
Revision #: DRAFT
Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : POWER GENER	ATION				
SELECTIVE CATALYTIC REDUCTION, UNIT NO. 2, TWO BABCOCK & WILCOX REACTORS, 1760 CUBIC FEET OF TOTAL CATALYST VOLUME, WIDTH: 19 FT 3 IN; HEIGHT: 23 FT 9 IN; LENGTH: 12 FT 10 IN WITH A/N: 259534	C75	D4		NH3: 20 PPMV NATURAL GAS (4) [RULE 1303(a)(1)- BACT,5-10-1996; RULE 1303(a)(I)-BACT,12-6-2002]; NH3: 10 PPMV FUEL OIL (4) [RULE 1303(a)(1)-BACT,5-10- 1996 RULE 1303(a)(1)-BACT,12-6- 2002]	A99.1, C1.2, D12.2, D12.3, D28.2, D28.3, E73.1, E179.1, E179.2
AMMONIA INJECTION, UNIT NO. 2, TWO AMMONIA/AIR INJECTION GRIDS, EACH HAVING 1104 INJECTION NOZZLES	C76				
STACK, BOILER NO. 2 A/N: 410732	S97	D4			
BOILER, UNIT NO. 5, FUEL OIL, NATURAL GAS, BABCOCK AND WILCOX, OPPOSED FIRING, SUPERCRITICAL, AIR PREHEATED, WITH OXYGEN CONTENT CONTROL, 3240 MMBTU/HR WITH A/N: 410734	D7	C77 S98	NOX: MAJOR SOURCE**	CO: 2000 PPMV (5) [RULE 407,4-2-1982]; NOX: 12.37 LBS/1000 GAL FUEL OIL (1) [RULE 2012,5-11-2001; RULE 2012,12-5-2003] NOX: 5 PPMV (5A) [RULE 2009,5-11-2001]; PM: 0.1	A195.5, B59.1, D182.1, D371.1, E202.1, E204.1, E204.2, K171.1
				GRAINS/SCF (5) [RULE 409,8-7-1981] ; SO2: (9) [40CFR 72 - Acid Rain Provisions,11-24-1997]	

k	(1)(1A)/IB	Denotes	RECLAIM	emission	factor
r	(1)(1A)(1B)	Denotes	RECLAIM	emission	ractor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

Section D Facility I.D.: Revision #: DRAFT Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : POWER GENER	ATION				s
		ar or server	Control of the state of the sta	SOX: 500 PPMV FUEL OIL (5) [RULE 407,4-2-1982]	
GENERATOR, 343 MW					
INJECTOR, MAGNESIUM COMPOUNDS, FUEL OIL ADDITIVE SYSTEM					,
SELECTIVE CATALYTIC REDUCTION, UNIT NO. 5, NOELL REACTOR, 3339 CUBIC FEET OF TOTAL CATALYST VOLUME, WIDTH: 39 FT; HEIGHT: 30 FT; LENGTH: 53 FT 4 IN WITH A/N: 274319	C77	D7		NH3: 20 PPMV NATURAL GAS (4) [RULE 1303(a)(1)- BACT,5-10-1996; RULE 1303(a)(1)-BACT,12-6-2002]; NH3: 20 PPMV FUEL OIL (4) [RULE 1303(a)(1)-BACT,5-10- 1996 RULE 1303(a)(1)-BACT,12-6- 2002]	D12.2, D12.3, D28.2, D28.3, E73.1, E179.1, E179.2
AMMONIA INJECTION, UNIT NO. 5, AMMONIA/AIR INJECTION GRID, HAVING 480 INJECTION NOZZLES	C78		•		
STACK, BOILER NO. 5 A/N: 410734	S98	D7			

*	(1)(1A)(1B) Denote	s RECLAIM	emission	factor

Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

Denotes NSR applicability limit (7)

(9) See App B for Emission Limits (2)(2A)(2B) Denotes RECLAIM emission rate

Denotes BACT emission limit (4)

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS,etc.) See Section J for NESHAP/MACT requirements (10)

Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

Date:


Page: 5 .: 800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : POWER GENER	ATION				·
BOILER, UNIT NO. 6, FUEL OIL, NATURAL GAS, BABCOCK AND WILCOX, OPPOSED FIRING, SUPERCRITICAL, AIR PREHEATED, STEAM PIPE ID: 6.17", OD: 10.75", WITH OXYGEN CONTENT CONTROL, 2510 MMBTU/HR WITH A/N: 471457	D9	C79 S99	NOX: MAJOR SOURCE**	CO: 2000 PPMV (5) [RULE 407,4-2-1982]; NOX: 12.37 LBS/1000 GAL FÜEL OIL (1) [RULE 2012,5-6-2005]; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981]	B59.1, D182.1, D371.1, E193.5, E202.1, E204.1, E204.2, K171.1
				SO2: (9) [40CFR 72 - Acid Rain Provisions,11-24-1997]; SOX: 500 PPMV FUEL OIL (5) [RULE 407,4-2-1982]	
GENERATOR, RATED 261 MW, LIMITED TO 243 MW BY CEC					
INJECTOR, MAGNESIUM COMPOUNDS, FUEL OIL ADDITIVE SYSTEM					
STACK, BOILER NO. 6 A/N: 471457	S99	D9			,
System 2 : TURBINES		÷			
GAS TURBINE, UNIT NO. 9, DIESEL FUEL, NATURAL GAS, GENERAL ELECTRIC, MODEL PG7241FA, COMBINED CYCLE, WATER INJECTION (DIESEL FIRING ONLY), WITH LOW NOX BURNER, 1757 MMBTU/HR WITH A/N: 462975	D125	C130	NOX: MAJOR SOURCE**	CO: 2000 PPMV (5) [RULE 407,4-2-1982] ; CO: 4 PPMV (4) [RULE 1303(a)(1)-BACT,5- 10-1996; RULE 1303(a)(1)- BACT, 12-6-2002]	A63.3, A99.2, A99.3, A195.1, A195.2, A195.3, A327.1, A433.1, B75.1, D29.4, D29.5, D82.1, D82.2,



(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B)Denotes 40 CFR limit(e.g. NSPS, NESHAPS,etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

Section D Facility I.D.: Revision #: DRAFT Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : POWER GEN	ERATION				,
				NOX: 2 PPMV NATURAL GAS (4) [RULE 2005,5-6-2005]; NOX: 121 PPMV DIESEL (8) [40CFR 60 Subpart GG,3-6-1981]; NOX: 111 PPMV NATURAL GAS (8) [40CFR 60 Subpart GG,3-6-1981]	D372.1, E57.1, E193.1, I296.1, K40.3, K67.4
				NOX: 22.16 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6- 2005]; PM: 0.01 GRAINS/SCF (5A) [RULE 475,10-8-1976; RULE 475,8-7-1978]	
			,	PM: 11 LBS/HR (5B) [RULE 475,10-8-1976; RULE 475,8-7-1978] ; PM: 0.1 GRAINS/SCF NATURAL GAS (5) [RULE 409,8-7-1981]	
		·		SO2: (9) [40CFR 72 - Acid Rain Provisions,11-24-1997]; SOX: 500 PPMV FUEL OIL (5) [RULE 407,4-2-1982]; SOX: 150 PPMV (8) [40CFR 60 Subpart GG,3-6-1981]	
				VOC: 2 PPMV (4) [RULE 1303(a)(1)-BACT,5-10-1996;RULE 1303(a)(1)-BACT,12-6-2002]	•

*	(1)(1A)(1B)Denotes RECLAIM emission factor	(2)
	(3)	Denotes RECLAIM concentration limit	(4)

(5)(5A)(5B) Denotes command and control emission limit

Denotes NSR applicability limit (7)

See App B for Emission Limits (9)

2)(2A)(2B) Denotes RECLAIM emission rate

Denotes BACT emission limit

Denotes air toxic control rule limit (6)

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.) See Section J for NESHAP/MACT requirements (10)

Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

Section D
Facility I.D.:
Payision #:

Page: 7 .: 800074 DRAFT April 24, 2008

Revision #:
Date: Apr

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : POWER GENER	ATION				
GENERATOR, (MAX GROSS OUTPUT AT 65 DEG. F), 169.9 MW					
GENERATOR, HEAT RECOVERY STEAM					
STEAM TURBINE, STEAM, UNIT NO. 8, COMMON TO GAS TURBINES NO. 9 AND NO. 10, 257 MW (AT 65 DEG. F)					
BURNER, DUCT, NATURAL GAS, LOCATED IN THE HRSG OF TURBINE NO. 9, 286.6 MMBTU/HR A/N: 462975	D129	C130	NOX: MAJOR SOURCE**	CO: 2000 PPMV (5) [RULE 407,4-2-1982]; CO: 4 PPMV (4) [RULE 1303(a)(1)-BACT,5- 10-1996; RULE 1303(a)(1)- BACT, 12-6-2002]	A63.3, A99.2, A99.3, A195.1, A195.2, A195.3, A327.1, A433.1, B75.1, D29.4, D29.5, D82.1, D82.2,
				NOX: 0.2 LBS/MMBTU NATURAL GAS (8) [40CFR 60 Subpart Da,10-4-1991]; NOX: 2 PPMV NATURAL GAS (4) [RULE 2005,5-6-2005]	D372.1, E57.1, E193.1, I296.1, K40.3, K67.4
				PM: 0.03 LBS/MMBTU NATURAL GAS (8) [40CFR 60 Subpart Da,10-4-1991]; PM: 0.1 GRAINS/SCF NATURAL GAS (5) [RULE 409,8-7-1981]	

*	(1)(1)	A)/1R)	Denotes	DECL	Δ TM	emission	factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

Section D Page: 8 Facility I.D.: 800074 Revision #: DRAFT Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : POWER GENER	ATION				
			,	PM: 0.01 GRAINS/SCF (5A) [RULE 475,10-8-1976; RULE 475,8-7-1978]; PM: 11 LBS/HR (5B) [RULE 475,10-8-1976; RULE 475,8-7-1978] SO2: (9) [40CFR 72 - Acid Rain Provisions,11-24-1997]; SOX: 0.2 LBS/MMBTU NATURAL GAS (8) [40CFR 60 Subpart Da,10-4-1991] VOC: 2 PPMV (4) [RULE 1303(a)(1)-BACT,5-10-1996; RULE 1303(a)(1)-BACT,12-6-2002]	
STACK, SERVING UNIT NO. 9, HEIGHT: 140 FT; DIAMETER: 19 FT A/N: 462975	S133	C131			
CO OXIDATION CATALYST, SERVING UNIT NO. 9, HITACHI, MITSUBISHI, PEERLESS OR EQUAL, HEIGHT:61 FT; LENGTH:26 FT; WIDTH:4 FT; WITH 6344 CUBIC FEET OF CATALYST VOLUME A/N: 432467	C130	D125 D129 C131			

					_
*	(1)(1A)	(1B) Denotes	RECLAIM	emission	factor

3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

Section D

DRAFT

Facility I.D.: Revision #: Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : POWER GENER	ATION				
SELECTIVE CATALYTIC REDUCTION, SERVING UNIT NO. 9, HITACHI, MITSUBISHI, PEERLESS OR EQUAL, HEIGHT: 61 FT; LENGTH:26 FT; WIDTH: 5 FT, WITH 7930 CU FEET OF CATALYST VOLUME WITH A/N: 432467 AMMONIA INJECTION, INJECTION GRID	C131	C130 S133		NH3: 5 PPMV NATURAL GAS (4) [RULE 1303(a)(1)- BACT,5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]	A195.4, D12.6, D12.7, D12.8, D29.2, E73.2, E179.3, E179.4
GAS TURBINE, UNIT NO. 10, DIESEL FUEL, NATURAL GAS, GENERAL ELECTRIC, MODEL PG7241FA, COMBINED CYCLE, WATER INJECTION (DIESEL FIRING ONLY), WITH LOW NOX BURNER, 1757 MMBTU/HR WITH A/N: 462976	D134	C138	NOX: MAJOR SOURCE**	CO: 2000 PPMV (5) [RULE 407,4-2-1982]; CO: 4 PPMV (4) [RULE 1303(a)(1)-BACT,5- 10-1996; RULE 1303(a)(1)- BACT, 12-6-2002]	A63.2, A99.2, A99.3, A195.1, A195.2, A195.3, A327.1, A433.1, B75.1, D29.4, D29.5, D82.1, D82.2,
A/N. 402970	,			NOX: 2 PPMV NATURAL GAS (4) [RULE 2005,5-6-2005]; NOX: 121 PPMV DIESEL (8) [40CFR 60 Subpart GG,3-6-1981]; NOX: 111 PPMV NATURAL GAS (8) [40CFR 60 Subpart GG,3-6-1981]	D372.1, E57.1, E193.1, I296.1, K40.3, K67.4
				NOX: 22.16 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6- 2005]; PM: 0.01 GRAINS/SCF (5A) [RULE 475,10-8-1976; RULE 475,8-7-1978]	

*	(1)(1A)(1B)	Denotes	RECLAIM	emission	factor
---	-------------	---------	---------	----------	--------

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)

See Section J for NESHAP/MACT requirements (10)

Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

Section D Page: 10 Facility I.D.: 800074 Revision #: DRAFT April 24, 2008 Date:

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : POWER GENE	RATION				
				PM: 11 LBS/HR (5B) [RULE 475,10-8-1976; RULE 475,8-7-1978] ; PM: 0.1 GRAINS/SCF NATURAL GAS (5) [RULE 409,8-7-1981]	
	·			SO2: (9) [40CFR 72 - Acid Rain Provisions,11-24-1997]; SOX: 500 PPMV FUEL OIL (5) [RULE 407,4-2-1982]; SOX: 150 PPMV (8) [40CFR 60 Subpart GG,3-6-1981]	•
				VOC: 2 PPMV (4) [RULE 1303(a)(1)-BACT,5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]	
GENERATOR, (MAX GROSS OUTPUT AT 65 DEG. F), 169.9 MW					
GENERATOR, HEAT RECOVERY STEAM					
STEAM TURBINE, STEAM, UNIT NO. 8, COMMON TO GAS TURBINES NO. 9 AND NO. 10, 257 MW (AT 65 DEG, F)	,				

*	(1)(1 A)(1B) Denotes	RECLAIM	emission	factor

Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9)See App B for Emission Limits (2)(2A)(2B) Denotes RECLAIM emission rate

Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)

See Section J for NESHAP/MACT requirements

(10)

Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

Section D Page: 11 Facility I.D.: 800074 Revision #: DRAFT Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : POWER GENER	ATION				
BURNER, DUCT, NATURAL GAS, LOCATED IN THE HRSG OF TURBINE NO. 10, 286.6 MMBTU/HR A/N: 462976	D142	C138	NOX: MAJOR SOURCE**	CO: 2000 PPMV (5) [RULE 407,4-2-1982] ; CO: 4 PPMV (4) [RULE 1303(a)(1)-BACT,5- 10-1996;RULE 1303(a)(1)- BACT,12-6-2002]	A63.2, A99.2, A99.3, A195.1, A195.2, A195.3, A327.1, A433.1, B75.1, D29.4, D29.5, D82.1, D82.2,
				NOX: 0.2 LBS/MMBTU NATURAL GAS (8) [40CFR 60 Subpart Da,10-4-1991]; NOX: 2 PPMV NATURAL GAS (4) [RULE 2005,5-6-2005]	D372.1, E57.1, E193.1, I296.1, K40.3, K67.4
				PM: 0.03 LBS/MMBTU NATURAL GAS (8) [40CFR 60 Subpart Da,10-4-1991]; PM: 0.1 GRAINS/SCF NATURAL GAS (5) [RULE 409,8-7-1981]	
	-			PM: 0.01 GRAINS/SCF (5A) [RULE 475,10-8-1976; RULE 475,8-7-1978]; PM: 11 LBS/HR (5B) [RULE 475,10-8-1976; RULE 475,8-7-1978]	
		,		SO2: (9) [40CFR 72 - Acid Rain Provisions,11-24-1997]; SOX: 0.2 LBS/MMBTU NATURAL GAS (8) [40CFR 60 Subpart Da,10-4-1991]	

ķ	(1)(I:A)(I:B) Denotes	RECLAIM	emission facto	r

Denotes RECLAIM concentration limit (3)

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9)

See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

Section D Page: 12
Facility I.D.: 800074
Revision #: DRAFT
Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : POWER GENER	ATION				
				VOC: 2 PPMV (4) [RULE 1303(a)(1)-BACT,5-10-1996; RULE 1303(a)(1)-BACT,12-6-2002]	
STACK, SERVING UNIT NO. 10, HEIGHT: 140 FT; DIAMETER: 19 FT A/N: 462976	S141	C139			
CO OXIDATION CATALYST, SERVING UNIT NO. 10, HITACHI, MITSUBISHI, PEERLESS OR EQUAL, HEIGHT:61 FT; LENGTH:26 FT; WIDTH:4 FT; WITH 6344 CUBIC FEET OF CATALYST VOLUME A/N: 432466	C138	D134 C139 D142			
SELECTIVE CATALYTIC REDUCTION, SERVING UNIT NO. 10, HEIGHT: 61 FT; LENGTH:26 FT; WIDTH: 5 FT, WITH 7930 CU FEET OF CATALYST VOLUME WITH A/N: 432466	C139	C138 S141		NH3: 5 PPMV NATURAL GAS (4) [RULE 1303(a)(1)- BACT,5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]	A195.4, D12.6, D12.7, D12.8, D29.2, E73.2, E179.3, E179.4
AMMONIA INJECTION, INJECTION GRID		eron (c)	7		
Process 2: INORGANIC CE STORAGE TANK, NO. 1, AQUEOUS AMMONIA, CARBON STEEL, 38233 GALS; DIAMETER: 14 FT; HEIGHT: 38 FT 6 IN A/N: 272086	D34	C40 C41			C157.1, E144.1

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS,etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.


Page: 13
.: 800074
DRAFT
April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2 : INORGANIC CH	IEMICAI	STORAGE			
STORAGE TANK, NO. 2, AQUEOUS AMMONIA, CARBON STEEL, 38233 GALS; DIAMETER: 14 FT; HEIGHT: 38 FT 6 IN A/N; 272087	D35	C40 C41			C157.1, E144.1
STORAGE TANK, NO. 3, AQUEOUS AMMONIA, 38233 GALS; DIAMETER: 14 FT; HEIGHT: 38 FT 6 IN A/N: 272088	D36	C40 C41			C157.1, E144.1
STORAGE TANK, NO. 4, AQUEOUS AMMONIA, 38233 GALS; DIAMETER: 14 FT; HEIGHT: 38 FT 6 IN A/N: 272089	D37	C40 C41			C157.1, E144.1
STORAGE TANK, NO. 5, AQUEOUS AMMONIA, 38233 GALS; DIAMETER: 14 FT; HEIGHT: 38 FT 6 IN A/N: 272090	D38	C40 C41			C157.1, E144.1
STORAGE TANK, NO. 6, AQUEOUS AMMONIA, 38233 GALS; DIAMETER: 14 FT; HEIGHT: 38 FT 6 IN A/N: 272091	D39	C40 C41		,	C157.1, E144.1
SCRUBBER, PACKED BED, NO. 1, VERTICAL PACKED TYPE, POLYPROPYLENE PACKING, HEIGHT: 9 FT 3 IN; DIAMETER: 8 IN A/N: 272090	C40	D34 D35 D36 D37 D38 D39			C8.1, D12.1, K67.2
SCRUBBER, PACKED BED, NO. 2, VERTICAL PACKED TYPE, POLYPROPYLENE PACKING, HEIGHT: 9 FT 3 IN; DIAMETER: 8 IN A/N: 272090	C41	D34 D35 D36 D37 D38 D39			C8.1, D12.1, K67.2



(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS,etc.)

(10) See Section J for NESHAP/MACT requirements

^{**} Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

Section D Page: 14
Facility 1.D.: 800074
Revision #: DRAFT
Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 2 : INORGANIC CI	IEMICA	L STORAGI	C		
STORAGE TANK, UNIT NO. 1, MAGNESIUM COMPOUNDS, FUEL OIL ADDITIVE, 350 GALS A/N: 410730	D21				
STORAGE TANK, UNIT NO. 2, MAGNESIUM COMPOUNDS, FUEL OIL ADDITIVE, 350 GALS A/N: 410732	D22				
STORAGE TANK, UNIT NO. 5, MAGNESIUM COMPOUNDS, FUEL OIL ADDITIVE, 350 GALS A/N: 410734	D25				
STORAGE TANK, UNIT NO. 6, MAGNESIUM COMPOUNDS, FUEL OIL ADDITVE, 350 GALS A/N: 471457	D26				
Process 3 : PETROLEUM S	TORAGI	£			
STORAGE TANK, EXTERNAL FLOATING ROOF, STEAM HEATED, NO. 500,003, FUEL OIL, SINGLE SEAL, 500000 BBL; DIAMETER: 255 FT; HEIGHT: 56 FT WITH A/N: G02233	D44				B22.2, H23.1
FLOATING ROOF					4
PRIMARY SEAL, METALLIC SHOE					

	(1)(1.4)(1.D) D.a	nates DECLAIM	Lamicaian	footor
¥.	(D)(TA)(TB)De	notes RECLAIM	emission	ractor

3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS,etc.)

(10) See Section J for NESHAP/MACT requirements

Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

Date:

Page: 15 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 3 : PETROLEUM S	STORAG	E			
STORAGE TANK, FIXED ROOF, STEAM HEATED, NO. 172,003-A, FUEL OIL, 172000 BBL; DIAMETER: 160 FT; HEIGHT: 48 FT A/N: C25861	D46				H23.1
STORAGE TANK, FIXED ROOF, STEAM HEATED, NO. 172,001-B, FUEL OIL, 172000 BBL; DIAMETER: 160 FT; HEIGHT: 48 FT A/N: C25859	D47		,	6.	H23.1
STORAGE TANK, FIXED ROOF, STEAM HEATED, NO. 172,002-C, FUEL OIL, 172000 BBL; DIAMETER: 160 FT; HEIGHT: 48 FT A/N: C25860	D48				H23.1
STORAGE TANK, FIXED ROOF, STEAM HEATED, NO. 200,001-D, FUEL OIL, 200000 BBL; DIAMETER: 160 FT; HEIGHT: 56 FT A/N: C25862	D49				H23.1
STORAGE TANK, FIXED ROOF, STEAM HEATED, NO. 300,001-E, FUEL OIL, 300000 BBL; DIAMETER: 200 FT; HEIGHT: 56 FT A/N: C25863	D50				H23.1
TANK, UNIT NO. 1, TURBINE LUBE OIL RESERVOIR A/N: 122505	DII	C27		PM: (9) [RULE 404,2-7-1986]	
TANK, UNIT NO. 1, TURBINE GOVERNOR OIL RESERVOIR A/N: 122505	D12	C27		PM: (9) [RULE 404,2-7-1986]	

k	(1)	(1A)(1B)	Denotes	RECLAIM	emission	factor

Denotes RECLAIM concentration limit (3)

(5)(5A)(5B) Denotes command and control emission limit

Denotes NSR applicability limit (7)

See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

Denotes BACT emission limit

Denotes air toxic control rule limit (6)

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS,etc.)

See Section J for NESHAP/MACT requirements

(10)

Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

Section D Page: 16 Facility I.D.: 800074 Revision #: Date:


DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 3 : PETROLEUM S	TORAG	E			
ELECTROSTATIC PRECIPITATOR, NO. 1, SMOG HOG, MODEL SH-10-PE, TWO STAGE, PENNY TYPE, 60 KW A/N: 122505	C27	D11 D12			D323.1
TANK, UNIT NO. 2, TURBINE LUBE OIL RESERVOIR A/N: 122506	D13	C28		PM: (9) [RULE 404,2-7-1986]	
TANK, UNIT NO. 2, TURBINE GOVERNOR OIL RESERVOIR A/N: 122506	D14	C28		PM: (9) [RULE 404,2-7-1986]	
ELECTROSTATIC PRECIPITATOR, NO. 2, SMOG HOG, MODEL SH-10-PE, TWO STAGE, PENNY TYPE, 60 KW A/N: 122506	C28	D13 D14			D323.1
TANK, UNIT NO. 3, TURBINE LUBE OIL RESERVOIR A/N: 122507	D15	C29		PM: (9) [RULE 404,2-7-1986]	_
TANK, UNIT NO. 3, TURBINE GOVERNOR OIL RESERVOIR A/N: 122507	D16	C29		PM: (9) [RULE 404,2-7-1986]	
ELECTROSTATIC PRECIPITATOR, NO. 3, SMOG HOG, MODEL SH-10-PE, TWO STAGE, PENNEY TYPE, 60 KW A/N: 122507	C29	D15 D16			D323.1
TANK, UNIT NO. 4, TURBINE LUBE OIL RESERVOIR A/N: 122508	D17	C30		PM: (9) [RULE 404,2-7-1986]	
TANK, UNIT NO. 4, TURBINE GOVERNOR OIL RESERVOIR A/N: 122508	D18	C30		PM: (9) [RULE 404,2-7-1986]	



Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

Denotes NSR applicability limit (7)

(9) See App B for Emission Limits (2)(2A)(2B) Denotes RECLAIM emission rate

Denotes BACT emission limit (4)

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS,etc.) See Section J for NESHAP/MACT requirements

(10)

Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

Section D

Facility I.D.: Revision #: Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 3 : PETROLEUM S	TORAG	E			
ELECTROSTATIC PRECIPITATOR, NO. 4, SMOG HOG, MODEL SH-10-PE, TWO STAGE, PENNEY TYPE, 60 KW A/N: 122508	C30	D17 D18			D323.1
TANK, UNIT NO. 5, TURBINE LUBE OIL RESERVOIR A/N: 122509	D19	C31		PM: (9) [RULE 404,2-7-1986]	
ELECTROSTATIC PRECIPITATOR, NO. 5, SMOG HOG, MODEL SH-10-PE, TWO STAGE, PENNEY TYPE, 60 HP A/N: 122509	C31	D19			D323.1
TANK, UNIT NO. 6, TURBINE LUBE OIL RESERVOIR A/N: 122510	D100	C32		PM: (9) [RULE 404,2-7-1986]	
ELECTROSTATIC PRECIPITATOR, NO. 6, SMOG HOG, MODEL SH-10-PE, TWO STAGE, PENNEY TYPE, 60 KW A/N: 122510	C32	D100			D323.1
Process 4 : EMERGENCY F	OWER	+			
INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, ALCO, MODEL 251, 16 CYLINDERS, WITH AFTERCOOLER, TURBOCHARGER, 2500 HP WITH A/N: 410740	D53		NOX: PROCESS UNIT**	NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,5-11- 2001;RULE 2012,12-5-2003]; PM: (9) [RULE 404,2-7-1986]	C1.3, C177.1, D12.5, E116.1, K67.5
GENERATOR, 2000 KW				·	

(1)(1A)(1B) Denotes RECLAIM emission factor

Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

Denotes NSR applicability limit (7)

See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

Denotes air toxic control rule limit (6)

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)

See Section J for NESHAP/MACT requirements (10)

Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

Section D Page: 18 Facility I.D.: 800074 Revision #: DRAFT April 24, 2008 Date:

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 5 : ABRASIVE BLA	STING				
ABRASIVE BLASTING, OPEN, KELCO, MODEL 124, 600 LBS CAPACITY, TWO NOZZLES, DIAMETER: 0.313 IN A/N: 123171	D56			PM: (9) [RULE 1140,8-2- 1985; RULE 405,2-7-1986]	D323.2
Process 6 : BULK TERMINA	ALS				
SUMP, RAINWATER, UNDERGROUND, 420 BBL; WIDTH: 17 FT 6 IN; DEPTH: 7 FT 9 IN; LENGTH: 17 FT 6 IN A/N: 189814	D69				
Process 7: R-219 EXEMPT	EQUIPM	IENT SUBJI	ECT TO SOURC	E-SPECIFIC RULES	
RULE 219 EXEMPT EQUIPMENT, ABRASIVE BLASTING EQUIPMENT, GLOVE-BOX, < = 53 FT3, WITH DUST FILTER	E112			PM: (9) [<i>RULE 1140,8-2-1985</i> ; RULE 404,2-7-1986; RULE 405,2-7-1986]	D322.1, D381.1, K67.1
RULE 219 EXEMPT EQUIPMENT, AIR CONDITIONING UNITS	E113				H23.5
RULE 219 EXEMPT EQUIPMENT, REFRIGERATION UNITS	E114				H23.6
RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, PORTABLE, ARCHITECTURAL COATINGS	E124			ROG: (9) [RULE 1113,11-8- 1996; RULE 1113,5-14-1999; RULE 1171,11-7-2003; RULE 1171,5-6- 2005]	K67.3

Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7)Denotes NSR applicability limit

See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

Denotes BACT emission limit (4)

Denotes air toxic control rule limit (6)

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)

See Section J for NESHAP/MACT requirements (10)

⁽¹⁾⁽¹A)(1B) Denotes RECLAIM emission factor

Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

Section D Page: 19
Facility I.D.: 800074
Revision #: DRAFT
Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: DEVICE ID INDEX

The following sub-section provides an index to the devices that make up the facility description sorted by device ID.

Section D Page: 20 Facility I.D.: 800074 Revision #: DRAFT Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: DEVICE ID INDEX

·	Device Index For Sec		
Device ID	Section D Page No.	Process	System
D1	1	1	1
D4	2	1	1
D7	3	1	1
D9 .	5	1	1
D11	15	3	C
D12	15	3	C
D13	16	3	C
D14	16	3	C
D15	16	3	C
D16	16	3	C
D17	16	3	·C
D18	16	3	C
D19	17	3	C
D21	14	2	C
D22	14	2	C
D25	14	2	(
D26	14	2	C
C27	16	3	C
C28	16	3	
C29	16	3	C
C30	17	3	C
C31	17	3	C
C32	17	3	(
D34	12	2	(
D35	13	2	
D36	13	2	C
D37	13	2	. (
D38	13	2	(
D39	13	2	(
C40	13	2	(
C41	13	2	(
D44	14	3	(
D46	15	3	(
D47	15	3	(
D48	15	3	(
D49	15	3 .	(

Section D Page: 21 Facility I.D.: 800074 Revision #: DRAFT Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: DEVICE ID INDEX

	Device Index For Sec		
Device ID	Section D Page No.	Process	System
D50	15	3	0
D53	17	4	0
D56	18	5	0
D69	18	6	0
C73	1	1	1
C74	2	1	1
C75	3	1	1
C76	3	1	1
C77	4	1	1
C78	4	1	1
S96	2	1	1
S97	3	1	1
S98	4	1	1
S99	5	1	1
D100	17	3	C
E112	18	7	C
E113	18	7	C
E114	18	7	C
E124	18	7	C
D125	5	1	2
D129	7	1	2
C130	8	1	2
C131	9	1	2
S133	8	1	
D134	9	1	2
C138	12	. 1	2
C139	12	1	2
S141	12	1	2
D142	11	1	2

Page: 22 800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

FACILITY CONDITIONS

- F9.1 Except for open abrasive blasting operations, the operator shall not discharge into the atmosphere from any single source of emissions whatsoever any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
 - (a) As dark or darker in shade as that designated No.1 on the Ringelmann Chart, as published by the United States Bureau of Mines; or
 - (b) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in subparagraph (a) of this condition.

[RULE 401, 3-2-1984; RULE 401, 11-9-2001]

F14.1 The operator shall not use fuel oil containing sulfur compounds in excess of 0.05 percent by weight.

The .05 percent sulfur limit shall not apply to existing supplies of any liquid fuel in storage as of October 1, 1993 until such supply is exhausted.

[RULE 431.2, 5-4-1990; RULE 431.2, 9-15-2000]

F14.2 The operator shall not purchase fuel oil containing sulfur compounds in excess of 15 ppm by weight as supplied by the supplier.

This condition shall become effective on or after June 1, 2004.

[RULE 431.2, 9-15-2000]

F16.1 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

purchase records of fuel oil and sulfur content of the fuel

[RULE 3004(a)(4)-Periodic Monitoring, 8-11-1995; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

Page: 23 800074 DRAFT April 24, 2008

Date:

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

F18.1 Acid Rain SO2 Allowance Allocation for affected units are as follows:

Device ID	Boiler ID	Contaminant	Tons in any year
1	Boiler No. 1	SO2	677
4	Boiler No. 2	SO2	335
71	Boiler No. 3	SO2	1234
5	Boiler No. 4	SO2	994
7	Boiler No. 5	SO2	1391
9	Boiler No. 6	SO2	1516

- The allowance allocation(s) shall apply to calendar years 2000 through 2009.
- The number of allowances allocated to Phase II affected units by U.S. EPA may change in a 1998 revision to 40CFR73 Tables 2,3, and 4. In addition, the number of allowances actually held by an affected source in a unit account may differ from the number allocated by U.S. EPA. Neither of the aforementioned conditions necessitate a revision to the unit SO2 allowance allocations identified in this permit (see 40 CFR 72.84)

[40CFR 73 Subpart B, 1-11-1993]

- F24.1 Accidental release prevention requirements of Section 112(r)(7):
 - The operator shall comply with the accidental release prevention requirements pursuant to 40 CFR Part 68 and shall submit to the Executive Officer, as a part of an annual compliance certification, a statement that certifies compliance with all of the requirements of 40 CFR Part 68, including the registration and submission of a risk management plan (RMP).
 - The operator shall submit any additional relevant information requested by the Executive Officer or designated agency.

[40CFR 68 - Accidental Release Prevention, 5-24-1996]

DEVICE CONDITIONS

A. Emission Limits

Page: 24 800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

A63.2 The operator shall limit emissions from this equipment as follows:

CONTAMINANT	EMISSIONS LIMIT
CO	Less than or equal to 18842 LBS IN ANY ONE MONTH
PM10	Less than or equal to 10784 LBS IN ANY ONE MONTH
VOC	Less than or equal to 4409 LBS IN ANY ONE MONTH
SOX	Less than or equal to 327 LBS IN ANY ONE MONTH

The operator shall calculate the emission limit(s) by using calendar monthly fuel use data and the following emission factors: Natural Gas: PM10 = 7.50 lbs/MMscf, VOC = 2.58 lbs/MMscf, and SOx = 0.21 lbs/MMscf. Diesel Fuel: PM10 = 1.67 lbs/Mgal, VOC = 0.52 lbs/Mgal, and SOx = 0.21 lbs/Mgal.

The operator shall calculate the emission limit(s), after the CO CEMS certification, based on the readings from the certified CO CEMS. In the event the CO CEMS is not operating, has been certification tested but is not certified, or the emissions exceed the valid upper range of the analyzer, the emissions shall be calculated in accordance with the approved CEMS plan. During diesel readiness testing, the CO shall be calculated using the fuel use data and a 24.2 lbs/Mgal emission factor

The operator shall calculate the emission limit(s) for CO in the absence of valid CEMS data, by using the monthly fuel use data and the following factor: Natural Gas: 9.03 lbs/MMscf

For the purposes of this condition, the limit(s) shall be based on the total combined emissions from combined cycle gas turbine No. 10 and it's associated duct burner during any calendar month. The duct burner shall not be operated when the turbine is firing diesel fuel.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition: D134, D142]

Page: 25 800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

A63.3 The operator shall limit emissions from this equipment as follows:

CONTAMINANT	EMISSIONS LIMIT
CO	Less than or equal to 18842 LBS IN ANY ONE MONTH
PM10	Less than or equal to 10784 LBS IN ANY ONE MONTH
VOC	Less than or equal to 4409 LBS IN ANY ONE MONTH
SOX	Less than or equal to 327 LBS IN ANY ONE MONTH

The operator shall calculate the emission limit(s) by using calendar monthly fuel use data and the following emission factors: Natural Gas: PM10 = 7.50 lbs/MMscf, VOC = 2.58 lbs/MMscf, and SOx = 0.21 lbs/MMscf. Diesel Fuel: PM10 = 1.67 lbs/Mgal, VOC = 0.52 lbs/Mgal, and SOx = 0.21 lbs/Mgal.

The operator shall calculate the emission limit(s), after the CO CEMS certification, based on the readings from the certi ed CO CEMS. In the event the CO CEMS is not operating, has been certification tested but is not certified, or the emissions exceed the valid upper range of the analyzer, the emissions shall be calculated in accordance with the approved CEMS plan. During diesel readiness testing, the CO shall be calculated using the fuel use data and a 24.2 lbs/Mgal emission factor

For the purposes of this condition, the limit(s) shall be based on the total combined emissions from combined cycle gas turbine No. 9 and it's associated duct burner during any calendar month. The duct burner shall not be operated when the turbine is firing diesel fuel.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition: D125, D129]

A99.1 The 10 PPM NH3 emission limit(s) shall not apply when ammonia injection has not commenced. (NH3 emissions).

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition: C73, C75]

Page: 26 800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

A99.2 The 2 PPM NOX emission limit(s) shall not apply during turbine startups, diesel readiness testing, or shutdowns. Shutdowns shall not exceed 30 minutes/event. Written records of startups and shutdowns shall be maintained and made available to the AQMD upon request.

For the purposes of this condition, cold start up shall be defined as a start up which occurs after the steam turbine has been shutdown for 72 hours or more. A non-cold start up shall be defined as a start up which occurs after the steam turbine has been shutdown for less than 72 hours. The beginning of start up occurs at initial fire in the combustor and the end of start up occurs when the BACT levels are achieved. No more than one turbine shall be in cold start-up mode at any one time. The turbines shall not be started on diesel fuel.

For the purposes of this condition, steam turbine shutdown period shall be defined as the number of hours between the closing and reopening of the steam stop valve. The operator shall keep records of the date and time of the steam stop valve opening and closing, and make these records available to AQMD personnel upon request.

[RULE 2005, 5-6-2005]

[Devices subject to this condition: D125, D129, D134, D142]

A99.3 The 4 PPM CO emission limit(s) shall not apply during turbine startups, diesel readiness testing, or shutdowns. Shutdowns shall not exceed 30 minutes/event. Written records of startups and shutdowns shall be maintained and made available to the AQMD upon request.

For the purposes of this condition, cold start up shall be defined as a start up which occurs after the steam turbine has been shutdown for 72 hours or more. A non-cold start up shall be defined as a start up which occurs after the steam turbine has been shutdown for less than 72 hours. The beginning of start up occurs at initial fire in the combustor and the end of start up occurs when the BACT levels are achieved. No more than one turbine shall be in cold start-up mode at any one time. The turbines shall not be started on diesel fuel.

For the purposes of this condition, steam turbine shutdown period shall be defined as the number of hours between the closing and reopening of the steam stop valve. The operator shall keep records of the date and time of the steam stop valve opening and closing, and make these records available to AQMD personnel upon request.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition: D125, D129, D134, D142]

Page: 27 800074 DRAFT

Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

A195.1 The 2 PPMV NOX emission limit(s) is averaged over 60 minutes at 15 percent oxygen, dry.

[RULE 2005, 5-6-2005]

[Devices subject to this condition: D125, D129, D134, D142]

A195.2 The 4 PPMV CO emission limit(s) is averaged over 60 minutes, at 15 percent oxygen, dry.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition: D125, D129, D134, D142]

A195.3 The 2 PPMV VOC emission limit(s) is averaged over 60 minutes, at 15 percent oxygen, dry. The limit does not apply during diesel readiness tests.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition: D125, D129, D134, D142]

A195.4 The 5 PPMV NH3 emission limit(s) is averaged over 60 minutes at 15 percent O2 dry. The operator shall calculate and continuously record the NH3 slip concentration using the following: NH3(ppmv)=[ab*c/1E6]*1E6/b, where a=NH3 injection rate (lb/hr)/17 (lb/lb/mole), b=dry exhaust gas flow rate (lb/hr)/29(lb/lb/mole), and c=change in measured NOx across the SCR (ppmvd at 15 percent O2). The operator shall install and maintain a NOx analyzer to measure the SCR inlet NOx ppm accurate to within +/- 5 percent calibrated at least once every 12 months.

> The operator shall use the method described above or another alternative method approved by the Executive Officer.

> The ammonia slip calculation procedures described above shall not be used for compliance determination or emission information determination without corroborative data using an approved reference method for the determination of ammonia.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition: C131, C139]

Page: 28 800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

A195.5 The 5 PPMV NOX emission limit(s) is averaged over 720 operating hours (heat input weighted average).

A data acquisition system shall be installed and maintained to continuously calculate and record the NOx ppm based on the 720 operating hour average.

The average shall be calculated based on emissions during all boiler operating hours except during:

startups defined as whenever the unit is being brought up to normal operating temperature from an inactive status and the exhaust temperature entering the SCR catalyst is less than 530 degrees F;

shutdowns defined as whenever the unit is allowed to cool from a normal operating temperature to inactive status and the exhaust temperature entering the SCR catalyst is less than 530 degrees F;

calibration and maintenance periods, Part 75 linearity testing, RATA testing, equipment breakdown periods as defined in Rule 2004, and periods of zero fuel flow.

The heat input weighted average NOx concentration shall be calculated using the following equation, or other equivalent equation.

PPMV(3%O2) = (Et/Qt)*K; where PPMV(3%O2) = the concentration of NOx in PPMV at 3%O2; K = a conversion factor from lbs/MMBtu to PPM, which can be determined using EPA 40 CFR60 Method 19. The default K value is 819; Et = Total reported NOx emissions during the averaging period including emissions reported as a result of missing data procedures pursuant to Rule 2012; Qt = Total heat input during the averaging period.

[RULE 2009, 5-11-2001]

[Devices subject to this condition: D1, D4, D7]

A327.1 For the purpose of determining compliance with District Rule 475, combustion contaminant emissions may exceed the concentration limit or the mass emission limit listed, but not both limits at the same time.

[RULE 475, 10-8-1976; RULE 475, 8-7-1978]

[Devices subject to this condition: D125, D129, D134, D142]

Page: 29 800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

A433.1 The operator shall comply at all times with the 2.0 ppm 1 hour BACT limit for NOx, except as specified in Conditions A99.2, and for the following operating scenarios::

Operating Scenario	Maximum Hourly Emission Limit	Operational Limit
Cold Start Non-Cold Start	225 lbs/hr 170 lbs/hr	NOx emissions not to exceed 600 lbs total per cold start. Cold start not to exceed 360 minutes total, 4 starts per month, and 48 starts per year per turbine NOx emissions not to exceed 300 lbs total per non cold start. Non cold start not to exceed
		180 minutes total, 27 starts per month, and 324 starts per year per turbine

[RULE 2005, 5-6-2005]

[Devices subject to this condition: D125, D129, D134, D142]

B. Material/Fuel Type Limits

B22.2 The operator shall not use this equipment with materials having a(n) true vapor pressure of 1.5 psia or greater under actual operating conditions.

[RULE 463, 3-11-1994]

[Devices subject to this condition: D44]

Page: 30 800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

B59.1 The operator shall only use the following material(s) in this device :

Air preheater elements that are made of corrosion resistant stainless steel, type 409 or equivalent

A gunite lining in the flue gas duct surfaces between the air preheaters and exhaust stack, except for the turning vanes, expansion joints, and related parts

[RULE 401, 3-2-1984; RULE 401, 11-9-2001]

[Devices subject to this condition: D1, D4, D7, D9]

B75.1 The operator shall not use fuel oil in this equipment except under the following circumstance(s):

Interruption in natural gas service due to unforeseeable failure, malfunction, or natural disaster, not resulting from an intentional or negligent act or omission on the part of the owner or operator

For diesel fuel readiness testing not to exceed 60 minutes per turbine per month.

Fuel oil shall be low nitrogen, low sulfur diesel. Sulfur content shall not exceed 15 ppm by weight, or other more stringent limit specified in Rule 431.2. The operator shall keep records of the date diesel was used, the amount of diesel used, and the reason for use. These records shall be kept for a minimum of 5 years and be made available for AQMD inspection upon request.

Vendor specification for the initial and each subsequent shipment of diesel shall be maintained to verify sulfur and nitrogen content. If the vendor information is not available, the operator shall have a sample of each shipment of fuel analyzed by an independent lab for sulfur and nitrogen concentration. These records shall be kept for a minimum of 5 years and be made available for AQMD inspection upon request.

For the above circumstances, diesel fuel shall not be used in this equipment unless water injection is fully employed.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 2005, 4-9-1999; RULE 2005, 4-20-2001]

[Devices subject to this condition: D125, D129, D134, D142]

C. Throughput or Operating Parameter Limits

Page: 31 800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

C1.2 The operator shall limit the throughput to no more than 561 lb(s)/hr.

For the purpose of this condition, throughput shall be defined as the ammonia injection rate which is monitored by condition number 12-3.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition: C73, C75]

C1.3 The operator shall limit the operating time to no more than 199 hour(s) in any one year.

The 199 hours per year shall include no more than 20 hours in any one year for maintenance and testing purposes.

The operation of the engine beyond the 20 hr/yr allotted for engine maintenance and testing shall be allowed only in the event of a loss of grid power or up to 30 minutes prior to a rotating outage, provided that the grid operator or electric utility has ordered rotating outages in the control area where the engine is located or has indicated that it expects to issue such an order at a certain time, and the engine is located in a utility service block that is subject to the rotating outage.

Engine operation shall be terminated immediately after the utility distribution company advises that a rotating outage is no longer imminent or in effect.

[RULE 1110.2, 11-14-1997; RULE 1470, 6-1-2007; RULE 2012, 5-11-2001; RULE 2012, 12-5-2003]

[Devices subject to this condition: D53]

C8.1 The operator shall use this equipment in such a manner that the flow rate being monitored, as indicated below, is not less than 2.5 gpm.

To comply with this condition, the operator shall monitor the flow rate as specified in condition number 12-1.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition: C40, C41]

Page: 32 800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

C157.1 The operator shall install and maintain a pressure relief valve set at 15 psig.

[RULE 402, 5-7-1976]

[Devices subject to this condition: D34, D35, D36, D37, D38, D39]

C177.1 The operator shall set and maintain the fuel injection timing of the engine at 4 degrees retarded relative to standard timing.

[RULE 2009, 5-11-2001]

[Devices subject to this condition: D53]

D. Monitoring/Testing Requirements

D12.1 The operator shall install and maintain a(n) flow meter to accurately indicate the flow rate of the incoming scrubbing (city) water.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition: C40, C41]

D12.2 The operator shall install and maintain a(n) temperature gauge to accurately indicate the temperature at the inlet of each selective catalytic reduction reactor.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 2012, 5-11-2001; RULE 2012, 12-5-2003]

[Devices subject to this condition: C73, C75, C77]

Page: 33 800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D12.3 The operator shall install and maintain a(n) continuous monitoring system to accurately indicate the ammonia injection rate of the ammonia injection system.

The operator shall also install and maintain a device to continuously record the parameter being measured.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition: C73, C75, C77]

D12.5 The operator shall install and maintain a(n) non-resettable elapsed time meter to accurately indicate the elapsed operating time of the engine.

[RULE 1110.2, 11-14-1997; RULE 2012, 5-11-2001; RULE 2012, 12-5-2003]

[Devices subject to this condition: D53]

D12.6 The operator shall install and maintain a(n) temperature gauge to accurately indicate the temperature in the exhaust at the inlet to the SCR reactor.

The operator shall also install and maintain a device to continuously record the parameter being measured.

The measuring device or gauge shall be accurate to within plus or minus 5 percent. It shall be calibrated once every 12 months.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 2012, 5-11-2001; RULE 2012, 12-5-2003]

[Devices subject to this condition: C131, C139]

Page: 34 800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D12.7 The operator shall install and maintain a(n) pressure gauge to accurately indicate the differential pressure across the SCR catalyst bed in inches of water column.

The operator shall also install and maintain a device to continuously record the parameter being measured.

The measuring device or gauge shall be accurate to within plus or minus 5 percent. It shall be calibrated once every 12 months.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 2012, 5-11-2001; RULE 2012, 12-5-2003]

[Devices subject to this condition: C131, C139]

D12.8 The operator shall install and maintain a(n) continuous monitoring system to accurately indicate the ammonia injection rate of the ammonia injection system.

The operator shall also install and maintain a device to continuously record the parameter being measured.

The measuring device or gauge shall be accurate to within plus or minus 5 percent. It shall be calibrated once every 12 months.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition: C131, C139]

Page: 35 800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D28.2 The operator shall conduct source test(s) in accordance with the following specifications:

The test shall be conducted to determine the PM emissions using District method 5.1 measured over a 60 minute averaging time period.

The test shall be conducted to determine the NH3 emissions using District method 207.1 measured over a 60 minute averaging time period.

The test shall be conducted to determine the NH3 emissions using either District method 5.3 or EPA method 17 measured over a 60 minute averaging time period.

Source test shall be conducted when this equipment is using fuel oil.

Source test shall be conducted when this equipment is operating at loads of 100 percent, 75 percent, 50 percent, and the minimum load at which ammonia injection commences in the SCR reactor.

The District shall be notified of the date and time of the test at least 14 days prior to the test.

The test shall be conducted using a certified continuous emissions monitoring system to measure the emissions of NOx and CO.

The test shall be conducted by a testing laboratory certified by the California Air Resources Board in the required test methods for each criteria pollutant to be measured, and in compliance with District Rule 304 (no conflict of interest).

The test shall be conducted during the next fuel oil readiness testing.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 2012, 5-11-2001; RULE 2012, 12-5-2003]

[Devices subject to this condition: C73, C75, C77]

Page: 36 800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D28.3 The operator shall conduct source test(s) in accordance with the following specifications:

The test shall be conducted quarterly during the first 12 months after the initial source test, and once a year thereafter.

The District shall be notified of the date and time of the test at least 7 days prior to the test.

Source test shall be conducted when this equipment is using natural gas.

The test shall be conducted by a testing laboratory certified by the California Air Resources Board in the required test methods, and in compliance with District Rule 304 (no conflict of interest).

The test shall be conducted to determine the NH3 emissions using District method 207.1 measured over a 60 minute averaging time period.

The test shall be conducted to determine the NH3 emissions using either District method 5.3 or EPA method 17 measured over a 60 minute averaging time period.

The test shall be conducted when the equipment is operating at 80 percent load or greater.

The test shall be conducted and the results submitted to the District within 45 days after the test date.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition: C73, C75, C77]

Page: 37 800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D29.2 The operator shall conduct source test(s) for the pollutant(s) identified below.

Pollutant(s) to be tested	Required Test Method(s)	Averaging Time	Test Location
NH3 emissions	District method 207.1 and 5.3 or EPA method 17	1 hour	Outlet of the SCR serving this equipment

The test(s) shall be conducted at least once each calendar quarter during the first 12 months of operation and at least annually thereafter. The NOx concentration, as determined by the CEMS, shall be simultaneously recorded during the ammonia slip test. If the CEMS is inoperable, a test shall be conducted to determine the NOx emissions using District Method 100.1 measured over a 60 minute averaging time period.

The test shall be conducted to demonstrate compliance with the Rule 1303 concentration limit.

The test shall be conducted when the equipment is operating at 80 percent load or greater.

The test shall be conducted and the results submitted to the AQMD permitting engineer within 45 days after the test date.

The test shall be conducted during natural gas firing.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition: C131, C139]

Page: 38 800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D29.4 The operator shall conduct source test(s) for the pollutant(s) identified below.

Pollutant(s) to be tested	Required Test Method(s)	Averaging Time	Test Location
SOX emissions	Approved District method	District-approved averaging time	Fuel sample
ROG emissions	Approved District method	1 hour	Outlet of the SCR serving this equipment
PM10 emissions	District method 5.2	District-approved averaging time	Outlet of the SCR serving this equipment

The test(s) shall be conducted at least once every three years.

For gas turbines only the VOC test shall use the following method: a) Stack gas samples are extracted into Summa canisters, maintaining a final canister pressure between 400-500 mm Hg absolute, b) Pressurization of Summa canisters is done with zero gas analyzed/certified to having less than 0.05 ppmv total hydrocarbons as carbon, and c) Analysis of Summa canisters is per EPA Method TO-12 (with pre-concentration) and the canisters temperature when extracting samples for analysis is not to be below 70 deg F.

The use of this alternative VOC test method is solely for the determination of compliance with the VOC BACT level of 2.0 ppmv calculated as carbon for natural gas fired turbines. Because the BACT level was set using data derived from various source test methods, this alternate method provides a fair comparison and represents the best sampling and analysis technique for this purpose at this time. The test results must be reported with two significant digits.

The test shall be conducted and the results submitted to the AQMD within 60 days after the test date. The AQMD shall be notified of the date and time of the test at least 7 days prior to the test.

The test shall be conducted to demonstrate compliance with the Rule 1303 concentration and emissions limit.

The test shall be conducted when the turbine and duct burner are operating simultaneously at 100 percent of full rated load, when the turbine is operating alone at 100 percent of full rated load, and when the turbine is operating alone at 75 and 50 percent of full rated load for NOx, CO, ROG, and NH3 source tests.

The test shall be conducted when firing natural gas.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

Page: 39 800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D29.5 The operator shall conduct source test(s) for the pollutant(s) identified below.

Pollutant(s) to be tested Required Test Method(s)		Averaging Time	Test Location	
NOX emissions	District method 100.1	30 minutes	Outlet of the SCR serving this equipment	

The test shall be conducted when the unit is firing diesel fuel in order to determine the emissions profile of the unit. A minimum of 6 tests shall be performed and the operator shall record the turbine output, ammonia injection rate, and temperature of the exhaust during each test, based on a 30 minute averaging time. Test results shall also include the fuel flow rate (CFH), the flue gas flow rate, and the duct burner fuel use during the test.

The test shall be conducted in order to generate a load curve for NOx (lbs/MW) vs. MW output over the span of tested loads. The operator may, after receiving approval from the AQMD, use this curve to report NOx emissions during the monthly 60 minute (total) diesel readiness testing periods.

[RULE 2012, 5-6-2005]

Page: 40 800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D82.1 The operator shall install and maintain a CEMS to measure the following parameters:

CO concentration in ppmv

Concentrations shall be corrected to 15 percent oxygen on a dry basis.

The CEMS will convert the actual CO concentrations to mass emission rates (lbs/hr) and record the hourly emission rates on a continuous basis.

The CEMS shall be installed and operated no later than 90 days after initial start up of the turbine, and in accordance with an approved AQMD Rule 218 CEMS plan application. The operator shall not install the CEMS prior to receiving initial approval from AQMD. Within two weeks of the turbine start up date, the operator shall provide written notification to the AQMD of the exact start up.

The CEMS shall be installed and operated to measure CO concentration over a 15 minute averaging time period.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 218, 8-7-1981; RULE 218, 5-14-1999]

[Devices subject to this condition: D125, D129, D134, D142]

D82.2 The operator shall install and maintain a CEMS to measure the following parameters:

NOX concentration in ppmv

Concentrations shall be corrected to 15 percent oxygen on a dry basis.

The CEMS shall be installed and operated no later than 12 months after initial start up of the turbine and shall comply with the requirements of Rule 2012. During the interim period between the initial start up and the provisional certification date of the CEMS, the operator shall comply with the monitoring requirements of Rule 2012(h)(2) and 2012(h)(3). Within two weeks prior to the turbine start up date, the operator shall provide written notification to the AQMD of the exact date of start up.

[RULE 2012, 5-6-2005]

Page: 41 800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D182.1 The operator shall test this equipment in accordance with the following specifications:

The operator shall collect samples using a 1983 District-approved induct fallout monitor (IFM) every 24 hours beginning from all startups, except for natural gas firing, where if three 24-hour IFM samples show no abnormal collection, subsequent samples can be taken once a week.

The operator shall analyze the IFM samples for acidity, weight, increase of particle size, volume, and appearance, and use the results of the analysis to determine the necessary operational changes to minimize the fallouts, such as, but not limited to, increasing the fuel oil additives and lancing frequencies.

[RULE 401, 3-2-1984; RULE 401, 11-9-2001]

[Devices subject to this condition: D1, D4, D7, D9]

D322.1 The operator shall perform annual inspection of the equipment and filter media for leaks, broken or torn filter media, and improperly installed filter media.

[RULE 3004(a)(4)-Periodic Monitoring, 8-11-1995; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition: E112]

Page: 42 800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D323.1 The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on a daily basis, at least, unless the equipment did not operate during the entire daily period. The routine daily inspection shall be conducted while the equipment is in operation and during daylight hours.

If any visible emissions (not including condensed water vapor) are detected that last more than three minutes in any one hour, the operator shall verify and certify within 24 hours that the equipment causing the emission and any associated air pollution control equipment are operating normally according to their design and standard procedures and under the same conditions under which compliance was achieved in the past, and either:

- 1). Take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in Section K of this permit; or
- 2). Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB manual "Visible Emission Evaluation", within three business days and report any deviations to AQMD. SUGGESTED CHAR

The operator shall keep the records in accordance with the recordkeeping requirements in Section K of this permit and the following records:

- 1). Stack or emission point identification;
- 2). Description of any corrective actions taken to abate visible emissions;
- 3). Date and time visible emission was abated; and
- 4). All visible emission observation records by operator or a certified smoke reader.

[RULE 3004(a)(4)-Periodic Monitoring, 8-11-1995; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition: C27, C28, C29, C30, C31, C32]

Page: 43 800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D323.2 The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on a semi-annual basis, at least, unless the equipment did not operate during the entire semi-annual period. The routine semi-annual inspection shall be conducted while the equipment is in operation and during daylight hours.

If any visible emissions (not including condensed water vapor) are detected that last more than three minutes in any one hour, the operator shall verify and certify within 24 hours that the equipment causing the emission and any associated air pollution control equipment are operating normally according to their design and standard procedures and under the same conditions under which compliance was achieved in the past, and either:

- 1). Take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in Section K of this permit; or
- 2). Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB manual "Visible Emission Evaluation", within three business days and report any deviations to AQMD.

The operator shall keep the records in accordance with the recordkeeping requirements in Section K of this permit and the following records:

- 1). Stack or emission point identification;
- 2). Description of any corrective actions taken to abate visible emissions;
- 3). Date and time visible emission was abated; and
- 4). All visible emission observation records by operator or a certified smoke reader.

[RULE 3004(a)(4)-Periodic Monitoring, 8-11-1995; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition: D56]

Page: 44 800074 DRAFT April 24, 2008

Date:

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D371.1 The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever this equipment has combusted one million gallons of diesel fuel, to be counted cumulatively over a five year period. The inspection shall be conducted while the equipment is in operation and during daylight hours. If any visible emissions (not including condensed water vapor) are detected, the operator shall:

Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB manual "Visible Emission Evaluation", within three working days (or during the next fuel oil firing period if the unit ceases firing on fuel oil within the three working day time frame) and report any deviations to AQMD.

In addition, the operator shall keep the records in accordance with the recordkeeping requirements in Section K of this permit and the following records:

- Stack or emission point identification; a).
- b). Description of any corrective actions taken to abate visible emissions;
- c). Date and time visible emission was abated; and
- d). Visible emission observation record by a certified smoke reader.

[RULE 3004(a)(4)-Periodic Monitoring, 8-11-1995; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition: D1, D4, D7, D9]

- D372.1 The operator shall determine compliance with the particulate matter (PM) emission limit by conducting a source test at the outlet of the exhaust stack annually using AQMD Method 5.1. Each test shall include:
 - (a) One test using natural gas operating at minimum load under normal operating conditions, if natural gas is burned more than 120 consecutive hours or 200 hours accumulated over any 12 consecutive months. The test shall be conducted no later than six months after the time limit has been exceeded;
 - (b) One test using natural gas operating at maximum load under normal operating conditions, if natural gas is burned more than 120 consecutive hours or 200 hours accumulated over any 12 consecutive months. The test shall be conducted no later than six months after the time limit has been exceeded;
 - (c) One test using fuel oil operating at maximum load under normal operating conditions, if fuel oil is burned more than 120 consecutive hours or 200 hours accumulated over any twelve consecutive months. The test shall be conducted no later than six months after the time limit has been exceeded.

[RULE 3004(a)(4)-Periodic Monitoring, 8-11-1995; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

Page: 45 800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D381.1 The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on an annual basis, at least, unless the equipment did not operate during the entire annual period. The routine annual inspection shall be conducted while the equipment is in operation and during daylight hours. If any visible emissions (not including condensed water vapor) are detected, the operator shall take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in Section K of this permit.

The operator shall keep the records in accordance with the recordkeeping requirements in Section K of this permit and the following records:

- 1). Stack or emission point identification;
- 2). Description of any corrective actions taken to abate visible emissions; and
- 3). Date and time visible emission was abated.

[RULE 3004(a)(4)-Periodic Monitoring, 8-11-1995; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition: E112]

E. Equipment Operation/Construction Requirements

E57.1 The operator shall vent this equipment to the SCR and CO control whenever this equipment is in operation.

Ammonia injection shall be used at all times at an injection rate which minimizes NOx emissions whenever the exhaust temperature prior to the inlet of the SCR catalyst is 450 degrees F or greater as measured by the temperature gauge required by condition D12.6

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 2005, 4-20-2001; RULE 2005, 5-6-2005]

Page: 46 800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

- E73.1 Notwithstanding the requirements of Section E conditions, the operator shall not use ammonia injection if any of the following requirement(s) are met:
 - 1. Whenever the inlet exhaust temperature prior to the SCR reactor is less than 530 degrees Fahrenheit.
 - 2. Within the first 150 days (or other period approved in writing by the Executive Officer) after initial startup of the SCR system.

[RULE 2012, 5-11-2001; RULE 2012, 12-5-2003]

[Devices subject to this condition: C73, C75, C77]

E73.2 Notwithstanding the requirements of Section E conditions, the operator may, at his discretion, choose not to use ammonia injection if all of the following requirement(s) are met:

The inlet exhaust temperature to the SCR is 450 degrees F or less, not to exceed 360 minutes during a cold startup or 180 minutes during a non-cold startup.

During diesel readiness testing.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 2005, 4-9-1999; RULE 2005, 4-20-2001]

[Devices subject to this condition: C131, C139]

E116.1 This engine shall not be used as part of a demand response program using interruptible service contract in which a facility receives a payment or reduced rates in return for reducing its electric load on the grid when requested to do so by the utility or the grid operator.

[RULE 1470, 6-1-2007]

[Devices subject to this condition: D53]

E144.1 The operator shall vent this equipment, during filling, only to the vessel from which it is being filled.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition: D34, D35, D36, D37, D38, D39]

Page: 47 800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

E179.1 For the purpose of the following condition number(s), "continuous monitoring" shall be defined as measuring at least once every 15 minutes, except as allowed by Rule 2000.

Condition Number D 12-3

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition: C73, C75, C77]

E179.2 For the purpose of the following condition number(s), "continuously record" shall be defined as recording at least once every hour and shall be calculated based upon the average of the continuous monitoring for that hour.

Condition Number D 12-3

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 2012, 5-11-2001; RULE 2012, 12-5-2003]

[Devices subject to this condition: C73, C75, C77]

E179.3 For the purpose of the following condition number(s), continuously record shall be defined as recording at least once every hour and shall be calculated upon the average of the continuous monitoring for that month.

Condition Number D 12-7

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 2012, 5-11-2001; RULE 2012, 12-5-2003]

[Devices subject to this condition: C131, C139]

Page: 48 800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

E179.4 For the purpose of the following condition number(s), continuously record shall be defined as recording at least once every hour and shall be calculated upon the average of the continuous monitoring for that hour.

Condition Number D 12-6

Condition Number D 12-8

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 2012, 5-11-2001; RULE 2012, 12-5-2003]

[Devices subject to this condition: C131, C139]

E193.1 The operator shall upon completion of construction, operate and maintain this equipment according to the following specifications:

In compliance with all mitigation measures as stipulated by the "Statement of Findings, Statement of Overriding Considerations, and Mitigation Monitoring Plan" and final Environmental Impact Report dated July 16, 2002 (SCH No. 20011121013), and addendum to the FEIR

[CA PRC CEQA, 11-23-1970]

[Devices subject to this condition: D125, D129, D134, D142]

E193.5 The operator shall operate and maintain this equipment according to the following requirements:

The electrical output of Unit 6 shall be limited to 243 MW.

[RULE 1304(c)-Offset Exemption, 6-14-1996]

[Devices subject to this condition: D9]

Page: 49 800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

E202.1 The operator shall clean and maintain this equipment according to the following specifications:

The operator shall wash and/or vacuum and then inspect the boiler ducts, stack, and air preheaters during each shutdown in which a boiler is cooled. The operator shall reinspect and perform additional cleaning on these areas as necessary prior to startup.

The operator shall install and maintain a permanent stack washing system in the boiler stack

The operator shall wash the stack prior to start-up each time the boiler is shut down for 48 hours or more

[RULE 401, 3-2-1984; RULE 401, 11-9-2001]

[Devices subject to this condition: D1, D4, D7, D9]

E204.1 The operator shall employ the fuel oil additive system according to the following specifications:

The operator shall inject District-approved additives at a rate between 6,500 and 10,500 parts of oil per part of additive, based on volume.

The operator shall inject District-approved additives into the fuel oil whenever fuel oil is burned, as soon as fuel oil firing has stabilized.

The operator shall take corrective action as expeditiously as practicable if there is a failure to comply with either of the above requirements, so that compliance is achieved within 48 hours of such failure; the operator shall switch the unit to natural gas fuel, provided such fuel is available, if such failure is longer than 48 hours, and will remain on natural gas until such time as the failure is corrected.

The operator shall check the flow of fuel oil additive at least once a shift by recording the level of the additive in the holding tank.

[RULE 401, 3-2-1984; RULE 401, 11-9-2001]

[Devices subject to this condition: D1, D4, D7, D9]

Page: 50 800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

E204.2 The operator shall perform a boiler lancing according to the following specifications:

The operator shall cycle the boiler and air preheater lancing continuously while burning fuel oil and shall commence as soon as oil firing has stabilized; the operator shall continue the lancing cycle for the first 24 hours following a change from fuel oil to natural gas.

The operator shall cycle the air preheater lances and boiler lances once daily and once weekly, respectively, during periods of natural gas burning.

The operator shall repair and return to services individual lances as soon as practicable; the operator shall switch the unit to natural gas, provided such fuel is available, in the event that five or more lances are out of service simultaneously for more than 48 hours, and shall keep the unit on natural gas until such time as the repairs have been completed so that no more than two lances remain out of service.

[RULE 401, 3-2-1984; RULE 401, 11-9-2001]

[Devices subject to this condition: D1, D4, D7, D9]

H. Applicable Rules

H23.1 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
VOC	District Rule	463

[RULE 463, 3-11-1994]

[Devices subject to this condition: D44, D46, D47, D48, D49, D50]

Page: 51 800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

H23.5 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
Refrigerants	District Rule	1415

[RULE 1415, 10-14-1994]

[Devices subject to this condition: E113]

H23.6 This equipment is subject to the applicable requirements of the following rules or regulations:

Contaminant	Rule	Rule/Subpart
Refrigerants	40CFR82, SUBPART	В
Refrigerants	District Rule	1411

[RULE 1411, 3-1-1991; 40CFR 82 Subpart B, 7-14-1992]

[Devices subject to this condition: E114]

I. Administrative

Page: 52 800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

I296.1 This equipment shall not be operated unless the operator demonstrates to the Executive Officer that the facility holds sufficient RTCs to offset the prorated annual emissions increase for the first compliance year of operation. In addition, this equipment shall not be operated unless the operator demonstrates to the Executive Officer that, at the commencement of each compliance year after the first compliance year of operation, the facility holds sufficient RTCs in an amount equal to the annual emissions increase.

For purposes of this condition, the amount of RTCs to be held shall be 421,038 lbs NOx total for Turbines 9 and 10 and their associated duct burners. To comply with this condition, the operator shall limit the total compliance year NOx emissions to 421,038 lbs NOx for Turbines 9 and 10 and their associated duct burners

[RULE 2012, 5-6-2005]

[Devices subject to this condition: D125, D129, D134, D142]

K. Record Keeping/Reporting

800074

DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

K40.3 The operator shall provide to the District a source test report in accordance with the following specifications:

Source test results shall be submitted to the District no later than 60 days after the source test was conducted.

Emission data shall be expressed in terms of concentration (ppmv), corrected to 15 percent oxygen, dry basis.

All exhaust flow rate shall be expressed in terms of dry standard cubic feet per minute (DSCFM) and dry actual cubic feet per minute (DACFM).

All moisture concentration shall be expressed in terms of percent corrected to 15 percent oxygen.

Emission data shall be expressed in terms of mass rate (lbs/hr). In addition, solid PM emissions, if required to be tested, shall also be reported in terms of grains per DSCF.

Source test results shall also include fuel flow and exhaust gas rate under which the test was conducted.

Source test results shall also include turbine and generator output under which the test was conducted.

Emission data shall be expressed in terms of lbs/MM cubic feet.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 2005, 4-9-1999; RULE 2005, 4-20-2001]

[Devices subject to this condition: D125, D129, D134, D142]

K67.1 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

the name of the person performing the inspection and/or maintenance of the dust collector

the date, time and results of the inspection

the date, time and description of any maintenance or repairs resulting from the inspection

[RULE 3004(a)(4)-Periodic Monitoring, 8-11-1995; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition: E112]

Page: 54 800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

K67.2 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

The operator shall monitor and record on a daily basis the flowrate of the incoming scrubbing (city) water when this scrubber is operated

[RULE 3004(a)(4)-Periodic Monitoring, 8-11-1995; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition: C40, C41]

K67.3 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

For architectural applications where no thinners, reducers, or other VOC containing materials are added, maintain semi-annual records for all coating consisting of (a) coating type, (b) VOC content as supplied in grams per liter (g/l) of materials for low-solids coatings, (c) VOC content as supplied in g/l of coating, less water and exempt solvent, for other coatings.

For architectural applications where thinners, reducers, or other VOC containing materials are added, maintain daily records for each coating consisting of (a) coating type, (b) VOC content as applied in grams per liter (g/l) of materials used for low-solids coatings, (c) VOC content as applied in g/l of coating, less water and exempt solvent, for other coatings.

[RULE 3004(a)(4)-Periodic Monitoring, 8-11-1995; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition: E124]

- K67.4 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):
 - Natural gas and Diesel fuel usage after CEMS certification.

The date, time, duration, and CEMS minute data for start-ups. These records shall be maintained and made available upon request from AQMD

[RULE 2012, 5-6-2005]

Page: 55 800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

K67.5 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

An engine operating log listing on a monthly basis the emergency use hours of operation, maintenance and testing hours of operation, and any other hours of use with a description of the reasone for operation. Additionally, each time the engine is started manually, the log shall include the date of operation and the timer reading in hours at the beginning and end of operation

The log shall be kept for a minimum of three calendar years prior to the current year and be made available to District personnel upon request. The total hours of operation for the previous calendar year shall be recorded sometime during the first 15 days of January of each year

[RULE 1110.2, 6-3-2005; RULE 1304(a)-Modeling and Offset Exemption, 6-14-1996; RULE 1470, 6-1-2007]

[Devices subject to this condition: D53]

K171.1 The operator shall notify the District if any of the following situations occur:

When fuel oil is fired in this equipment

This notification shall be provided to the District no later than 48 hours after fuel oil is fired in this boiler.

[RULE 401, 3-2-1984; RULE 401, 11-9-2001]

[Devices subject to this condition: D1, D4, D7, D9]

SECTION E: ADMINISTRATIVE CONDITIONS

The operating conditions in this section shall apply to all permitted equipment at this facility unless superseded by condition(s) listed elsewhere in this permit.

- 1. The permit shall remain effective unless this permit is suspended, revoked, modified, reissued, denied, or it is expired for nonpayment of permit processing or annual operating fees. [201, 203, 209, 301]
 - a. The permit must be renewed annually by paying annual operating fees, and the permit shall expire if annual operating fees are not paid pursuant to requirements of Rule 301(d). [301(d)]
 - b. The Permit to Construct listed in Section H shall expire one year from the Permit to Construct issuance date, unless a Permit to Construct extension has been granted by the Executive Officer or unless the equipment has been constructed and the operator has notified the Executive Officer prior to the operation of the equipment, in which case the Permit to Construct serves as a temporary Permit to Operate. [202, 205]
 - c. The Title V permit shall expire as specified under Section K of the Title V permit. The permit expiration date of the Title V facility permit does not supercede the requirements of Rule 205. [205, 3004]
- 2. The operator shall maintain all equipment in such a manner that ensures proper operation of the equipment. [204]
- 3. This permit does not authorize the emissions of air contaminants in excess of those allowed by Division 26 of the Health and Safety Code of the State of California or the Rules and Regulations of the AQMD. This permit cannot be considered as permission to violate existing laws, ordinances, regulations, or statutes of other governmental agencies. [204]
- 4. The operator shall not use equipment identified in this facility permit as being connected to air pollution control equipment unless they are so vented to the identified air pollution control equipment which is in full use and which has been included in this permit. [204]
- 5. The operator shall not use any equipment having air pollution control device(s) incorporated within the equipment unless the air pollution control device is in full operation. [204]
- 6. The operator shall maintain records to demonstrate compliance with rules or permit conditions that limit equipment operating parameters, or the type or quantity of material processed. These records shall be made available to AOMD personnel upon request and be maintained for at least: [204]

SECTION E: ADMINISTRATIVE CONDITIONS

- a. Three years for a facility not subject to Title V; or
- b. Five years for a facility subject to Title V.
- 7. The operator shall maintain and operate all equipment to ensure compliance with all emission limits as specified in this facility permit. Compliance with emission limits shall be determined according to the following specifications, unless otherwise specified by AQMD rules or permit conditions: [204]
 - a. For internal combustion engines and gas turbines, measured concentrations shall be corrected to 15 percent stack-gas oxygen content on a dry basis and be averaged over a period of 15 consecutive minutes; [1110.2, 1134, 204]
 - b. For other combustion devices, measured concentrations shall be corrected to 3 percent stack-gas oxygen content on a dry basis and be averaged over a period of 15 consecutive minutes; [1146, 1146.1, 204]
 - c. For a large NOx source, compliance with a RECLAIM concentration limit shall be measured over a continuous 60 minutes for that source; [2012]
 - d. For non-combustion sources, compliance with emission limits shall be determined and averaged over a period of 60 minutes; [204]
 - e. For the purpose of determining compliance with Rule 407, carbon monoxide (CO) shall be measured on a dry basis and be averaged over 15 consecutive minutes, and sulfur compounds which would exist as liquid or gas at standard conditions shall be calculated as sulfur dioxide (SO2) and be averaged over 15 consecutive minutes; [407]
 - f. For the purpose of determining compliance with Rule 409, combustion contaminant emission measurements shall be corrected to 12 percent of carbon dioxide (CO2) at standard conditions and averaged over 15 consecutive minutes. [409]
 - g. For the purpose of determining compliance with Rule 475, combustion contaminant emission measurements shall be corrected to 3 percent of oxygen (O2) at standard conditions and averaged over 15 consecutive minutes or any other averaging time specified by the Executive Officer. [475]
- 8. All equipment operating under the RECLAIM program shall comply concurrently with all provisions of AQMD Rules and Regulations, except those listed in Table 1 of Rule 2001 for NOx RECLAIM sources and Table 2 of Rule 2001 for SOx RECLAIM sources. Those provisions listed in Tables 1 or 2 shall not apply to NOx or SOx emissions after the date the facility has demonstrated compliance with all monitoring and reporting requirements of Rules 2011 or 2012, as applicable. Provisions of the listed AQMD rules in Tables 1 or 2 which have initial implementation dates in 1994 shall not apply to a RECLAIM NOx or SOx source, respectively. [2001]

SECTION E: ADMINISTRATIVE CONDITIONS

- 9. The operator shall, when a source test is required by AQMD, provide a source test protocol to AQMD no later than 60 days before the proposed test date. The test shall not commence until the protocol is approved by AQMD. The test protocol shall contain the following information: [204, 304]
 - a. Brief description of the equipment tested.
 - b. Brief process description, including maximum and normal operating temperatures, pressures, through-put, etc.
 - c. Operating conditions under which the test will be performed.
 - d. Method of measuring operating parameters, such as fuel rate and process weight. Process schematic diagram showing the ports and sampling locations, including the dimensions of the ducts/stacks at the sampling locations, and distances of flow disturbances, (e,g. elbows, tees, fans, dampers) from the sampling locations (upstream and downstream).
 - e. Brief description of sampling and analytical methods used to measure each pollutant, temperature, flow rates, and moisture.
 - f. Description of calibration and quality assurance procedures.
 - g. Determination that the testing laboratory qualifies as an "independent testing laboratory" under Rule 304 (no conflict of interest).
- 10. The operator shall submit a report no later than 60 days after conducting a source test, unless otherwise required by AQMD Rules or equipment-specific conditions. The report shall contain the following information: [204]
 - a. The results of the source test.
 - b. Brief description of the equipment tested.
 - c. Operating conditions under which test will be performed.
 - d. Method of measuring operating parameters, such as fuel rate and process weight. Process schematic diagram showing the ports and sampling locations, including the dimensions of the ducts/stacks at the sampling locations, and distances of flow disturbances, (e.g. elbows, tees, fans, dampers) from the sampling locations (upstream and downstream).
 - e. Field and laboratory data forms, strip charts and analyses.
 - f. Calculations for volumetric flow rates, emission rates, control efficiency, and overall control efficiency.
- The operator shall, when a source test is required, provide and maintain facilities for sampling and testing. These facilities shall comply with the requirements of AQMD Source Test Method 1.1 and 1.2. [217]

Section E Page 4
Facility I.D.#: 800074
Revision #: DRAFT
Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION E: ADMINISTRATIVE CONDITIONS

Whenever required to submit a written report, notification or other submittal to the Executive Officer, AQMD, or the District, the operator shall mail or deliver the material to: Deputy Executive Officer, Engineering and Compliance, AQMD, 21865 E. Copley Drive, Diamond Bar, CA 91765-4182. [204]

SECTION F: RECLAIM MONITORING AND SOURCE TESTING REQUIREMENTS

The Facility shall comply with all applicable monitoring and source testing requirements in Regulation XX. These requirements may include but are not limited to the following:

I. NOx Monitoring Conditions

- A. The Operator of a NOx Major Source, as defined in Rule 2012, shall, as applicable:
- 1. Install, maintain, and operate an AQMD certified direct or time-shared monitoring device or an approved alternative monitoring device for each major NOx source to continuously measure the concentration of NOx emissions and all other applicable variables specified in Rule 2012, Table 2012-1 and Rule 2012, Appendix A, Table 2-A to determine the NOx emissions rate from each source. The time-sharing of CEMS among NOx sources may be allowed by the Executive Officer in accordance with the requirements for time sharing specified in Appendix A. [2012]
- 2. Install, maintain, and operate a totalizing fuel meter approved by the Executive Officer for each major source. [2012]
- 3. If the facility is operating existing CEMS and fuel meters, continue to follow recording and reporting procedures required by AQMD Rules and Regulations in effect prior to October 15, 1993 until the CEMS is certified pursuant to Rule 2012. [2012]
- 4. Use valid data collected by an AQMD certified or provisionally certified CEMS in proper operation that meets all the requirements of Appendix A of Rule 2012, unless final certification of the CEMS is denied, to determine mass emissions for all purposes, including, but not limited to, determining: [2012]
 - a. compliance with the annual Allocation;
 - b. excess emissions;
 - c. the amount of penalties; and
 - d. fees.
- 5. Follow missing data procedures as specified in Rule 2012 Appendix A whenever valid data is not available or collected to determine mass emissions for all purposes, including, but not limited to, determining: [2012]
 - a. compliance with the annual Allocation;
 - b. excess emissions;
 - c. the amount of penalties; and
 - d. fees.

Section F Page 2 Facility I.D.#: 800074 Revision #: DRAFT Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION F: RECLAIM MONITORING AND SOURCE TESTING REQUIREMENTS

- B. The Operator of a NOx Large Source, as defined in Rule 2012, shall, as applicable:

 Not Applicable
- C. The Operator of a NOx Process Unit, as defined in Rule 2012, shall, as applicable:
- 1. Install, maintain, and operate a totalizing fuel meter or any device approved by the Executive Officer to measure quarterly fuel usage or other applicable variables specified in Rule 2012, Table 2012-1, and Rule 2012, Appendix A, Table 4-A. The sharing of totalizing fuel meters may be allowed by the Executive Officer if the fuel meter serves process units which have the same emission factor or emission rate. The sharing of totalizing meter shall not be allowed for process units which are required to comply with an annual heat input limit. [2012]

II. NOx Source Testing and Tune-up Conditions

- 1. The operator shall conduct all required NOx source testing in compliance with an AQMD-approved source test protocol. [2012]
- 2. The operator shall, as applicable, conduct source tests for every large NOx source no later than December 31, 1996 and every 3 years thereafter. The source test shall include the determination of NOx concentration and a relative accuracy audit of the exhaust stack flow determination (e.g. in-stack flow monitor or fuel flow monitor based F-factor calculation). Such source test results shall be submitted per the schedule described by APEP. In lieu of submitting the first source test report, the facility permit holder may submit the results of a source test not more than 3 years old which meets the requirements when conducted. [2012]
- 3. All NOx large sources and NOx process units shall be tuned-up in accordance with the schedule specified in Rule 2012, Appendix A, Chapter 5, Table 5-B. [2012]
- 4. Process Unit source testing

Section G Page 1 Facility I.D.#: 800074 Revision #: DRAFT Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION G: RECORDKEEPING AND REPORTING REQUIREMENTS FOR RECLAIM SOURCES

The Facility shall comply with all applicable reporting and recordkeeping requirements in Regulation XX. These requirements may include but are not limited to the following:

I. Recordkeeping Requirements for all RECLAIM Sources

- 1. The operator shall maintain all monitoring data required to be measured or reported pursuant to Rule 2011 and Rule 2012, whichever is applicable. All records shall be made available to AQMD staff upon request and be maintained for at least:
 - a. Three years after each APEP report is submitted to AQMD for a facility not subject to Title V, unless a different time period is required in Rule 2011 or Rule 2012 [2011 & 2012]; or

b. Five years after each APEP report is submitted to AQMD for a facility subject to Title V. [3004(a)(4)(E)]

- c. Notwithstanding the above, all data gathered or computed for intervals of less than 15 minutes shall only be maintained a minimum of 48 hours. [2011 & 2012]
- 2. The operator shall store on site and make available to the Executive Officer upon request: records used to determine emissions, maintenance records, sources test reports, relative accuracy test audit reports, relative accuracy audit reports and fuel meter calibration records.

 [2011 & 2012]

II. Reporting Requirements for all RECLAIM Sources

1. The operator shall submit a quarterly certification of emissions including the facility's total NOx or SOx emissions, whichever is applicable, for the quarter within 30 days after the end of the first three quarters and 60 days after the end of the fourth quarter of a compliance year. [2011 & 2012]

NOx Reporting Requirements

- A. The Operator of a NOx Major Source, as defined in Rule 2012, shall, as applicable:
- 1. No later than 12 months after entry into the RECLAIM program or after the initial operation of a new major source, whichever is later, install, maintain, and operate a reporting device to electronically report everyday to the AQMD central station for each major NOx source, the total daily mass emissions of NOx and daily status codes. Such data

Section G Page 2 Facility I.D.#: 800074 Revision #: DRAF1 Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION G: RECORDKEEPING AND REPORTING REQUIREMENTS FOR RECLAIM SOURCES

shall be transmitted by 5:00 p.m. of the following day. If the facility experiences a power, computer, or other system failure that prevents the submittal of the daily report, the Facility Permit holder shall be granted 24 hours extension to submit the report. [2012]

- 2. Calculate NOx emissions pursuant to missing data procedures set forth in Appendix A, Chapter 2 of Rule 2012 if the Facility Permit holder fails to meet the deadline for submitting the daily report. [2012]
- 3. Submit an electronic report within 15 days following the end of each month totaling NOX emissions from all major NOx sources during the month. [2012]
- 4. For those facilities with existing CEMS and fuel meters as of October 15, 1993, continue to follow recording and reporting procedures required by AQMD Rules and Regulations in effect until the CEMS is certified pursuant to Rule 2011 and/or Rule 2012, as applicable. [2012]
- B. The Operator of a NOx Large Source, as defined in Rule 2012, shall:

Not Applicable

- C. The Operator of a NOx Process Unit, as defined in Rule 2012, shall:
- 1. Electronically report the calculated quarterly NOx emissions for each NOx process unit. The Operator shall comply with this requirement within 12 months of the date of entry to the RECLAIM Program. [2012]

Section H Facility I.D.: Revision #: DRAFT

Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

Equipment	ID No.	Connected To	RECLAIM Source Type/ Monitoring Unit	Emissions * And Requirements	Conditions
Process 1 : POWER GENER	ATION				
System 1 : BOILERS					
SELECTIVE CATALYTIC REDUCTION, UNIT NO. 6, NOELL REACTOR, 3339 CUBIC FEET OF TOTAL CATALYST VOLUME, WIDTH: 39 FT; HEIGHT: 30 FT; LENGTH: 53 FT 4 IN WITH A/N: 274321 Permit to Construct Issued: 06/04/93	C79	D9		NH3: 20 PPMV NATURAL GAS (4) [RULE 1303(a)(1)- BACT,5-10-1996; RULE 1303(a)(1)-BACT,12-6-2002]; NH3: 20 PPMV FUEL OIL (4) [RULE 1303(a)(1)-BACT,5-10- 1996 RULE 1303(a)(1)-BACT,12-6- 2002]	D12.2, D12.3, D28.2, D28.3, E73.1, E179.1, E179.2, K40.4
AMMONIA INJECTION, UNIT NO. 6, AMMONIA/AIR INJECTION GRID, HAVING 480 INJECTION NOZZLES	C80				

(1)(1A)(1B) Denotes RECLAIM emission factor

Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

Denotes NSR applicability limit (7)'

See App B for Emission Limits (9)

(2)(2A)(2B) Denotes RECLAIM emission rate

Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)

(10)See Section J for NESHAP/MACT requirements

Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

Section H Page: 2 Facility I.D.: 800074 Revision #: DRAFT Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION H: DEVICE ID INDEX

The following sub-section provides an index to the devices that make up the facility description sorted by device ID.

Section H Page: 3
Facility I.D.: 800074
Revision #: DRAFT
Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION H: DEVICE ID INDEX

Device Index For Section H					
Device ID	Section H Page No.	Process	System		
C79	1	1	1		
C80	1	. 1	1		

Page: 4 800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

FACILITY CONDITIONS

- F9.1 Except for open abrasive blasting operations, the operator shall not discharge into the atmosphere from any single source of emissions whatsoever any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
 - (a) As dark or darker in shade as that designated No.1 on the Ringelmann Chart, as published by the United States Bureau of Mines; or
 - (b) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in subparagraph (a) of this condition.

[RULE 401, 3-2-1984; RULE 401, 11-9-2001]

F14.1 The operator shall not use fuel oil containing sulfur compounds in excess of 0.05 percent by weight.

The .05 percent sulfur limit shall not apply to existing supplies of any liquid fuel in storage as of October 1, 1993 until such supply is exhausted.

[RULE 431.2, 5-4-1990; RULE 431.2, 9-15-2000]

F14.2 The operator shall not purchase fuel oil containing sulfur compounds in excess of 15 ppm by weight as supplied by the supplier.

This condition shall become effective on or after June 1, 2004.

[RULE 431.2, 9-15-2000]

F16.1 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

purchase records of fuel oil and sulfur content of the fuel

[RULE 3004(a)(4)-Periodic Monitoring, 8-11-1995; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

Page: 5 800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

F18.1 Acid Rain SO2 Allowance Allocation for affected units are as follows:

Device ID	Boiler ID	Contaminant	Tons in any year
i	Boiler No. 1	SO2	677
4	Boiler No. 2	SO2	335
71	Boiler No. 3	SO2	1234
5	Boiler No. 4	SO2	994
7	Boiler No. 5	SO2	1391
9	Boiler No. 6	SO2	1516

- a). The allowance allocation(s) shall apply to calendar years 2000 through 2009.
- b). The number of allowances allocated to Phase II affected units by U.S. EPA may change in a 1998 revision to 40CFR73 Tables 2,3, and 4. In addition, the number of allowances actually held by an affected source in a unit account may differ from the number allocated by U.S. EPA. Neither of the aforementioned conditions necessitate a revision to the unit SO2 allowance allocations identified in this permit (see 40 CFR 72.84)

[40CFR 73 Subpart B, 1-11-1993]

- F24.1 Accidental release prevention requirements of Section 112(r)(7):
 - a). The operator shall comply with the accidental release prevention requirements pursuant to 40 CFR Part 68 and shall submit to the Executive Officer, as a part of an annual compliance certification, a statement that certifies compliance with all of the requirements of 40 CFR Part 68, including the registration and submission of a risk management plan (RMP).
 - b). The operator shall submit any additional relevant information requested by the Executive Officer or designated agency.

[40CFR 68 - Accidental Release Prevention, 5-24-1996]

DEVICE CONDITIONS

D. Monitoring/Testing Requirements

Page: 6 800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

D12.2 The operator shall install and maintain a(n) temperature gauge to accurately indicate the temperature at the inlet of each selective catalytic reduction reactor.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 2012, 5-11-2001; RULE 2012, 12-5-2003]

[Devices subject to this condition: C79]

D12.3 The operator shall install and maintain a(n) continuous monitoring system to accurately indicate the ammonia injection rate of the ammonia injection system.

The operator shall also install and maintain a device to continuously record the parameter being measured.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

Page: 7 800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

D28.2 The operator shall conduct source test(s) in accordance with the following specifications:

The test shall be conducted to determine the PM emissions using District method 5.1 measured over a 60 minute averaging time period.

The test shall be conducted to determine the NH3 emissions using District method 207.1 measured over a 60 minute averaging time period.

The test shall be conducted to determine the NH3 emissions using either District method 5.3 or EPA method 17 measured over a 60 minute averaging time period.

Source test shall be conducted when this equipment is using fuel oil.

Source test shall be conducted when this equipment is operating at loads of 100 percent, 75 percent, 50 percent, and the minimum load at which ammonia injection commences in the SCR reactor.

The District shall be notified of the date and time of the test at least 14 days prior to the test.

The test shall be conducted using a certified continuous emissions monitoring system to measure the emissions of NOx and CO.

The test shall be conducted by a testing laboratory certified by the California Air Resources Board in the required test methods for each criteria pollutant to be measured, and in compliance with District Rule 304 (no conflict of interest).

The test shall be conducted during the next fuel oil readiness testing.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 2012, 5-11-2001; RULE 2012, 12-5-2003]

800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

D28.3 The operator shall conduct source test(s) in accordance with the following specifications:

The test shall be conducted quarterly during the first 12 months after the initial source test, and once a year thereafter.

The District shall be notified of the date and time of the test at least 7 days prior to the test.

Source test shall be conducted when this equipment is using natural gas.

The test shall be conducted by a testing laboratory certified by the California Air Resources Board in the required test methods, and in compliance with District Rule 304 (no conflict of interest).

The test shall be conducted to determine the NH3 emissions using District method 207.1 measured over a 60 minute averaging time period.

The test shall be conducted to determine the NH3 emissions using either District method 5.3 or EPA method 17 measured over a 60 minute averaging time period.

The test shall be conducted when the equipment is operating at 80 percent load or greater. .

The test shall be conducted and the results submitted to the District within 45 days after the test date.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition: C79]

E. Equipment Operation/Construction Requirements

- Notwithstanding the requirements of Section E conditions, the operator shall not use ammonia injection if any of E73.1 the following requirement(s) are met:
 - 1. Whenever the inlet exhaust temperature prior to the SCR reactor is less than 530 degrees Fahrenheit.
 - 2. Within the first 150 days (or other period approved in writing by the Executive Officer) after initial startup of the SCR system.

[RULE 2012, 5-11-2001; RULE 2012, 12-5-2003]

Page: 9 800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

E179.1 For the purpose of the following condition number(s), "continuous monitoring" shall be defined as measuring at least once every 15 minutes, except as allowed by Rule 2000.

Condition Number D 12-3

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]

[Devices subject to this condition: C79]

E179.2 For the purpose of the following condition number(s), "continuously record" shall be defined as recording at least once every hour and shall be calculated based upon the average of the continuous monitoring for that hour.

Condition Number D 12-3

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 2012, 5-11-2001; RULE 2012, 12-5-2003]

[Devices subject to this condition: C79]

K. Record Keeping/Reporting

Page: 10 800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

The operator shall comply with the terms and conditions set forth below:

K40.4 The operator shall provide to the District a source test report in accordance with the following specifications:

Source test results shall be submitted to the District no later than 180 days after the source test was conducted.

Emission data shall be expressed in terms of concentration (ppmv), corrected to 3 percent oxygen, dry basis.

Emission data shall be expressed in terms of mass rate (lbs/hr). In addition, solid PM emissions, if required to be tested, shall also be reported in terms of grains per DSCF.

Source test results shall also include the fuel flow rate (CFM) under which the test was conducted.

Source test results shall also include the flue gas flow rate (SCFM) under which the test was conducted.

Source test results shall also include the utility boiler exhaust temperature (degrees Fahrenheit), before the SCR reactors, under which the test was conducted.

Source test results shall also include the NH3 injection rate (lb/hr), upstream of the SCR reactor, under which the test was conducted.

Source test results shall also include the NH3/NOx molar ratio under which the test was conducted.

Source test results shall also include the net utility boiler and steam turbine electric generator output (MW) under which the test was conducted.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 2012, 5-6-2005]

Section I Page 1
Facility I.D.#: 800074
Revision #: DRAFT
Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION I: PLANS AND SCHEDULES

This section lists all plans approved by AQMD for the purposes of meeting the requirements of applicable AQMD rules.

NONE

NOTE: This section does not list compliance schedules pursuant to the requirements of Regulation XXX - Title V Permits; Rule 3004(a)(10)(C). For equipment subject to a variance, order for abatement, or alternative operating condition granted pursuant to Rule 518.2, equipment specific conditions are added to the equipment in Section D or H of the permit.

Section J Page: 1 Facility I.D.: 800074 Revision #: DRAFT Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION J: AIR TOXICS

NOT APPLICABLE

Section K Page: 1 Facility I.D.: 800074 Revision #: DRAFT Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION K: TITLE V Administration

GENERAL PROVISIONS

- 1. This permit may be revised, revoked, reopened and reissued, or terminated for cause, or for failure to comply with regulatory requirements, permit terms, or conditions. [3004(a)(7)(C)]
- 2. This permit does not convey any property rights of any sort or any exclusive privilege. [3004(a)(7)(E)]

Permit Renewal and Expiration

- 3. (A) Except for solid waste incineration facilities subject to standards under Section 129(e) of the Clean Air Act, this permit shall expire five years from the date that the initial Title V permit is issued. The operator's right to operate under this permit terminates at midnight on this date, unless the facility is protected by an application shield in accordance with Rule 3002(b), due to the filing of a timely and complete application for a Title V permit renewal, consistent with Rule 3003. [3004(a)(2), 3004(f)]
 - (B) A Title V permit for a solid waste incineration facility combusting municipal waste subject to standards under Section 129(e) of the Clean Air Act shall expire 12 years from the date of issuance unless such permit has been renewed pursuant to this regulation. These permits shall be reviewed by the Executive Officer at least every five years from the date of issuance. [3004(f)(2)]
- 4. To renew this permit, the operator shall submit to the Executive Officer an application for renewal at least 180 days, but not more than 545 days, prior to the expiration date of this permit. [3003(a)(6)]

Duty to Provide Information

5. The applicant for, or holder of, a Title V permit shall furnish, pursuant to Rule 3002(d) and (e), timely information and records to the Executive Officer or designee within a reasonable time as specified in writing by the Executive Officer or designee. [3004(a)(7)(F)]

Payment of Fees

6. The operator shall pay all required fees specified in Regulation III - Fees. [3004(a)(7)(G)]

Reopening for Cause

- 7. The Executive Officer will reopen and revise this permit if any of the following circumstances occur:
 - (A) Additional regulatory requirements become applicable with a remaining permit term of three or more years. Reopening is not required if the effective date of the requirement is later than the expiration date of this permit, unless the permit or any of its terms and conditions has been extended pursuant to paragraph (f)(4) of Rule 3004.

Section K Page: 2 Facility I.D.: 800074 Revision #: DRAFT Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION K: TITLE V Administration

- (B) The Executive Officer or EPA Administrator determines that this permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of this permit.
- (C) The Executive Officer or EPA Administrator determines that the permit must be revised or revoked to assure compliance with the applicable requirements. [3005(g)(1)]

COMPLIANCE PROVISIONS

- 8. The operator shall comply with all regulatory requirements, and all permit terms and conditions, except:
 - (A) As provided for by the emergency provisions of condition no. 17 or condition no. 18, or
 - (B) As provided by an alternative operating condition granted pursuant to a federally approved (SIP-approved) Rule 518.2.

Any non-compliance with any federally enforceable permit condition constitutes a violation of the Federal Clean Air Act and is grounds for enforcement action; for permit termination, revocation and reissuance, or revision; or denial of a permit renewal application. Non-compliance may also be grounds for civil or criminal penalties under the California State Health and Safety Code. [3004(a)(7)(A)]

- 9. The operator shall allow the Executive Officer or authorized representative, upon presentation of appropriate credentials to:
 - (A) Enter the operator's premises where emission-related activities are conducted, or records are kept under the conditions of this permit;
 - (B) Have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit;
 - (C) Inspect at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and
 - (D) Sample or monitor at reasonable times, substances or parameters for the purpose of assuring compliance with the facility permit or regulatory requirements. [3004(a)(10)(B)]
- 10. All terms and conditions in this permit, including any provisions designed to limit a facility's potential to emit, are enforceable by the EPA Administrator and citizens under the federal Clean Air Act, unless the term or condition is designated as not federally enforceable. Each day during any portion of which a violation occurs is a separate offense. [3004(g)]

Section K Page: 3 Facility I.D.: 800074 Revision #: DRAFT Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION K: TITLE V Administration

- 11. A challenge to any permit condition or requirement raised by EPA, the operator, or any other person, shall not invalidate or otherwise affect the remaining portions of this permit. [3007(b)]
- 12. The filing of any application for a permit revision, revocation, or termination, or a notification of planned changes or anticipated non-compliance does not stay any permit condition. [3004(a)(7)(D)]
- 13. It shall not be a defense for a person in an enforcement action, including those listed in Rule 3002(c)(2), that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit, except as provided for in "Emergency Provisions" of this section. [3004(a)(7)(H)]
- 14. The operator shall not build, erect, install, or use any equipment, the use of which, without resulting in a reduction in the total release of air contaminants to atmosphere, reduces or conceals an emission which would otherwise constitute a violation of Chapter 3 (commencing with Section 41700) of Part 4, of Division 26 of the California Health and Safety Code or of AQMD rules. This rule shall not apply to cases in which the only violation involved is of Section 41700 of the California Health and Safety Code, or Rule 402 of AQMD Rules. [408]
- 15. Nothing in this permit or in any permit shield can alter or affect:
 - (A) Under Section 303 of the federal Clean Air Act, the provisions for emergency orders;
 - (B) The liability of the operator for any violation of applicable requirements prior to or at the time of permit issuance;
 - (C) The applicable requirements of the Acid Rain Program, Regulation XXXI:
 - (D) The ability of EPA to obtain information from the operator pursuant to Section 114 of the federal Clean Air Act;
 - (E) The applicability of state or local requirements that are not "applicable requirements", as defined in Rule 3000, at the time of permit issuance but which do apply to the facility, such as toxics requirements unique to the State; and
 - (F) The applicability of regulatory requirements with compliance dates after the permit issuance date. [3004(c)(3)]
- 16. For any portable equipment that requires an AQMD or state permit or registration, excluding a) portable engines, b) military tactical support equipment and c) AQMD-permitted portable equipment that are not a major source, are not located at the facility for more than 12 consecutive months after

Facility I.D.: Revision #:

DRAFT April 24, 2008

Date:

800074

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION K: TITLE V Administration

commencing operation, and whose operation does not conflict with the terms or conditions of this Title V permit: 1) the facility operator shall keep a copy of the AQMD or state permit or registration; 2) the equipment operator shall comply with the conditions on the permit or registration and all other regulatory requirements; and 3) the facility operator shall treat the permit or registration as a part of its Title V permit, subject to recordkeeping, reporting and certification requirements. [3004(a)(1)]

Section K Page: 5
Facility I.D.: 800074
Revision #: DRAFT
Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION K: TITLE V Administration

EMERGENCY PROVISIONS

- 17. An emergency¹ constitutes an affirmative defense to an action brought for non-compliance with a technology-based emission limit only if:
 - (A) Properly signed, contemporaneous operating records or other credible evidence demonstrate that:
 - (1) An emergency occurred and the operator can identify the cause(s) of the emergency;
 - (2) The facility was operated properly (i.e. operated and maintained in accordance with the manufacturer's specifications, and in compliance with all regulatory requirements or a compliance plan), before the emergency occurred;
 - (3) The operator took all reasonable steps to minimize levels of emissions that exceeded emissions standard, or other requirements in the permit; and,
 - (4) The operator submitted a written notice of the emergency to the AQMD within two working days of the time when the emissions limitations were exceeded due to the emergency. The notice shall contain a description of the emergency, any steps taken to mitigate emissions, and corrective actions taken; and
 - (B) The operator complies with the breakdown provisions of Rule 430 Breakdown Provisions, or subdivision (i) of Rule 2004 Requirements, whichever is applicable. [3002(g), 430, 2004(i)]
- 18. The operator is excused from complying with any regulatory requirement that is suspended by the Executive Officer during a state of emergency or state of war emergency, in accordance with Rule 118 Emergencies. [118]

^{1 &}quot;Emergency" means any situation arising from sudden and reasonably unforeseeable events beyond the control of the operator, including acts of God, which: (A) requires immediate corrective action to restore normal operation; and (B) causes the facility to exceed a technology-based emission limitation under the permit, due to unavoidable increases in emissions attributable to the emergency; and (C) is not caused by improperly designed equipment, lack of preventative maintenance, careless or imporper operation, or operator error.

Section K 800074 Facility I.D.: Revision #: DRAFT

April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION K: TITLE V Administration

RECORDKEEPING PROVISIONS

- In addition to any other recordkeeping requirements specified elsewhere in this 19. permit, the operator shall keep records of required monitoring information, where applicable, that include:
 - The date, place as defined in the Title V permit, and time of sampling (A) or measurements:
 - (B) The date(s) analyses were performed;
 - The company or entity that performed the analyses: (C)
 - (D) The analytical techniques or methods used;
 - The results of such analyses; and (E)
 - The operating conditions as existing at the time of sampling or (F) measurement. [3004(a)(4)(B)]
- 20. The operator shall maintain records pursuant to Rule 109 and any applicable material safety data sheet (MSDS) for any equipment claimed to be exempt from a written permit by Rule 219 based on the information in those records. [219(t)]
- 21. The operator shall keep all records of monitoring data required by this permit or by regulatory requirements for a period of at least five years from the date of the monitoring sample, measurement, report, or application. [3004(a)(4)(E)]

REPORTING PROVISIONS

- The operator shall comply with the following requirements for prompt reporting 22. of deviations:
 - Breakdowns shall be reported as required by Rule 430 Breakdown (A) Provisions or subdivision (i) of Rule 2004 - Requirements, whichever is applicable.
 - Other deviations from permit or applicable rule emission limitations, (B) equipment operating conditions, or work practice standards, determined by observation or by any monitoring or testing required by the permit or applicable rules that result in emissions greater than those allowed by the permit or applicable rules shall be reported within 72 hours (unless a shorter reporting period is specified in an applicable State or Federal Regulation) of discovery of the deviation by contacting AQMD enforcement personnel assigned to this facility or otherwise calling (800) CUT-SMOG.

Section K Page: 7
Facility I.D.: 800074
Revision #: DRAFT
Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION K: TITLE V Administration

Þ

- (C) A written report of such deviations reported pursuant to (B), and any corrective actions or preventative measures taken, shall be submitted to AQMD, in an AQMD approved format, within 14 days of discovery of the deviation.
- (D) All other deviations shall be reported with the monitoring report required by condition no. 23. [3004(a)(5)]
- Unless more frequent reporting of monitoring results are specified in other permit conditions or in regulatory requirements, the operator shall submit reports of any required monitoring to the AQMD at least twice per year. The report shall include a) a statement whether all monitoring required by the permit was conducted; and b) identification of all instances of deviations from permit or regulatory requirements. A report for the first six calendar months of the year is due by August 31 and a report for the last six calendar months of the year is due by February 28. [3004(a)(4)(F)]
- 24. The operator shall submit to the Executive Officer and to the Environmental Protection Agency (EPA), an annual compliance certification. For RECLAIM facilities, the certification is due when the Annual Permit Emissions Program (APEP) report is due and shall cover the same reporting period. For other facilities, the certification is due on March 1 for the previous calendar year. The certification need not include the period preceding the date the initial Title V permit was issued. Each compliance certification shall include:
 - (A) Identification of each permit term or condition that is the basis of the certification;
 - (B) The compliance status during the reporting period;
 - (C) Whether compliance was continuous or intermittent;
 - (D) The method(s) used to determine compliance over the reporting period and currently, and
 - (E) Any other facts specifically required by the Executive Officer to determine compliance.

The EPA copy of the certification shall be sent to: Director of the Air Division Attn: Air-3 USEPA, Region IX 75 Hawthorne St. San Francisco, CA 94105 [3004(a)(10)(E)]

25. All records, reports, and documents required to be submitted by a Title V operator to AQMD or EPA shall contain a certification of accuracy consistent with Rule 3003(c)(7) by a responsible official (as defined in Rule 3000). [3004(a)(12)]

Entertained by Entertained

Section K Facility I.D.:

Page: 8 800074 DRAFT

Revision #: Date:

April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION K: TITLE V Administration

PERIODIC MONITORING

26. All periodic monitoring required by this permit pursuant to Rule 3004(a)(4)(c) is based on the requirements and justifications in the AQMD document "Periodic Monitoring Guidelines for Title V Facilities" or in case-by-case determinations documented in the Title V application file. [3004(a)(4)]

Section K Page: 9 Facility I.D.: Revision #: Date:

800074 DRAFT April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION K: TITLE V Administration

FACILITY RULES

This facility is subject to the following rules and regulations:

With the exception of Rule 402, 473, 477, 1118 and Rules 1401 through 1420, the following rules that are designated as non-federally enforceable are pending EPA approval as part of the state implementation plan. Upon the effective date of that approval, the approved rule(s) will become federally enforceable, and any earlier versions of those rules will no longer be federally enforceable.

RULE SOURCE	Adopted/Amended Date	FEDERAL Enforceability
RULE 1110.2	11-14-1997	Non federally enforceable
RULE 1110.2	6-3-2005	Non federally enforceable
RULË 1113	11-8-1996	Federally enforceable
RULE 1140	8-2-1985	Non federally enforceable
RULE 1171	11-7-2003	Federally enforceable
RULE 118	12-7-1995	Non federally enforceable
RULE 1303(a)(1)-BACT	12-6-2002	Non federally enforceable
RULE 1303(a)(1)-BACT	5-10-1996	Federally enforceable
RULE 1303(b)(2)-Offset	12-6-2002	Non federally enforceable
RULE 1303(b)(2)-Offset	5-10-1996 .	Federally enforceable
RULE 1304(a)-Modeling and Offset Exemption	6-14-1996	Federally enforceable
RULE 1304(c)-Offset Exemption	6-14-1996	Federally enforceable
RULE 1411	3-1-1991	Non federally enforceable
RULE 1415	10-14-1994	Non federally enforceable
RULE 1470	6-1-2007	Non federally enforceable
RULE 2005	4-20-2001	Federally enforceable
RULE 2005	4-9-1999	Federally enforceable
RULE 2005	5-6-2005	Federally enforceable
RULE 2009	5-11-2001	Non federally enforceable
RULE 2012	12-5-2003	Federally enforceable
RULE 2012	5-11-2001	Federally enforceable
RULE 2012	5-6-2005	Federally enforceable
RULE 204	10-8-1993	Federally enforceable
RULE 217	1-5-1990	Federally enforceable
RULE 218	5-14-1999	Non federally enforceable
RULE 218	8-7-1981	Federally enforceable
RULE 219	9-4-1981	Federally enforceable
RULE 3002	11-14-1997	Federally enforceable
RULE 3003	11-14-1997	Federally enforceable

Section K Facility I.D.:

800074 DRAFT

Revision #: April 24, 2008

Date:

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

SECTION K: TITLE V Administration

RULE SOURCE	Adopted/Amended Date	FEDERAL Enforceability
RULE 3004(a)(4)-Periodic Monitoring	12-12-1997	Federally enforceable
RULE 3005	11-14-1997	Federally enforceable
RULE 3007	10-8-1993	Federally enforceable
RULE 304	1-14-1982	Non federally enforceable
RULĖ 401	11-9-2001	Non federally enforceable
RULE 401	3-2-1984	Federally enforceable
RULE 402	5-7-1976	Non federally enforceable
RULE 404	2-7-1986	Federally enforceable
RULE 405	2-7-1986	Federally enforceable
RULE 407	4-2-1982	Federally enforceable
RULE 408	5-7-1976	Federally enforceable
RULE 409	8-7-1981	Federally enforceable
RULE 430	7-12-1996	Non federally enforceable
RULE 431.1	11-17-1995	Non federally enforceable
RULE 431.2	5-4-1990	Federally enforceable
RULE 431.2	9-15-2000	Non federally enforceable
RULE 463	3-11-1994	Federally enforceable
RULE 464	12-7-1990	Federally enforceable
RULE 475	10-8-1976	Federally enforceable
RULE 475	8-7-1978	Non federally enforceable
40CFR 60 Subpart Da	10-4-1991	Federally enforceable
40CFR 60 Subpart GG	3-6-1981	Federally enforceable
40CFR 68 - Accidental Release Prevention	5-24-1996	Federally enforceable
RULE 701	6-13-1997	Federally enforceable
40CFR 72 - Acid Rain Provisions	11-24-1997	Federally enforceable
40CFR 73 Subpart B	1-11-1993	Federally enforceable
40CFR 82 Subpart B	7-14-1992	Federally enforceable
CA PRC CEQA	11-23-1970	Non federally enforceable

Appendix A Page 1
Facility I.D.#: 800074
Revision #: DRAFT
Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

APPENDIX A: NOX AND SOX EMITTING EQUIPMENT EXEMPT FROM WRITTEN PERMIT PURSUANT TO RULE 219

- 1. VACUUM, GASOLINE
- 2. BACKPACK AIR BLOWER, GASOLINE
- 3. CHAIN SAW, GASOLINE
- 4. CONCRETE SAW, GASOLINE
- 5. AIR COMPRESSOR, GASOLINE
- 6. CONCRETE MIXERS, GASOLINE
- 7. WELDER, GASOLINE
- 8. WATER BLASTER, GASOLINE
- 9. IC ENGINES

Appendix B Page 1 Facility I.D.#: 800074 Revision #: DRAFT Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 11-8-1996]

- (1) Except as provided in paragraphs (c)(2), (c)(3), and (c)(4) of Rule 1113, the operator shall not supply, sell, offer for sale, apply, or solicit the application of, any architectural coating which, at the time of sale or manufacture, contains more than 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, and less any colorant added to tint bases, or manufacture, blend, or repackage such a coating for use within the District.
- (2) Except as provided in paragraphs (c)(3) and (c)(4) of Rule 1113, the operator shall not supply, sell, offer for sale, apply, solicit the application of, manufacture, blend, or repackage, for use within the District, any architectural coating listed in the Table of Standards which contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified.

TABLE OF STANDARDS

VOC LIMITS

Grams of VOC Per Liter of Coating, Less Water And Less Exempt Compounds

COATING	Limit*	Effective Date of Adoption	Effective 1/1/1998	Effective 1/1/1999	Effective 7/1/2001	Effective 1/1/2005	Effective 7/1/2008
Bond Breakers Clear Wood Finishes Varnish Sanding Sealers Lacquer Concrete-Curing Compounds Dry-Fog Coatings Fire-proofing Exterior Coatings Fire-Retardant Coatings Clear Pigmented Flats Graphic Arts (Sign) Coatings Industrial Maintenance	350 350 350 680 350 400 350 650 350 250 500	450	550	350	100	275	50

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 11-8-1996]

Primers and Topcoats			j]]
Alkyds	420					
Catalyzed Epoxy	420					
Bituminous Coatings	420	ļ				
Materials						
Inorganic Polymers	420					
Vinyl Chloride Polymers	420					
Chlorinated Rubber	420					
Acrylic Polymers	420					
Urethane Polymers	420	}				
Silicones	420					
Unique Vehicles	420					
Japans/Faux Finishing	350	700		350		
Coatings						
Magnesite Cement Coatings	600			450		
Mastic Coatings	300				'	
Metallic Pigmented Coatings	500					1
Multi-Color Coatings	420		250			
Pigmented Lacquer	680		550		275	
Pre-Treatment Wash Primers	780					ļ
Primers, Sealers, and	350					
Undercoaters						
Quick-Dry Enamels	400				,	
Roof Coatings	300			,]
Shellac			İ			
Clear	730					
Pigmented	550				'	
Stains	350					
Swimming Pool Coatings						
Repair	650					1
Other	340				,	
Traffic Coatings	250		150			
Waterproofing Sealers	400]			
Wood Preservatives				i		}
Below-Ground	350					
Other	350		<u> </u>			

^{*} The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards

Appendix B Page 3 Facility I.D.#: 800074 Revision #: DRAFT Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 11-8-1996]

TABLE OF STANDARDS (cont.)

VOC LIMITS

Grams of VOC Per Liter of Material

COATING Limit

Low-Solids Coating 120

Appendix B Page 4
Facility I.D.#: 800074
Revision #: DRAFT
Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 5-14-1999]

- (1) Except as provided in paragraphs (c)(2), (c)(3), (c)(4), and specified coatings averaged under (c)(6) of Rule 1113, the operator shall not supply, sell, offer for sale, manufacture, blend, or repackage any architectural coating for use in the District which, at the time of sale or manufacture, contains more than 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, and less any colorant added to tint bases, and no person shall apply or solicit the application of any architectural coating within the District that exceeds 250 grams of VOC per liter of coating as calculated in this paragraph.
- Except as provided in paragraphs (c)(3), (c)(4), and designated coatings averaged under (c)(6) of Rule 1113, the operator shall not supply, sell, offer for sale, manufacture, blend, or repackage, for use within the District, any architectural coating listed in the Table of Standards which contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified, and no person shall apply or solicit the application of any architectural coating within the District that exceeds the VOC limit as specified in this paragraph. No person shall apply or solicit the application within the District of any industrial maintenance coatings for residential use; or of any rust-preventative coating for industrial use.

Appendix B Page 5 Facility I.D.#: 800074 Revision #: DRAFT Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 5-14-1999]

TABLE OF STANDARDS VOC LIMITS

Grams of VOC Per Liter of Coating, Less Water And Less Exempt Compounds

COATING	Limit*	Effective							
Dand Drookers	200	1/1/1998	1/1/1999	5/14/99	7/1/2001	7/1/2002	1/1/2005	7/1/2006	7/1/2008
Bond Breakers	350							400	
Chemical Storage Tank Coatings	420							100	
Clear Wood Finishes									
Varnish	350								
Sanding Sealers	350							,	·
Lacquer	680	550					275		
Concrete-Curing Compounds	350				•				
Dry-Fog Coatings	400								
Essential Public Service Coating	420					340		100	
Fire-proofing Exterior Coatings	450		350						
Fire-Retardant Coatings									
Clear	650								
Pigmented	350								
Flats	250				100				50
Floor Coatings	420					100		50	
Graphic Arts (Sign) Coatings	500								
High Temperature Industrial Maintenance Coatings						550		420	
Coatings Industrial Maintenance Coatings	420					250		100	
Japans/Faux Finishing Coatings	700		350						
Magnesite Cement Coatings	600		450						
Mastic Coatings	300								
Metallic Pigmented Coatings	500		·						
Multi-Color Coatings	420	250							
Non-Flat Coatings	250					150		50	
Pigmented Lacquer Pre-Treatment Wash	680	550					275		
Primers	780								
Primers, Sealers, and Undercoaters	350					200		100	
Quick-Dry Enamels	400					250		50	
Quick-Dry Primers, Sealers, and Undercoaters	350**					200		100	
Recycled Coatings				250		250		100	

Appendix B Page 6
Facility I.D.#: 800074
Revision #: DRAFT
Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 5-14-1999]

DoofContings	1 200 1		1	1 250	т	I	· · · · · · · · · · · · · · · · · · ·		
Roof Coatings	300			250					
Bituminous Roof	300					250			
Coatings	j		}		•		<u> </u>		
Rust Preventative Coatings	420			400				100	
Shellac	1								
Clear	730							,	
Pigmented Specialty Primers	550						l		
Specialty Primers	350							100	
Stains	350					250			
Swimming Pool Coatings							-		
Repair	650								
Other	340	·							
Traffic Coatings Waterproofing Sealers Wood	250	150							
Waterproofing Sealers		•							
Wood	400				}	250			
L Concrete/Masonry	400								
Wood Preservatives Below-Ground									
Below-Ground	350								
Other	350								

^{*} The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards

Grams of VOC Per Liter of Material

COATING Limit

Low-Solids Coating 120

^{**} The specified limit applies unless the manufacturer submits a report pursuant to Rule 1113(g)(2).

Appendix B Page 7 Facility I.D.#: 800074 Revision #: DRAFT

Date: April 24, 2008

FACILITY PERMIT TO OPERATE

APPENDIX B: RULE EMISSION LIMITS [RULE 1140 8-2-1985]

LA CITY, DWP HAYNES GENERATING STATION

- (1) The operator shall not, if he complies with an applicable performance standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
 - As dark or darker in shade as that designated as No. 2 on the (A) Ringelmann Chart, as published by the United States Bureau of Mines,
 - Of such opacity as to obscure an observer's view to a degree equal to (B) or greater than does smoke described in (1)(A).
- The operator shall not, if he is not complying with an applicable performance (2) standard in section (b)(4) of Rule 1140, discharge into the atmosphere from any abrasive blasting any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:
 - (A) As dark or darker in shade as that designated as No. 1 on the Ringelmann Chart, as published by the United States Bureau of Mines, or
 - (B) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in (2)(A).

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 11-7-2003]

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

SOLVENT CLEANING ACTIVITY	CURRENT LIMITS VOC g/l (lb/gal)
(A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application	
(i) General	25 (0.21)
(ii) Electrical Apparatus Components & Electronic Components	500 (4.2)
(iii) Medical Devices & Pharmaceuticals	800 (6.7)
(B) Repair and Maintenance Cleaning	
(i) General	25 (0.21)
(ii) Electrical Apparatus Components & Electronic Components	900 (7.5)
(iii) Medical Devices & Pharmaceuticals	
(A) Tools, Equipment, & Machinery	800 (6.7)
(B) General Work Surfaces	600 (5.0)

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 11-7-2003]

SOLVENT CLEANING ACTIVITY	CURRENT LIMITS VOC g/l (lb/gal)
(C) Cleaning of Coatings or Adhesives Application Equipment	550 (4.6)
(D) Cleaning of Ink Application Equipment	
(i) General	25 (0.21)
(ii) Flexographic Printing	. 25 (0.21)
(iii) Gravure Printing	
(A) Publication	750 (6.3)
(B) Packaging	25 (0.21)
(iv) Lithographic or Letter Press Printing .	
(A) Roller Wash – Step 1	600 (5.0)
(B) Roller Wash-Step 2, Blanket Wash, & On-Press Components	800 (6.7)
(C) Removable Press Components	25 (0.21)
(v) Screen Printing	750 (6.3)
(vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing)	800

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 11-7-2003]

SOLVENT CLEANING ACTIVITY	CURRENT LIMITS VOC g/l (lb/gal)
(vii) Specialty Flexographic Printing	600 (5.0)
(E) Cleaning of Polyester Resin Application Equipment	25 (0.21)

Appendix B Page 11 Facility I.D.#: 800074 Revision #: DRAFT Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 5-6-2005]

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

	CURRENT LIMITS*	Effective 7/1/2005*	Effective 7/1/2006
SOLVENT CLEANING ACTIVITY	VOC g/l (lb/gal)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application			
(i) General	25 (0.21)		
(ii) Electrical Apparatus Components & Electronic Components	500 (4.2)	100 (0.83)	
(iii) Medical Devices & Pharmaceuticals	800 (6.7)		
(B) Repair and Maintenance Cleaning			
(i) General	25 (0.21)		
(ii) Electrical Apparatus Components & Electronic Components	900 (7.5)	100 (0.83)	
(iii) Medical Devices & Pharmaceuticals			

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 5-6-2005]

	CURRENT LIMITS*	Effective 7/1/2005*	Effective 7/1/2006	
SOLVENT CLEANING ACTIVITY	VOC g/l (lb/gal)	VOC g/l (lb/gal)	VOC g/l (lb/gal)	
(A) Tools, Equipment, & Machinery	800 (6.7)	·		
(B) General Work Surfaces	600 (5.0)			
(C) Cleaning of Coatings or Adhesives Application Equipment	550 (4.6)	25 (0.21)		
(D) Cleaning of Ink Application Equipment				
(i) General	25 (0.21)			
(ii) Flexographic Printing	25 (0.21)			
(iii) Gravure Printing				
(A) Publication	750 (6.3)	100 (0.83)		
(B) Packaging	25 (0.21)			
(iv) Lithographic or Letter Press Printing			ţ	
(A) Roller Wash – Step 1	600 (5.0)	500 (4.2)	100 (0.83)	

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 5-6-2005]

	CURRENT LIMITS*	Effective 7/1/2005*	Effective 7/1/2006	
SOLVENT CLEANING ACTIVITY	VOC g/l (lb/gal)	VOC g/l (lb/gal)	VOC g/l (lb/gal)	
(B) Roller Wash-Step 2, Blanket Wash, & On- Press Components	800 (6.7)	500 (4.2)	100 (0.83)	
(C) Removable Press Components	25 (0.21)			
(v) Screen Printing	750 (6.3)	500 (4.2)	100 (0.83)	
(vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing)	800 (6.7)	500 (4.2)	100 (0.83)	
(vii) Specialty Flexographic Printing	600 (5.0)	100 (0.83)		
(E) Cleaning of Polyester Resin Application Equipment	25 (0.21)			

^{*} The specified limits remain in effect unless revised limits are listed in subsequent columns.

Appendix B Page 14 Facility I.D.#: 800074 Revision #: DRAFT Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

APPENDIX B: RULE EMISSION LIMITS [RULE 404 2-7-1986]

The operator shall not discharge into the atmosphere from this equipment, particulate matter in excess of the concentration at standard conditions, shown in Table 404(a). Where the volume discharged is between figures listed in the Table, the exact concentration permitted to be discharged shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

TABLE 404(a)

Volume Dis Calculated Gas At Stan Condit	as Dry dard	of Part Matter"A Dischar Calculate Gas at S	oncentration iculate allowed in ged Gas bry Standard itions	Volume Di Calculated a At Standard	s Dry Gas	Maximum Co of Particula Allowed in I Gas Calculated at Standard Co	te Matter Discharged I as Dry Gas
Cubic	Cubic	Milligrams	Grains per	Cubic	Cubic	Milligrams	Grains per
meters	feet	per	Cubic Foot	meters	feet	per	Cubic
Per	Per	Cubic		Per Minute	Per	Cubic Meter	Foot
Minute	Minute	Meter			Minute		
25 or	883	450	0.196	900	31780	118	0.0515
less	or						
	less						
30	1059	420	.183	1000	35310	113	.0493
35	1236	397	.173	1100	38850	109	.0476
40	1413	377	.165	1200	42380	106	.0463
1							
45	1589	361	.158	1300	45910	102	.0445
50	1766	347	.152	1400	49440	100	.0437
60	2119	324	.141	1500	52970	97	.0424
70	2472	306	.134	1750	61800	92	.0402

Appendix B Page 15 Facility I.D.#: 800074 Revision #: DRAFT Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

APPENDIX B: RULE EMISSION LIMITS [RULE 404 2-7-1986]

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter"Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions	
Cubic	Cubic	Milligrams	Grains per	Cubic	Cubic	Milligrams	Grains per
meters Per	feet Per	per Cubic	Cubic Foot	meters Per Minute	feet Per	per Cubic Meter	Cubic Foot
Minute	Minute	Meter		rei Millute	Minute	Cubic Meter	1001
			107	2000	···	0.7	0200
80	2825		.127	2000	70630	87	.0380
90	3178	279	.122	2250	79460	83	.0362
100	3531	267	.117	2500	88290	80	.0349
125	4414	246	.107	3000	105900	75	.0327
1.50		200	100	1000	1,11000		
150	5297	230	.100	4000	141300	67	.0293
175	6180	217	.0947	5000	176600	62	.0271
200	7063	206	.0900	6000	211900	58	.0253
250	8829	190	.0830	8000	282500	52	.0227
300	10590	177	.0773	10000	353100	48	.0210
350	12360	167	.0730	15000	529700	41	.0179
							ļ
400	14130	159	.0694	20000	706300	37	.0162
450	15890	152	.0664	25000	882900	34	.0148
500	17660	146	.0637	30000	1059000	32	.0140
600	21190	137	.0598	40000	1413000	28	.0122
700	24720	129	.0563	50000	1766000	26	.0114
800	28250	123	.0537	70000 or more	2472000 or more	23	.0100

Appendix B Page 16 Facility I.D.#: 800074 Revision #: DRAFT Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

APPENDIX B: RULE EMISSION LIMITS [RULE 405 2-7-1986]

The operator shall not discharge into the atmosphere from this equipment, solid particulate matter including lead and lead compounds in excess of the rate shown in Table 405(a).

Where the process weight per hour is between figures listed in the table, the exact weight of permitted discharge shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

TABLE 405(a)

Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All Points of Process		Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All points of Process	
Kilograms	Pounds	Kilograms	Pounds	Kilograms	Pounds	Kilograms	Pounds
Per Hour	Per Hour	Per Hour	Per Hour	Per Hour	Per Hour	Per Hoür	Per Hour
100 or	220 or	0.450	0.99	9000	19840	5.308	11.7
less	less						
150	331	0.585	1.29	10000	22050	5.440	12.0
200	441	0.703	1.55	12500	27560	5.732	12.6
250	551	0.804	1.77	15000	33070	5.982	13.2
300	661	0.897	1.98	17500 ,	38580	6.202	13.7
350	772	0.983	2.17	20000	44090	6.399	14.1
400	882	1,063	2.34	25000	55120	6.743	14,9
450	992	1.138	2.51	30000	66140	7.037	15.5
500	1102	1.209	2.67	35000	77160	. 7.296	16.1
600 ·	1323	1.340	2.95	40000	88180	7.527	16.6
700	1543	1.461	3.22	45000	99210	7,738	17.1
800	1764	1.573	3.47	50000	110200	7,931	17.5
900	1984	1.678	3.70	60000	132300	8.277	18.2
1000	2205	1.777	3.92	70000	154300	8.582	18.9

Appendix B Page 17
Facility I.D.#: 800074
Revision #: DRAFT
Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

APPENDIX B: RULE EMISSION LIMITS [RULE 405 2-7-1986]

Process Weight Per Hour		Maximum Ra Allowed to Particulat (Aggregate	te for Solid e Matter Discharged	Process Weight Per Hour		Maximum Discharge Rate Allowed for Solid Particulate Matter (Aggregate Discharged From All points of	
		From All Points of Process				Process	
Kilograms	Pounds	Kilograms	Pounds	Kilograms	Pounds	Kilograms	Pounds
Per Hour	Per Hour	Per Hour	Per Hour	Per Hour	Per Hour	Per Hour	Per Hour
1250	2756	2.003	. 4.42	80000	176400	8.854	19.5
1500	3307	2.206	4.86	90000	198400	9.102	20.1
1750	3858	2,392	5.27	100000	220500	9.329	20,6
2000	4409	2.563	5.65	125000	275600	9.830	21.7
2250	4960	2.723	6,00	150000	330700	10.26	22.6
2500	5512	2.874	6.34	175000	385800	10.64	23.5
2750	6063	3.016	6.65	200000	440900	10.97	24.2
3000	6614	3.151	6.95	225000	496000	11.28	24.9
3250	7165	3.280	7.23	250000	551200	11.56	25,5
3600	7716	3.404	7.50	275000	606300	11.82	26.1
4000	8818	3.637	8.02	300000	661400	12.07	26.6
4500	9921	3.855	8.50	325000	716500	12.30	27.1
5000	11020	4.059	8.95	350000	771600	12.51	27.6
6000	13230	4.434	9.78	400000	881800	12.91	28.5
7000	15430	4.775	10.5	450000	992100	13.27	29.3
8000	17640	5.089	11.2	500000 or more	1102000 or more	13,60	30.0

Appendix B Page 18 Facility I.D.#: 800074 Revision #: DRAFT Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

APPENDIX B: RULE EMISSION LIMITS [40CFR 72 - Acid Rain Provisions 11-24-1997]

1. A Title V permit revision is not required for emission increases that are authorized by allowances acquired under the Acid Rain Program, provided that the increases do not trigger a Title V permit revision under any other applicable requirement. [70.6 (a)(4)(ii)]

Monitoring Requirements

- The owners and operators and, to the extent applicable, the designated representative of each affected source and each affected unit at the source shall comply with the monitoring requirements as provided in 40 CFR Parts 74, 75, and 76. [40 CFR 72.50, 72.31, 72.9(b)(1)]
- 3. The emissions measurements recorded and reported in accordance with 40 CFR Part 75 shall be used to determine compliance by the unit with the acid rain emissions limitations and emissions reduction requirements for sulfur dioxide (SO₂) under the Acid Rain Program. [40 CFR 72.9(b)(2), 40 CFR 75.2]
- 4. The requirements of 40 CFR Parts 74 and 75 shall not affect the responsibility of the operator to monitor emissions of other pollutants or other emissions characteristics at the unit under other applicable requirements and other provisions of this permit. [40 CFR 72.9(b)(3), 40 CFR 72.5]

Sulfur Dioxide Requirements

- The owners and operators of each source and each affected unit at the source shall:

 (A) Hold allowances, as of the allowance transfer deadline, in the unit's compliance subaccount (after deductions under 40 CFR Part 73, Section 73.34(C)) not less than the total annual emissions of SO₂ for the previous calendar year from the unit, and, [40 CFR 72.9(c)(i)],
 - (B) Comply with the applicable acid rain emissions limitations for SO₂ [40 CFR 72.9(c)(ii)]
- 6. Each ton of SO₂ emitted in excess of the acid rain emissions limitations for sulfur dioxide shall constitute a separate violation of the Act. [40 CFR 72.9(g)(7)]
- 7. SO₂ allowances shall be held in, deducted from, or transferred among allowance tracking system accounts in accordance with the Acid Rain Program. [40 CFR 72.9(g)(4)]

Appendix B Page 19 Facility I.D.#: 800074 Revision #: DRAFT Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

APPENDIX B: RULE EMISSION LIMITS [40CFR 72 - Acid Rain Provisions 11-24-1997]

- 8. A SO₂ allowance shall not be deducted in order to comply with the requirements under paragraph 41(A) of the SO₂ requirements prior to the calendar year for which the allowance was allocated. [40 CFR 72.9(g)(5)]
- 9. An affected unit shall be subject to the SO₂ requirements under the Acid Rain Program as follows: [40 CFR 72.6(a)]
 - (A) Starting January 1, 2000, an affected unit under 40 CFR Part 72, Section 72.6(a)(2); or [40 CFR 72.6(a)(2)]
 - (B) Starting on the later of January 1, 2000 or the deadline for monitor certification under 40 CFR Part 75, an affected unit under 40 CFR Part 72, Section 72.6(a)(3). [40CFR 72.6(a)(3)]
- An allowance allocated by the EPA administrator under the Acid Rain Program is a limited authorization to emit SO₂ in accordance with the Acid Rain Program. No provision of the Acid Rain Program, the acid rain permit application, the acid rain permit, or the written exemption under 40 CFR Part 72, Sections 72.7, 72.8, or 72.14, and no provision of law shall be construed to limit the authority of the United States to terminate or limit such authorization. [40 CFR 72.9 (c)(6)]
- 11. An allowance allocated by the EPA Administrator under the Acid Rain Program does not constitute a property right. [40 CFR 72.9(c)(7)]

Excess Emissions Requirements

- 12. The designated representative of an affected unit that has excess emissions in any calendar year shall submit a proposed offset plan, as required under 40 CFR Part 77. [40 CFR 72.9(e)]
- 13. The owners and operators of an affected unit that has excess emissions in any calendar year shall: [40 CFR 72.9(e)(2)]
 - (A) Pay without demand the penalty required, and pay upon demand the interest on that penalty, as required by 40 CFR Part 77; and [40 CFR 72.9(e)(2)(i)]
 - (B) Comply with the terms of an approved offset plan, as required by 40 CFR Part 77. [40 CFR 72.9(e)(2)(ii)]

Appendix B Page 20 Facility I.D.#: 800074 Revision #: DRAFT Date: April 24, 2008

FACILITY PERMIT TO OPERATE
LA CITY, DWP HAYNES GENERATING STATION

APPENDIX B: RULE EMISSION LIMITS [40CFR 72 - Acid Rain Provisions 11-24-1997]

Recordkeeping and Reporting Requirements

- 14. Unless otherwise provided, the owners and operators of the source and each affected unit at the source that are subject to the acid rain provisions under Title IV shall keep on site at the source each of the following documents for a period of five years from the date the document is created. This period may be extended for cause, at any time prior to the end of five years, in writing by the EPA Administrator or the Executive Officer: [40 CFR 72.9(f)(1)]
 - (A) The certificate of representation for the designated representative for the source and each affected unit at the source and all documents that demonstrate the truth of the statements in the certificate of representation, in accordance with 40 CFR 72.24; provided that the certificate and documents shall be retained on site at the source beyond such five year period until such documents are superseded because of the submission of a new certificate of representation changing the designated representative; [40 CFR 72.9(f)(1)(i)]
 - (B) All emissions monitoring information, in accordance with 40 CFR Part 75, [40 CFR 72.9(f)(1)(ii)]
 - (C) Copies of all reports, compliance certifications, and other submissions and all records made or required under the Acid Rain Program; and, [40 CFR 72.9(f)(1)(iii)]
 - (D) Copies of all documents used to complete an acid rain permit application and any other submission under the Acid Rain Program or to demonstrate compliance with the requirements of the Acid Rain Program. [40 CFR 72.9(f)(1)(iv)]
- The designated representative of an affected source and each affected unit at the source shall submit the reports and compliance certifications required under the Acid Rain Program, including those under 40 CFR Part 72 Subpart I and 40 CFR Part 75. [40 CFR 72.9(f)(2)]

Liability

16. Any person who knowingly violates any requirement or prohibition of the Acid Rain Program, a complete acid rain permit application, an acid rain permit, or a written exemption under 40 CFR Part 72, Sections 72.7, 72.8, or 72.14, including any requirement for the payment of any penalty owed to the United States, shall be subject to enforcement pursuant to Section 113(c) of the Act. [40 CFR 72.9 (g)(1)]

Appendix B Page 21 Facility 1.D.#: 800074 Revision #: DRAFT Date: April 24, 2008

FACILITY PERMIT TO OPERATE LA CITY, DWP HAYNES GENERATING STATION

APPENDIX B: RULE EMISSION LIMITS [40CFR 72 - Acid Rain Provisions 11-24-1997]

- 17. Any person who knowingly makes a false, material statement in any record, submission, or report under the Acid Rain Program shall be subject to criminal enforcement pursuant to Section 113(c) of the Act and 18 U.S.C. 1001. [40 CFR 72.9 (g)(2)]
- 18. No permit revision shall excuse any violation of the requirements of the Acid Rain Program that occurs prior to the date that the revision takes effect. [40 CFR 72.9 (g)(3)]
- 19. Each affected source and each affected unit shall meet the requirements of the Acid Rain Program. [40 CFR 72.9 (g)(4)]
- Any provision of the Acid Rain Program that applies to an affected source (including a provision applicable to the designated representative of an affected source) shall also apply to the owners and operators of such source and of the affected units at the source. [40 CFR 72.9 (g)(5)]
- Any provision of the Acid Rain Program that applies to an affected unit (including a provision applicable to the designated representative of an affected unit) shall also apply to the owners and operators of such unit. Except as provided under 40 CFR Part 72, Section 72.44 (Phase II repowering extension plans) and 40 CFR Part 76, Section 76.11 (NOx averaging plans), and except with regard to the requirements applicable to units with a common stack under 40 CFR Part 75 (including 40 CFR Part 75, Sections 75.16, 75.17, and 75.18), the owners and operators and the designated representative of one affected unit shall not be liable for any violation by any other affected unit of which they are not owners or operators or the designated representative and that is located at a source of which they are not owners or operators or the designated representative. [40 CFR 72.9 (g)(6)]
- 22. Each violation of a provision of 40 CFR Parts 72, 73, 74, 75, 76, 77, and 78 by an affected source or affected unit, or by an owner or operator or designated representative of such source or unit, shall be a separate violation of the Act. [40 CFR 72.9 (g)(7)]

Effect on Other Authorities

No provision of the Acid Rain Program, an acid rain permit application, an acid rain permit, or a written exemption under 40 CFR Part 72, Sections 72.7, 72.8, or 72.14 shall be construed as: [40 CFR 72.9 (h)]

Appendix B Page 22 Facility I.D.#: 800074 Revision #: DRAFT Date: April 24, 2008

FACILITY PERMIT TO OPERATE
LA CITY, DWP HAYNES GENERATING STATION

APPENDIX B: RULE EMISSION LIMITS [40CFR 72 - Acid Rain Provisions 11-24-1997]

- (A) Except as expressly provided in Title IV of the Act, exempting or excluding the owners and operators and, to the extent applicable, the designated representative of an affected source or affected unit from compliance with any other provision of the Act, including the provisions of Title I of the Act relating to applicable National Ambient Air Quality Standards or state implementation plans; [40 CFR 72.9 (h)(1)]
- (B) Limiting the number of allowances a unit can hold; *provided*, that the number of allowances held by the unit shall not affect the source's obligation to comply with any other provisions of the Act; [40 CFR 72.9 (h)(2)]
- (C) Requiring a change of any kind in any state law regulating electric utility rates and charges, affecting any state law regarding such state regulation, or limiting such state regulation, including any prudence review requirements under such state law, [40 CFR 72.9 (h)(3)]
- (D) Modifying the Federal Power Act or affecting the authority of the Federal Energy Regulatory Commission under the Federal Power Act; or, [40 CFR 72.9 (h)(4)]
- (E) Interfering with or impairing any program for competitive bidding for power supply in a state in which such program is established. [40 CFR 72.9 (h)(5)]

NOTICE OF PROPOSED RENEWAL TITLE V PERMIT

The South Coast Air Quality Management District (AQMD) is proposing to renew the existing Title V permit previously issued to the facility listed below:

Facility Locations and Contact People

LOS ANGELES DEPARTMENT OF WATER AND POWER, HAYNES FACILITY

6801 2nd Street Long Beach, CA 90803 Facility ID 800074

Contact Person:

Aram Benyamin
Acting Senior Assistant General Manager
Los Angeles Department of Water and Power,
Haynes Facility
111 North Hope St, Room 1050
Los Angeles, CA 90012

The facility operates 4 utility boilers and 2 gas turbines along with auxiliary equipment used in the production of electrical power.

Pursuant to Title V of the federal Clean Air Act and the AQMD Rule 3004(f), a Title V permit shall expire five years from the date of issuance unless such permit has been renewed. Accordingly, this facility has submitted a Title V renewal application and requested the AQMD to renew their Title V permits. The proposed permit incorporates updates to the facility information provided in the facility's Title V renewal application and all rules and regulations that are currently applicable to this facility.

The proposed permit is available for public review at the AOMD, 21865 Copley Dr., Diamond Bar. CA, and at the Long Beach Public Library, 101 Pacific Avenue, Long Beach, CA 90822. Information regarding the facility owner's compliance history submitted to the AOMD pursuant to California Health & Safety Code Section 42336, or otherwise known to the AOMD based on credible information, is also available from the AOMD for public review. For more information or to review additional supporting documents, call the AOMD's Title V hotline at (909) 396-3013. Written comments should be submitted to Mr. Chris Perri, Air Ouality Engineer. 21865 Copley Drive, Diamond Bar, CA 91765-4178. Comments must be received by June 5, 2008. The AOMD will consider all public comments and may revise the Title V permit in accordance with AOMD rules and regulations.

The public may request the AQMD to conduct a public hearing on the proposed permit by submitting a Hearing Request Form (Form 500-G) to Chris Perri at the above AQMD address. The AQMD will hold a public hearing if there is evidence that the proposed permit is not correct or is not adequate to ensure compliance with regulatory requirements, and a hearing will likely provide additional information that will affect the drafting and/or issuance of the permit. Public hearing request forms and the schedule of public hearings may be obtained from the AOMD by calling the Title V hotline at (909) 396-3013, or from the Internet at http://www.agmd.gov/titlev. Requests for public hearings are due by May 21, 2008. A copy of the hearing request must also be sent by first class mail to the appropriate facility contact person listed above.

South Coast Air Quality Management District

Statement of Basis

Proposed Title V Renewal Permit

Facility Name:

LADWP, Haynes Generating Station

Facility ID: SIC Code:

800074 4940

Equipment Location:

6801 2nd Street

Long Beach, CA 90803

Application #(s):

421794

Application Submittal Date(s):

10/30/03

Permit Revision #:

varies depending on the section

Revision Date:

1/1/08

Permit Section(s) Affected:

All sections (A-K, plus Appendices A and B)

AQMD Contact Person:

Chris Perri, Air Quality Engineer

Phone Number:

(909) 396-2696

E-Mail Address:

cperri@aqmd.gov

1. Introduction and Scope of Permit

Title V is a national operating permit program for air pollution sources. Facilities subject to Title V must obtain a Title V permit and comply with specific Title V procedures to modify the permit. Title V permits are issued in 5 year terms, after which the facility must apply to have the permit renewed. The Title V permit for this facility expired on August 18, 2004. The facility has submitted the necessary information to renew their permit and has satisfied the requirements to obtain an application shield, which allows the continued operation of the facility under the terms and conditions of the existing permit until the permit renewal is approved.

The AQMD implements Title V through Regulation XXX – Title V Permits, adopted by the AQMD Governing Board in order to comply with EPA's requirement that local air permitting authorities develop a Title V program. Regulation XXX was developed with the participation of the public and affected facilities through a series of public workshops, working group meetings, public hearings and other meetings.

The Title V major source threshold for a particular pollutant depends on the attainment status of the pollutant. NO₂, SO₂, and lead are in attainment with federal standards. The status of CO has also recently been changed to attainment. The status for PM-10 is serious nonattainment. The status for ozone is currently extreme nonattainment. For the South Coast Air Basin (SOCAB) the threshold levels are as follows:

Pollutant	SOCAB Major Source Thresholds
VOC	10
NOx	10
SOx	100
CO	50
PM-10	70
Single HAP	10
Combination of HAPS	25

A Title V permit is proposed to be issued to cover the operations of LADWP, Haynes Generating Station located at 6801 2nd Street, Long Beach. This facility is subject to Title V requirements because it is a major source of one or more criteria pollutants.

2. Facility Description

This is an existing facility that is in the business of producing electrical power. This facility operates 4 utility steam boiler/turbine generators and 2 gas turbine generators to produce power for the City of Los Angeles and the State of California. Total facility generating capacity is about 1650 MWs. The boiler units are older installations which were retrofit with SCRs as BARCT control in 2005. The NOx limit on those units is 5 ppm, the CO limit is 2000 ppm, and there is no VOC limit. The 2 turbine units were issued construction permits in 2003 and are equipped with SCR and oxidation catalyst. BACT for the turbines, determined at the time the permits were issued, is 2 ppm NOx, 4 ppm CO, and 2 ppm VOC. There is also a 2500 hp emergency diesel engine, six 38,000 gallon aqueous ammonia storage tanks, and various other auxiliary equipment at the site.

3. Construction and Permitting History

The facility was originally issued air permits in the early 1960's for 6 utility boiler generators (2 are now shutdown). An initial Title V permit was issued to the facility on August 19, 1999 and since then there have been several minor and administrative revisions, and a significant revision when the gas turbines were constructed.

4. Regulatory Applicability Determinations

Applicable legal requirements for this facility are required to be identified in the Title V permit (for example, Section D, E, and H of the proposed Title V permit). Applicability determinations (i.e., determinations made by the District with respect to what legal requirements apply to a specific piece of equipment, process, or operation) can be found in the Engineering Evaluations.

The following summarizes the key rules that apply to the major equipment at this site:

Boilers

401 – Visible Emissions

402 - Nuisance

409 – Combustion Contaminants (PM emissions)

431.1 – Sulfur Content of Natural Gas

431.2 - Sulfur Content of Liquid Fuels

2012 – NOx RECLAIM (monitoring, recordkeeping and reporting of NOx)

Rule 2009 - BARCT

Regulation XXX - Title V

Turbine

218 - Continuous Emission Monitoring

401 – Visible Emissions

402 - Nuisance

407 – Liquid and Gaseous Air Contaminants (CO and SO2 emissions)

409 - Combustion Contaminants (PM emissions)

431.1 - Sulfur Content of Natural Gas

475 – Electric Power Generating Equipment (PM emissions)

Regulation XIII - BACT

2012 – NOx RECLAIM (monitoring, recordkeeping and reporting of NOx)

Regulation XXX - Title V

40 CFR 60 KKKK (Federal New Source Performance Standards)

Emergency Engines

401 – Visible Emissions

402 - Nuisance

431.2 – Sulfur Content of Liquid Fuels

Regulation XIII - BACT

Rule 1470 - Air Toxic Control Measure

2012 - NOx RECLAIM

Regulation XXX - Title V

The facility is not a major source of HAPs and therefore is not subject to any MACT standards. The permit terms and conditions may be found in Sections D and H of the Title V permit.

5. Monitoring and Operational Requirements

Applicable monitoring and operational requirements for the facility are identified in the Title V permit (for example, Section D, F, and J and Appendix B of the proposed Title V permit). Discussion of any applicable monitoring and operational requirements can be found in the Engineering Evaluations. Under Reclaim, the boilers and turbines are required to maintain a CEMS for NOx emissions, and report daily mass emissions through the RTU. As part of the CEMS, the boilers and turbines are also required to be equipped with fuel flow meters. The turbines are required to maintain CEMS for CO emissions, and submit quarterly emission reports for CO. Compliance Assurance Monitoring (CAM) requirements of 40 CFR Part 64 do not apply to the boilers because 1) the boilers use a continuous emissions monitor for NOx [exempt by continuous compliance determination of section 64.2(b)(vi)], 2) there is no CO or PM10 control equipment. CAM does not apply to the turbines because the turbines use continuous emission monitors for NOx and CO. Additionally, the facility is not a major source of VOC emissions.

6. Permit Features

Permit Shield

A permit shield is an optional part of a Title V permit that gives the facility explicit protection from requirements that may be incorrectly specified in the permit. A permit shield is a provision in a permit that states that compliance with the conditions contained in the permit shall be deemed compliance with all identified regulatory requirements. To incorporate a permit shield into the Title V permit involves submission of applications for change of conditions for each equipment affected by the permit shield. Permit shields are addressed in Rule 3004 (c). This facility has not applied for a permit shield.

Streamlining Requirements

Some emission units may be subject to multiple requirements which are closely related or redundant. The conditions may be streamlined to simplify the permit conditions and compliance. Emission limits, work practice standards, and monitoring, recordkeeping, and reporting requirements may be streamlined. Compliance with a streamlined condition will be deemed compliance with the underlying requirements whether or not the emission unit is actually in compliance with the specific underlying requirement. This facility has not applied for any streamlined conditions.

7. Summary of Emissions and Health Risks

Criteria Pollutant Emissions (tons/year) Annual Reported Emissions for Reporting Period 2003-04

Pollutant	Emissions (tons/year)
NOx	110
CO	184
VOC	108
PM	31
SOx	10

Toxic Air Contaminants Emissions (TAC) Annual Reported Emissions for Reporting Period 2003/2004

The Following TACs Were Reported	Emissions (lbs/yr)
Asbestos	0.036
Benzene .	47.4
1,3-Butadiene	4.8
Cadmium	0.028
Formaldehyde	122.4 ,
Hexavalent Chrome	0.002
Inorganic Arsenic	0.030
Lead	0.15,7
Nickel	0.076

Polynuclear aromatic hydrocarbons (PAHs)	10.9
Ammonia	211,508

Health Risk from Toxic Air Contaminants

The facility is subject to review by the Air Toxics Information and Assessment Act (AB2588). The Final Facility Health Risk was approved on 8/11/00 with the following risk factors:

Cancer Risk 0.17 in one million Acute Hazard Index 0.0 Chronic Hazard Index 0.01

8. Compliance History

The facility has been subject to both self-reporting requirements and AQMD inspections. The facility has had 7 citizen complaints filed, 0 Notices to Comply issued, and 3 Notices of Violation issued in the last two calendar years.

9. Compliance Certification

By virtue of the Title V permit application and renewal of this permit, the reporting frequency for compliance certification for the facility shall be annual.

10. Comments

There are no comments at this time.

SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT

ENGINEERING DIVISION

APPLICATION PROCESSING AND CALCULATIONS

PAGES 2	PAGE I
APPL. NO.	DATE
421794	1/25/2008
PROCESSED BY	CHECKED BY
CGP	

TITLE V PERMIT RENEWAL

COMPANY NAME AND ADDRESS:

LADWP, Haynes Generating Station 111 North Hope St, Room 1050 Los Angeles, CA 90012

EQUIPMENT LOCATION:

6801 2nd Street Long Beach, CA 90803

BACKGROUND:

This is an existing facility which is in the business of providing electrical power for the City of Los Angeles and the State of California. The facility operates 4 utility steam boiler generators and 2 combined cycle gas turbine generators, along with auxiliary equipment. Approximate total facility generating capacity is 1650 MW.

The facility was issued its initial Title V permit on August 19, 1999. The Title V permit expired on August 18, 2004, however the facility submitted its Title V renewal application on October 31, 2003, which is within the timeframe required to obtain an application shield. AQMD sent a letter to the facility on February 20, 2004 indicating that an application shield had been granted, therefore, the facility is currently operating under its application shield.

The application package contained the required forms, appropriately completed and signed, as follows:

400-A	500-C1	500-B
500-A2	500-H	500-F1

Along with a fee of \$645.86, which was the correct filing fee at the time the application was submitted.

SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT

ENGINEERING DIVISION

APPLICATION PROCESSING AND CALCULATIONS

PAGES 2	PAGE 2
APPL. NO.	DATE
421794	1/25/2008
PROCESSED BY	CHECKED BY
CGP	

COMPLIANCE RECORD REVIEW:

There are currently no outstanding compliance issues with the facility. The facility was issued 4 Notices to Comply and 9 Notices of Violation since the initial Title V permit was issued. The notices are summarized below:

Notice#	Violation	Description
4.1034	Date	
C70463	12/31/01	Perform tune up of ICE D53
C70464	3/21/02	Report breakdowns within 1 hour
C70467	9/10/02	Follow missing data procedures, submit breakdown emission report
C70470	4/29/03	Perform Unit #2 RATA on time
P10746	4/11/01	Exceeded allocation for 1998 NOx
P12166	4/15/03	Amonia injection for Unit #5
P28726	9/10/02	Failed to conduct valid CEMS calibration for D9
P28732	1/7/03	Various violations of Rule 2009 for plan submittal and meeting
		BARCT limit on Units 3 and 4
P45250	10/6/04	Improperly permitted oil/water separator
P45255	3/24/05	Unit #10 exceeded 2 ppm NOx limit, Unit #9 exceeded 15 minute
		shutdown limit
P45260	8/31/05	Unit #9 exceeded 2 ppm NOx limit
P51112	12/8/07	Unit #9 exceeded NOx limit
P51113	1/3/08	Unit #10 exceeded NOx and CO limit

DISCUSSION:

The following clarification/corrections are being made to the permit:

Device D53

This emergency diesel engine is subject to Rule 1470 and is limited to 20 operating hours/yr for maintenance and testing purposes. Language has been added to conditions C1.3 specifying the 20 hr/yr limit, and condition E116.1 has been added to the engine specifying that the engine cannot be used as part of a demand response program. Also, record keeping conditions K67.5 has been added to reflect the requirements of Rule 1470.

RECOMMENDATION:

After completion of the public notice and EPA review period, a Title V renewal permit should be issued for a new 5 year period, incorporating the above-described changes.



Mail Application To: P.O. Box 4944 Diamond Bar, CA 91765

Tel: (909) 396-3385 www.aqmd.gov

Section I - Facility Information		
Permit to be issued to (Business name of operator to appear on permit):		y ID (Available on Permit or Invoice
LA City DWP, Haynes Generating Station	Issued by AQMD):	800074
a Title V Application (Initial, Revision or Rer	newal)	CORD AND A CORD COMMENT OF A CORD COMMENT OF
3. This Certification is		•
submitted with a (Check one): c. (MACT Part 2.	,	
Section II - Responsible Official Certification Statement		
I certify under penalty of law that I am the responsible official for this far information and belief formed after reasonable inquiry, the statements a forms and other materials are true, accurate, and complete. Read each statement carefully and check each that applies – You must carefully and check each that applies – You must carefully and check each that applies – You must carefully and check each that applies – You must carefully and check each that applies – You must carefully and check each that applies – You must carefully each careful that the careful that are	nd information in this docum	
For Initial, Permit Renewal, and Administrative Application Certific	·	
 The facility, including equipment that are exempt from written operate in compliance with all applicable requirement(s) identified 	permit per Rule 219, is curr	
 i. <u>except</u> for those requirements that do not specifical identified as "Remove" on Section III of Form 500-C1. 	lly pertain to such devices of	or equipment and that have been
ii. <u>except</u> for those devices or equipment that have been <u>not</u> be operating in <i>compliance</i> with the specified appli	•	and attached Form 500-C2 that will
 The facility, including equipment that are exempt from written requirements with future effective dates. 	permit per Rule 219, will mee	et in a timely manner, all applicable
2. For Permit Revision Application Certifications:		•
 The equipment or devices to which this permit revision applies identified in Section II and Section III of Form 500-C1. 	s, will in a timely manner com	ply with all applicable requirements
3. For MACT Hammer Certifications:		
a. C The facility is subject to Section 112(j) of the Clean Air Act (Su The following information is submitted with a Title V applicati Part 2 has not been submitted, you must submit 500-MACT Pa	ion to comply with the Part 1	
b. The facility is not subject to Section 112(j) of the Clean Air Act	t (Subpart B of 40 CFR part 63	3).
If Bo		0/11/28
Signature of Responsible Official	•	Date
Aram H. Benyamin Type or Print Name of Responsible Official	00. / AN	(213) 367-4435 Phone
Acting Senior Assistant General Manager - Power System		(213) 367-0313
Title of Responsible Official	**************************************	Fax
111 N. Hope Street, room 1050	Los Angeles	CA 90012
Address of Responsible Official	City	State Zip Code

Acid Rain Facilities Only: Turn page over & complete Section III

Acid Rain facilities must certify their compliance status of the devices subject to applicable requirements under Title IV by an individual who meets the definition of Designated (or Alternate) Representative in 40 CFR Part 72.

Section III - Designated Representative Certification Statement	
1. For Acid Rain Facilities Only: I am authorized to make this submiss or affected units for which the submission is made. I certify unde with, the statements and information submitted in this document a with primary responsibility for obtaining the information, I certify the and belief true, accurate, and complete. I am aware that ther information or omitting required statements and information, include	sion on behalf of the owners and operators of the affected source or penalty of law that I have personally examined, and am familiar and all its attachments. Based on my inquiry of those individuals at the statements and information are to the best of my knowledge of are significant penalties for submitting false statements and
Mark J. Sedlack	2/15/08
Signature of Designated Representative or Alternate	Ďate
Mark J. Sedlacek	(213) 367-0403
Type or Print Name of Designated Representative or Alternative	e Phone
Director of Environmental Services	. (213) 367-4710
Title of Designated Representative or Alternate	Fax
111 N. Hr. 54 R. 1050, Address of Designated Representative or Alternate	Los Argelis CA 90012
Address of Designated Representative or Alternate	City State Zip Code

Enclosure 3 – AQMD Form 500 – C1



SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT Compliance Status Report

To provide the compliance status of your facility with applicable federally enforceable requirements and identify other local-only requirements, complete this form and attach it to a completed compliance certification Form 500-A2. As appropriate, all submittals of Form 500-C2 as appropriate should also be attached to this form.

Section I - General Information

Facility Name:

HAYNES GENERATING STATION

Facility ID (6-Digit): 800074

PROCEDURES FOR DETERMINING COMPLIANCE STATUS

- Equipment verification: Review the list of pending applications, and either the preliminary Title V facility permit or the list of current permits to operate that the AQMD provided you, to determine if they completely and accurately describe all equipment operating at the facility. Attach a statement to describe any discrepancies.
- methods, and monitoring, recordkeeping and reporting (MRR) requirements that apply to any equipment or process (including equipment exempt from a permit by Rule 219) Identify applicable requirements*: Use the checklist in Section II to identify all applicable and federally-enforceable local, state, and federal rules and regulations, test at your facility.
- The potential applicable requirements, test methods and MRR requirements are identified and listed adjacent to each given equipment/process description. Check off each box adjacent to the corresponding requirement as it applies to your particular equipment/process.
 - Note: Even if there is only one piece of equipment that is subject to a particular requirement, the appropriate box should be checked.
- applicable requirements. It does not include recently adopted NESHAP regulations by EPA or recent amendments to AQMD rules. Do not add rules listed in Section V here. Identify additional applicable requirements*: Use Section III to identify any additional requirements not found in Section II. Section II is not a complete list of all
 - that do not apply to a specific piece of equipment or process. Fill out Section III of this form and attach a separate sheet to explain the reason(s) why the identified rules do not apply. Note: Listing any requirement that does not apply to a specific piece of equipment will not provide the facility with a permit shield unless one is specifically requested. Identify any requirements that do not apply to a specific piece of equipment or process: Also use Section III to identify any requirements that are listed in Section II but by completing Form 500-D and is approved by AQMD.
- the State Implementation Plan (SIP), and that are still applicable requirements as defined by EPA. The facility is not required to certify compliance with the items checked in Identify SIP-approved rules that are not current AQMD rules: Use Section IV to identify older versions of current AQMD rules that are the EPA-approved versions in Section IV provided that the non-SIP approved rule in Section II is at least as stringent as the older SIP-approved version in Section IV.
- Identify Local-Only Enforceable Regulatory Requirements: Use Section V to identify AQMD rules that are not SIP-approved and are not federally enforceable.
- Determine compliance: Determine if all equipment and processes are complying with all requirements identified in Sections II and III. If each piece of equipment complies with all applicable requirements, complete and attach Form 500-A2 to certify the compliance status of the facility. If any piece of equipment is not in compliance with any of the applicable requirements, complete and attach Form 500-C2 in addition to Form 500-A2.
- The following AQMD rules and regulations are not required to be included in Section II and do not have to be added to Section III: Regulation I, List and Criteria in Regulation 11, Rule 201, Rule 201.1, Rule 202, Rule 203, Rule 205, Rule 206, Rule 207, Rule 209, Rule 209, Rule 210, Rule 212, Rule 214, Rule 215, Rule 216, Rule 217, Rule 219, Rule 220, Rule 221, Regulation III, Regulation V, Regulation VIII, Regulation XII, Regulation XV, Regulation XVI, Regulation XIX, Regulation XXI, Regulation XXII, and Regulation
- ** Emission units adversely affected by the gap between current and SIP-approved versions of rules may initially be placed in a non-Title V portion of the permit

-EQUIPMENT/FROCESS	APPLICABLE REQUIREMENT	TEST METHOD	MRR REQUIREMENT
All Air Pollution Control Equipment Using	Rule 480 (10/07/77)	N/A	N/A
Combustion (RECLAIM & non-RECLAIM counces)		; ;	
X All Coating Operations	X Rule 442 (12/15/00)	X Rule 442(f)	X Rule 442(g)
All Combustion Equipment, ≥ 555	Rule 474 (12/04/81)	AQMD TM 7.1 or 100.1	
Mmbtu/Hr (except for NOx RECLAIM sources)		4	
All Combustion Equipment Except Internal Combustion Engines (RECLAIM & non-	X Rule 407 (04/02/82) X Rule 409 (08/07/81)	X AQMD TM 100.1 or 10.1, 307-91 X AQMD TM 5.1, 5.2, or 5.3	
RECLAIM sources) All Combustion Equipment Using Gaseous	X Rule 431.1 (06/12/98)	X Rule 431.1(f)	Kule 431.1(d) & (e)
Fuel (except SOx RECLAIM sources)			
X All Combustion Equipment Using Liquid	X Rule 431.2 (09/15/00)	X Rule 431.2(g)	X Rule 431.2(f)
(except SOx RECLAIM sources)			
All Combustion Equipment Using Fossil Fuel (except SOx RECLAIM sources)	X Rule 431.3 (05/07/76)		
X All Equipment	X Rule 401 (11/09/01)	X California Air Resources Board	
	X Pude 405 (02/07/86)	Visible Emission Evaluation X AOMD TM 5 5 2 or 5 3	
		7 - 10 - 17 - 17 - 17 - 17 - 17 - 17 - 1	
	X Rule 430 (07/12/96)	N/A	X Rule 430(b)
	X Kuie /01 (00/13/97) X New Source Review, BACT		
•	X Rule 1703 (10/07/88)		
	■ 40 CFR68 - Accidental Release Prevention	See Applicable Subpart	See Applicable Subpart
All Equipment Processing Solid Materials	☐ Rule 403 (04/02/04)	Rule 403(d)(4)	☐ Rule 403(f)
All Equipment With Exhaust Stack	X Rule 404 (02/07/86)	X AQMD TM 5.1, 5.2, or 5.3	ı,
(except cement kilns subject to Kule 1112.1)	, Calcalan (02/07/07)	V P1- 100/-3	n.12 100/23
A All Facilities Using Solvents to Clean Various		X Kule 109(g) X Rule 1171(f)	X Kule 109(¢) X Rule 1171(¢)(6)
Items or Equipment	🔀 40 CFR63 SUBPART T	See Applicable Subpart	See Applicable Subpart
X All RECLAIM Equipment (NOx & SOx)	Reg. XX - RECLAIM	Rule 2011, App. A (12/05/03)	Rule 2011, App. A (12/05/03)
X Abrasive Blasting	X Rule 1140 (08/02/85)	Rule 1140(d) & (e), AQMD Visible Emission Method	
Aggregate and Related Operations	Rule 1157 (01/07/05)	Rule 1157(f)	Rule 1157(e)
Appliances Containing Ozone Depleting Substances (except Motor Vehicle Air Conditioners): Manufacturing, Repair, Maintenance, Service, & Disposal	☐ 40 CFR82 SUBPART F	See Applicable Subpart	See Applicable Subpart
Maintenance, Service	1 00	مستنبدا اسمامي عن مامي	
KEY Reg = AQMD Regulation	App. = Appendix	CFR = Code of Federal Regulations	AQMD Form Rev. 05/05

Section II - Applicable Requirements, Test Methods, & MRR Requirements	s, Test Methods, & MRR Requirem	ients	
EQUIPMENT/PROCESS	APPLICABLE REQUIREMENT	TEST METHOD	MRR REQUIREMENT
Asphalt	See Manufacturing, Asphalt Processing & A	Asphalt Roofing	
Asphalt Concrete/Batch Plants	SUBPARTI	See Applicable Subpart *	See Applicable Subpart
Benzene Emissions, Maleic Anhydride	۱. ـ	Rule 1173(j)	Rule 1173(i)
Plants,	-	Rule 1176(h)	Rule 1176(f) & (g)
Ethylbenzene/Styrene Plants, Benzene		See Applicable Subpart	See Applicable Subpart
Storage Vessels, Benzene Equipment Leaks,		See Applicable Subpart	See Applicable Subpart
& Coke By-Product Recovery Plants	SUBPART	See Applicable Subpart	See Applicable Subpart
	40 CFR63 SUBPART CC	See Applicable Subpart	See Applicable Subpart
Benzene Transfer Operations		Rule 1142(e)	Rule 1142(h)
		See Applicable Subpart	See Applicable Subpart
	40 CFR63 SUBPART Y	See Applicable Subpart	See Applicable Subpart
Benzene Waste Operations			☐ Rule 1176(f) & (g)
		See Applicable Subpart	See Applicable Subpart
Bertiliim Emissions	H 40 CFK03 SUBLAKT CC	See Applicable Subpart	See Applicable Subpart
Beryllium Emissions. Rocket Motor Firing		See Amplicable Subpart	See Applicable Subpart
Boiler, < 5 Mmbtu/Hr (non-RECLAIM)	1.4	Rule 1146.1(d)	Rule 1146.1(c)(2) & (c)(3)
sources)	\square Rule 1146.2 (01/07/05)	N/A	
	U 40 CFR63 SUBPART DDDDD	See Applicable Subpart	See Applicable Subpart
☐ Boiler, < 5 Mmbtu/Hr (RECLAIM sources)	Rule 1146.1 (05/13/94) - excluding	☐ Rule 1146.1(d)	Rule 1146.1(c)(2) & (c)(3)
	NOx requirements	200 - 1-1-00 Claim A 00 D	0 A
	_ ! '	see Applicable Subpart	See Applicable Suppari
☐ Boiler, ≥ 5 Mmbtu/Hr (non-RECLAIM	Rule 218 (05/14/99)	AQMD TM 100.1	Rule 218(e) & (f)
sources)		N/A	Rule 429(d)
,	Kule 4/5 (08/07/78)	AQMD IM 5.1, 5.2, or 5.3	
	[Kule 4/6 (10/08/76)]	AQMD 1M /.1, 100.1, 5.1, 5.2, or 5.3	D. 1 - 1 1 4 0 0 0 0 0 0 0 0
	Kule 1140 (11/1//00) 1 40 CED 40 STED 4 P.T. D	See A 221 222 A 221 222 A 222	C_{conf} And C_{conf}
		See Applicable Suopart	See Applicable Suppart
		See Applicable Subpair	See Applicable Subpart
		See Applicable Subpart	See Applicable Subpart
⊠ Boiler, ≥ 5 Mmbtu/Hr (RECLAIM sources)	1.	☐ AQMD TM 5.1, 5.2, or 5.3	
	X Rule 476 (10/08/76) - excluding	X AQMD TM 7.1, 100.1, 5.1, 5.2, or 5.3	
	NOx requirements	Dlo. 1146/2\	D.12 1145/2/(5) & (2)/7)
		Kuie 1140(d)	Kuie 1140(c)(0) & (c)(7)
•	NOX requirements X Rule 2011 (12/05/03) or		
	Rule 2012 (12/05/03)	Rule 2012. App. A (12/05/03)	or
·		See Applicable Subpart	Rule 2012, App. A (12/05/03)
	☐ 40 CFR60 SUBPART Da	See Applicable Subpart	See Applicable Subpart
	_	See Applicable Subpart	See Applicable Subpart
] 40 CFR63 SUBPART DDDDD	See Applicable Subpart	See Applicable Subpart
:			
•	App. = Appendix	CFR = Code of Federal Regulations	
ABBREVIATIONS: Rule = AQMD Rule	D Test Method	CCR = California Code of Regulations	500-C1 Page 3 of 3

Section II - Appli	cable Requirements,	Section II - Applicable Requirements, Test Methods, & MRR Requirements	ements	
EQUIPMENT/PROCESS	S	APPLICABLE REQUIREMENT	TEST METHOD	MRR REQUIREMENT
				See Applicable Subpart
Boiler, Petroleum R	Boiler, Petroleum Refining (non-RECLAIM	Rule 218 (05/14/99)	☐ AQMD TM 100.1	□ Rule 218(e) & (f)
somces)		Rule 429 (12/21/90)	N/A	Rule 429(d)
		Rule 431.1 (06/12/98)	□ Rule 431.1(f)	Rule 431.1(d) & (e)
	•	$\overline{}$	☐ AQMD TM 5.1, 5.2, or 5.3	
		Rule 1146 (11/17/00)	Rule 1146(d)	\square Rule 1146(c)(6) & (c)(7)
		•	See Applicable Subpart	See Applicable Subpart
		40 CFR63 SUBPART DDDDD	See Applicable Subpart	See Applicable Subpart
🔲 Boiler, Petroleum Refining (RECLAIM	tefining (RECLAIM	Rule 1146 (11/17/00) - excluding	Rule 1146(d)	\square Rule 1146(c)(6) & (c)(7)
sources)		NOx requirements.		(
		_	$ \Box$ Rule 2011, App. A (12/05/03) or	Rule 2011, App. A (12/05/03)
	· ·		Rule 2012, App. A (12/05/03)	
	•	• -	See Applicable Subpart	Rule 2012, App. A (12/05/03)
	•	40 CFR63 SUBPART DDDDD	See Applicable Subpart	See Applicable Subpart
				See Applicable Subpart
📗 Boilers, Electric Uti	Boilers, Electric Utility (non-RECLAIM	Rule 218 (05/14/99)	. 🔲 AQMD TM 100.1	□ Rule 218(e) & (f)
sources)		Rule 429 (12/21/90)	N/A	□ Rule 429(d)
		Rule 1135 (07/19/91)	Rule 1135(e)	Rule 1135(e)
		☐ 40 CFR60 SUBPART Db	See Applicable Subpart	See Applicable Subpart
•		☐ 40 CFR63 SUBPART DDDDD	See Applicable Subpart	See Applicable Subpart
Boilers, Electric Uti	Boilers, Electric Utility (RECLAIM sources)	Rule 2012 (12/05/03)	Rule 2012, App. A (12/05/03)	Rule 2012, App. A (12/05/03)
		40 CFR60 SUBPART Db	See Applicable Subpart	See Applicable Subpart
•		7 40 CFR63 SUBPART DDDDD	See Applicable Subpart	See Applicable Subpart
Bulk Loading Of Organic Liquids	reanic Liquids	Rule 462 (05/14/99)		Rule 462(g)
,	,	7 40 CFR60 SUBPART XX	See Applicable Subpart	See Applicable Subpart
		[] 40 CFR63 SUBPART R	See Applicable Subpart	See Applicable Subpart
		1 40 CFR63 SURPART FFFF	See Amilicable Subnart	See Applicable Subpart
		1 40 CFR63 SUBPART GGGG	See Applicable Subpart	See Annicable Subnart
Cadminm Flactronlating Operation	oting Operation	Pule 1426 (05/02/03)		Dula 1426(a)
Cotomor Mineral L	ating Operation	1 40 CEB 40 CITED A B T 1 11 1 1	0 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	Nate 1420(e)
Calciner, Mineral Industries	Idustries	al.	See Applicable Subpart	see Applicable Suppart
Calciner, Petroleum Coke	Coke	Rule 477 (04/03/81)	AQMD Visible Emissions, AQMD	•
	•		IM 5.1, 5.2, or 5.3	
		Kule 1/19 (03/02/19) 40 CEB 23 STIPB A B.T.	S 22 A 2215 25-1-25 25	S - A 1:
Charbanian	2		See Applicable Subpail	see Applicable Subpair
Chaldioners	-		A A CIVID TEST PROTOCOL	D. 1138(d)
Chroma Diating 8.	Promis Asid Anglining	~1 \	(g) (g)	Naie 1130(d)
Operation	Omeration		Rule 1469(e)	$[R_{\text{nle}} = 1420(e)]$ (i) & (k)
Costing Operation	Costing Operation Adhasing Application		- D.I. 100/2	3
Oneration	nuicaive application	Nule 102 (03/02/03) Rule 481 (01/11/02)	Nule 109(g) Rule 481(d)	(2)kg 103(c)
	•	Rule 1132 (05/07/04)		Rule 1132(9)
		Rule 1168 (01/07/05)	Rule 1168(f) & (g)	Rule 1168(e)
KEY	Reg. = AQMD Regulation	App. = Appendix	CFR = Code of Federal Regulations	AQMD Form Rev. 05/05
ABBREVIATIONS:	Rule = AQMD Rule	AQMD TM = AQMD Test Method	CCR = California Code of Regulations	

:

Section II = Applicable Requirements Test Methods - R/W	Test Methods & MRR Requirements	nents		3 6
EQUIPMENT/PROCESS		тезт метнор	MRR REQUIREMENT	
	☐ Rule 1171 (11/07/03)	Rule 1171(f)	Rule 1171(c)(6)	
\$	☐ 40 CFR60 SUBPART RR	See Applicable Subpart	See Applicable Subpart	
Coating Operation, Aerospace Assembly &	Rule 109 (05/02/03)	Rule 109(g) Rule 109(d)	Rule 109(c)	٠
Component Manufacturing	Kule 481 (01/11/02) Rule 1124 (09/21/01)			
	Rule 1132 (05/07/04)	\square Rule 1132(\mathfrak{t})	. Rule 1132(g)	
		Rule 1171(f)	Rule 1171(c)(6)	
	40 CFR63 SUBPART GG	See Applicable Subpart	See Applicable Subpart	٠
Coating Operation, Graphic Arts (Gravure,	Rule 109 (05/02/03)	Rule 109(g)	Rule 109(c)	
Letter Press, Flexographic & Lithographic			D. 1120(2)	
Frinting Process, Etc.)	Kule 1130 (10/08/99) Rule 1132 (05/07/04)	Kule 1130(h) Rule 1132(f)	Kule 1130(e) 	
	Rule 1171 (11/07/03)			
	☐ 40 CFR60 SUBPART QQ	See Applicable Subpart	See Applicable Subpart	
	40 CFR60 SUBPART RR	See Applicable Subpart	See Applicable Subpart	
	40 CFR60 SUBPART FFF	See Applicable Subpart	See Applicable Subpart	
		See Applicable Subpart	See Applicable Subpart	
		See Applicable Subpart	See Applicable Subpart	-
	40 CFK63 SUBPART JJJJ	See Applicable Subpart	See Applicable Subpart	. ,
Coating Operation, Magnet Wire Coating	Kule 109 (05/02/03) Pule 481 (01/11/02)		Kule 109(c)	· /
	Rule 1126 (01/11/02)			
1	Rule 1132 (05/07/04)	Rule 1132(d)	\square Rule 1132(σ)(τ)	
	Rule 1171 (11/07/03)		\square Rule 1171(c)(6)	23
Coating Operation, Marine Coating (Except	Rule 109 (05/02/03)	Rule 109(g)	☐ Rule 109(c)	,
for	Rule 481 (01/11/02)	Rule 481(d)	. [
recreational equipment)	Rule 1106 (01/13/95)	Rule 1106(e)	Rule 1106(c)(5)	
	Rule 1132 (05/07/04)	Rule 1132(f)	Rule 1132(g)	
		Kule 11/1(t) See Amplicable Submat	See Annicohla Suhnart	•
X Coating Operation Metal Coating	. [See Applicable Subpair	V Pula 100(c)	
amino morni (mornino)			(2) (c)	
	X Rule 1107 (11/09/01)		X Rule 1107(k)	,
*	☐ Rule 1132 (05/07/04)	Rule 1132(f)	Rule 1132(g)	
•		X Rule 1171(f)	. X Rule 1171(c)(6)	
		See Applicable Subpart	See Applicable Subpart	
		See Applicable Subpart	See Applicable Subpart	-
	SUBPART	See Applicable Subpart	See Applicable Subpart	
	40 CFR63 SUBPART MMMM	See Applicable Subpart See Applicable Subpart	See Applicable Subpart	
Coating Operation, Metal Containers,	1	Rule 109(g)	Rule 109(c)	
Closure,	Rule 481 (01/11/02)	Rule 481(d)		
& Coil Coating Operations	Rule 1125 (01/13/95)	Rule 1125(e)	☐ Rule 1125(c)(6)	
Reg = AQMD Regulation ARREVIATIONS: Rule = AOMD Rule	App. = Appendix AOMD TM = AOMD Test Method	CFR = Code of Federal Regulations	AQMD Form Rev. 05/05	
1	באר שכנוסם	בכון – במינוסו וומ כספב כו מבצחמת מווז		

Section II - Applicable Requirements, Test Meth	. Test Methods, & MRR Requirements	ients	
EQUIPMENT/PROCESS	APPLICABLE REQUIREMENT	TEST METHOD	MRR REQUIREMENT
	☐ Rule 1132 (05/07/04)	Rule 1132(f)	
	_	☐ Rule 1171(f)	Rule 1171(c)(6)
	• -	See Applicable Subpart	See Applicable Subpart
	SUBPART	See Applicable Subpart	See Applicable Subpart
	40 CFR63 SUBPART SSSS	See Applicable Subpart	See Applicable Subpart
Coating Operation, Motor Vehicle & Mobile	Rule 109 (05/02/03) · · · · · · · · · · · · · · · · · · ·	Rule 109(g) .	Rule 109(c)
Operation Control Coaming			Rule 1132(a)
Operation			Null 115±(6) Rule 115±(7)
			Rule 1171(c)(6)
Coating Operation, Motor Vehicle Assembly	10	Rule 109(g)	□ Rule 109(c)
Line	\square Rule 481 (01/11/02)	Rule 481(d)	
	_	. 🔲 Rule 1115(e)	Rule 1115(g)
	_	Rule 1132(f)	Rule 1132(g)
	_	Rule 1171(f)	\square Rule 1171(c)(6)
**	SUBPART	See Applicable Subpart	See Applicable Subpart
	40 CFK63 SUBPAKI IIII	See Applicable Subpart	See Applicable Subpart
Coating Operation, Paper, Fabric, & Film	Rule 109 (05/02/03)	Rule 109(g)	Rule 109(c)
Coaung Operations		Kuië 461(d) The feet 129(4)	. (%)6(11)9(%)
			Nuic 1120(e) Rule 1132(a)
-	_		
	_ •	Cas Annicable Subnert	See Annicable Subnart
		See Applicable Subpair	See Applicable Subpair
	1000000	See Applicable Subpair	See Applicable Subpair
Coaung Operanon, Flasue, Kubber, & Glass	Rufe 103 (02/02/03)		Kuie 109(c)
	\square Rule 1145 (12/03/04)	Rule 1145(e)	Rule 1145(d)
	_	□ Rule 1132(f)	Rule 1132(g)
	_	☐ Rule 1:171(f)	☐ Rule 1171(c)(6)
		See Applicable Subpart	See Applicable Subpart
	SUBPART	See Applicable Subpart	See Applicable Subpart
	40 CFR63 SUBPART PPPP	See Applicable Subpart	See Applicable Subpart
Coating Operation, Pleasure Craft	Rule 109 (05/02/03)		Rule 109(c)
	Rule 1106.1 (02/12/99)	Rule 1106.1(e)	Rule 1106.1(d)
	☐ Rule 1 i 32 (05/07/04)	Rule 1132(f)	Rule 1132(g) .
		□ Rule 1171(f) .	Rule 1171(c)(6)
	40 CFR63 SUBPART II	See Applicable Subpart	See Applicable Subpart
Coating Operation, Screen Printing	Rule 109 (05/02/03)	Rule 109(g)	☐ Rule 109(c)
		Kule 1130.1(g) 	
,	171 (Rule 1171(f)	Rule 1171(c)(6)
KEY Reg.= AQMD Regulation ARREVIATIONS: Pule - AOMD Pule	App. = Appendix	CFR = Code of Federal Regulations	AQMD Form Rev. 05/05
	אלאים ואין – אלאים ופזר איפווסם	Ch = Catilorina Code of Regulations	300-C1 rage 0.01 0

Section II - Applicable Require	Section Sapplicable Requirements, Test Methods: & MRR Requirements	nents	
EQUIPMENT/PROCESS	APPLICABLE REQUIREMENT	ТЕЅТ МЕТНОD	MRR REQUIREMENT
	. ,	See Applicable Subpart	See Applicable Subpart
X Coating Operation, Use Of Architectural		X Rule 109(g)	X Rule 109(c)
Coating (Stationary Structures)	X Rule 481 (01/11/02) Y D 11/13 (07/09/04)	X Rule 481(d) X Bule 1113(e)	•
•	Rule 1132 (05/07/04)		Rule 1132(g)
		$ \mathbf{X} $ Rule 1171(f)	X Rule 1171(c)(6)
Coating Operation, Wood Flat Stock	Rule 109 (05/02/03)	Rule 109(g)	Rule 109(c)
		Rule 481(d)	
	Kule 1104 (08/13/99) 	Kule 1104(e)	Kule 1104(d) Rule 1132(a)
		Nume 1122(1) Rule 1171(f)	
		See Applicable Subpart	See Applicable Subpart
Coating Operation, Wood Products		Rule 109(g)	Rule 109(c)
(Commercial Furniture, Cabinets, Shutters,	tters, Rule 481 (01/11/02)	Rule 481(d) P.:Jo 1123/6	D.12 1122(x)
ridnies, 10ys)		Kule 1132(1) .	
	Rule 1171 (11/07/03)	Rule 1171(f)	Rule 1171(c)(6)
The state of the s	40 CFR63 SUBPART JJ	See Applicable Subpart	See Applicable Subpart
Coater	See Coating Operations		
Columns	See Petroleum Refineries, Fugitive Emissions	ıns	
Composting Operation			
· .		Kule 1133.1(e) Rule 1133.2(o)	Kuie 1133.1(d)
Compressors		eries. Fugitive Emissions	
Concrete Batch Plants	See Nonmetallic Mineral Processing Plants	0	
Consumer Product Manufacturing	See Manufacturing, Consumer Product		
Cooling Tower, Hexavalent Chromium		See Applicable Subpart	See Applicable Subpart
Copper Electroplating Operation	☐ Rule 1426 (05/02/03)		. Rule 1426(e)
Crude Oil Production	See Oil Well Operations		
Crusher	See Nonmetallic Mineral Processing Plants		
Dairy Farms and Related Operations	Rule 1127	Rule 1127(h)	Rule 1127(g)
X Degreasers	X Rule 109 (05/02/03)	X Rule (109(g)	X Rule 109(c)
	X Rule 1172 (10/01/04)	X Rule 1122(fl)	
	40 CFR63 SUBPART T	See Applicable Subpart	See Applicable Subpart
Dry Cleaning, Perchloroethlyene	Rule 1421 (12/06/02)	Rule 1421(e) & (i)	Rule 1421(g) & (h)
Dry Cleaning, Petroleum Solvent	. Rule 109 (05/02/03)	Rule 109(g)	Rule 109(c)
	Kule 1102 (11/1//00) 40 CFR60 STIRPART III	Kule 1102(g) See Amplicable Sukmart	See Applicable Subpart
Dryers, Mineral Industries	40 CFR60 SUBPART UUU	See Applicable Subpart	See Applicable Subpart
Ethylene Oxide Sterilizer	See Sterilizer, Ethylene Oxide		
Flanges	See Fugitive Emissions or Petroleum Refineries, Fugitive Emissions	eries, Fugitive Emissions	*
	ation App. = Appendix	CFR = Code of Federal Regulations	
ABBREVIATIONS: Kule = AUMU Kule	AUMD IM = AUMD lest Method	CCR = California Code of Regulations	500-C1 Page 7 of 7

i i				
Section II - Applicable Requirements, Test Methods, & M	Test Methods: & MRR Requirements	ements		
EQUIPMENT/PROCESS	APPLICABLE REQUIREMENT	тезт метнор	MRR REQUIREMENT	
Fluid Catalytic Cracking Unit	Rule 218 (05/14/99)	☐ AQMD TM 100.1.	Rule 218(e) & (f)	
	Rule 1105 (09/01/84) Rule 1105.1 (11/07/03)	Rule 1105(c)(1) Rule 1105 1(f)	Rule 1105(c)(2) Rule 1105.1(e)	
Foundries, Iron and Steel	40 CFR63 SUBPART EEEEE	See Applicable Subpart	, See Applicable Subpart	•
Friction Materials Manufacturing	See Manufacturing, Friction Materials			٠
Fugitive Emissions, Benzene	Rule 1173 (12/06/02)	Rule 1173(j)	Rule 1173(i)	:
	40 CFR61 SUBPART L	See Applicable Subpart	See Applicable Subpart	
	40 CFR61 SUBPART V 40 CFP63 STIRDART B	See Applicable Subpart	See Applicable Subpart	
		See Applicable Subpart See Applicable Subpart	See Applicable Subpart	
Fugitive Emissions, Chemical Plant	Rule 466 (10/07/83)	Rule 466(f)	Rule 466(e)	
	🔲 Rule 466.1 (03/16/84)	Rule 466.1(g)	Rule 466.1(h).	
	Rule 467 (03/05/82)	Rule 467(f)	Rule 467(e)	
-		See Applicable Subpart	See Applicable Subpart	
		See Applicable Subpart	See Applicable Subpart	
		See Applicable Subpart	See Applicable Subpart	•
	SUBPART	See Applicable Subpart	See Applicable Subpart	
	1 40 CFR65 SUBPAKT H	See Applicable Subpart	See Applicable Subpart	
		See Applicable Subpart See Applicable Subpart	See Applicable Subpart	
	40 CFR63 SUBPART CC	See Applicable Subpart	See Applicable Subpart	
☐ Fugitive Emissions, Natural Gas Processing	Rule 466 (10/07/83)	□ Rule 466(f)	Rule 466(e)	r
Plant	Rule 466.1 (03/16/84)	Rule 466.1(g)	Rule 466.1(h)	•
	Rule 467 (03/05/82)	\mathbb{R}^{1} Rule $467(f)$	Rule 467(e)	
		Rule [173(j)	Rule 1173(i)	
	40 CFR60 SUBPART KKK	See Applicable Subpart	See Applicable Subpart	
	TO CER63 SUBPART F	See Applicable Subpart See Applicable Subpart	See Applicable Subpart	
	40 CFR63 SUBPART G	See Applicable Subpart	See Applicable Subpart	
	🔲 40 CFR63 SUBPART H	See Applicable Subpart	See Applicable Subpart	
	SUBPART	See Applicable Subpart	See Applicable Subpart	
	[] 40 CFR63 SUBPART R [_] 40 CFR63 SUBPART CC	See Applicable Subpart	See Applicable Subpart See Applicable Subpart	
Tugitive Emissions, Oil & Gas Production		Rule 466(f)	Rule 466(e)	-
Facility	🔲 Rule 466.1 (03/16/84)	Rule 466.1(g)	Rule 466.1(h)	
	Rule 467 (03/05/82)	Rule 467(f)	Rule 467(e)	
	Rule 1173 (12/06/02)	Rule 1173(j)	Rule 1173(i)	
•	1 40 CFR01 SUBFAKT V	See Applicable Subpart	See Applicable Subpart	
	40 CFR63 SUBPART G	See Applicable Subpart See Applicable Subpart	See Applicable Subpart	
		See Applicable Subpart	See Applicable Subpart	
	40 CFR63 SUBPART I	See Applicable Subpart	See Applicable Subpart	
KEY Reg = AQMD Regulation ABBREVIATIONS: Rule = AOMD Rule	App. = Appendix	CFR = Code of Federal Regulations	AQMD Form Rev. 05/05	-
	יייי בייייי ביייייי בייייייייייייייייי	ככון - כמון סווים כסתכ סו אכפתומנוסווים		

Section II - Applicable Requirements, Test Met	.s., Test Methods, & MRR Requirements	ements	
EQUIPMENT/PROCESS	APPLICABLE REQUIREMENT	теѕт метнор	MRR REQUIREMENT
	☐ 40 CFR63 SUBPART R☐ 40 CFR63 SUBPART CC	See Applicable Subpart See Applicable Subpart	See Applicable Subpart See Applicable Subpart
☐ Fugitive Emissions, Pipeline Transfer Station	Rule 466 (□ Rule 466(f)	Rule 466(e)
	Kule 460.1 (03/16/84) Rule 467 (03/05/82)	Kule 466.1(g) Rule 467(f)	U Kuie 460.1(n) □ Rule 467(e)
	(12/06/02)	Rule 1173(j)	Rule 1173(i)
4	40 CFR61 SUBPART V .	See Applicable Subpart	See Applicable Subpart
•		See Applicable Subpart	See Applicable Subpart
		See Applicable Subpart	See Applicable Subpart
		See Applicable Subpart	See Applicable Subpart
		See Applicable Subpart	See Applicable Subpart
		See Applicable Subpart	See Applicable Subpart
Furnace, Basic Oxygen Process	- 1	See Applicable Subpart	See Applicable Subpart
Furnace, Electric Arc, For Steel Plants Constructed After August 17, 1983	U 40 CFR60 SUBPART AAa	See Applicable Subpart	See Applicable Subpart
Turnace, Electric Arc, For Steel Plants:	U 40 CFR60 SUBPART AA	See Applicable Subpart	See Applicable Subpart
Constructed After Oct. 21, 1974, & On Or Before Aug. 17, 1983			
Furnace, Glass Melting	Rule 1117 (01/06/84) 40 CFR60 STIRPART CC	Rule 1117(c), AQMD TM 7.1 or	See Annlicable Submart
		See Applicable Subpart	see Applicatic Suspain
Furnace, Lead Melting, Automotive Batteries	Rule 1101 (10/07/77)	See Applicable Subpart	See Applicable Subpart
Gasoline Transfer & Dispensing Operation	_	Rule 461(f)	\square Rule 461(e)(6) & (e)(7) :
Glass Manufacturing	See Manufacturing, Glass		
Grain Elevators	40 CFR60 SUBPART DD	See Applicable Subpart	See Applicable Subpart
Halon-containing Equipment, Use for Technician Training, Testing, Maintenance, Service. Repair or Disposal	☐ 40 CFR82 SUBPART H	See Applicable Subpart	See Applicable Subpart
Heater, Asphalt Pavement	☐ Rule 1120 (08/04/78)	AQMD Visible Emissions, AQMD TM 6.2	☐ Rule 1120(f)
Heaters, Petroleum Refinery Process	Rule 429 (12/21/90)	N/A	Rule 429(d)
	_	Rule 431.1(f)	🔲 Rule 431.1(d) & (e)
		L Rule 1146(d)	L Rule 1146(c)(6) & (c)(7)
	. 40 CFR60 SUBPART J [~] 40 CFR63 SUBPART DDDDD	See Applicable Subpart	See Applicable Subpart
Heaters, Process			
☐ Incinerators	40 CFR60 SUBPART E	See Applicable Subpart	See Applicable Subpart
Inorganic Arsènic Emissions, Arsenic Trioxide	☐ 40 CFR61 SUBPART P	See Applicable Subpart	See Applicable Subpart
& Metallic Arsenic Production Facilities			
KFV Reg = AOMD Regulation	vibraard = ark m	CED - Code of Endoral Demilations	AOMD Form Box 05/05
REVIATIONS:		Cr = Code of regel at regulations CCR = California Code of Regulations	

Section II - Applicable Requirements. Test Meth	., Test Methods, & MRR Requirements	ments	
EQUIPMENT/PROCESS	APPLICABLE REQUIREMENT	теѕт метнор	MRR REQUIREMENT
Internal Combustion Engines, Reciprocating	∵	See Applicable Subpart	See Applicable Subpart
. Kiln, Cement Plant		N/A	N/A
	Rule 1112.1 (02/07/86) 40 CFR60 SUBPART F	N/A See Applicable Subpart	N/A See Applicable Subpart
Landfills			
	🔲 Rule 1150:1 (03/17/00)	☐ Rule 1150.1(j)	□ Rule 1150.1(e) & (f)
	40 CFR60 SUBPART WWW	See Applicable Subpart	See Applicable Subpart See Applicable Subpart
Lead Acid Battery Manufacturing Plants		mdano acomo del cono	
Lead Electroplating Operation	Rule 1426 (05/02/03)		Rule 1426(e)
Manufacturing, Asphalt Processing &	Rule 470 (05/07/76)	N/A	See Applicable Subpart
Asphalt	Rule 1108 (02/01/85).	Rule 1108(b).	See Applicable Subpart
1 Sillon		See Applicable Subpart	
	40 CFR63 SUBPART LLLLL	See Applicable Subpart	
Manufacturing, Brick & Structural Clay Products	☐ 40 CFR63 SUBPART JJJJJ	See Applicable Subpart	See Applicable Subpart
Manufacturing, Clay Ceramics	U 40 CFR63 SUBPART KKKKK	See Applicable Subpart	See Applicable Subpart
Manufacturing, Coatings & Ink	Rule 1141.1 (11/17/00)	N/A Sold Sold Sold Sold Sold Sold Sold Sold	Rule 1141 1(c)
(St. Cott. 2031)		See Applicable Subpair	See Applicable Subpair
Manufacturing, Food Product	Rule 1131 (06/06/03)	Rule 1131(e)	Rule 1131(d)
Manufacturing, Friction Materials	☐ 40 CFR63 SUBPART QQQQQ	See Applicable Subpart	See Applicable Subpart
Manufacturing, Glass	Rule 1117 (01/06/84) 40 CFR60 SUBPART CC	Rule 1117(c), AQMD TM 7.1 or 100.1	See Applicable Subpart
•	☐ 40 CFR61 SUBPART N	See Applicable Subpart See Applicable Subpart	See Applicable Subpart
Manufacturing, Hydrochloric Acid	40 CFR63 SUBPART NNNN	See Applicable Subpart	See Applicable Subpart
Manufacturing, Lead-Acid Battery	☐ 40 CFR60 SUBPART KK	See Applicable Subpart	See Applicable Subpart
Manufacturing, Lime	40 CFR63 SUBPART AAAAA	See Applicable Subpart	See Applicable Subpart
Manufacturing, Magnetic Tape Industry	☐ 40 CFR60 SUBPART SSS	See Applicable Subpart	See Applicable Subpart
Manufacturing, Miscellaneous Organic	1 0 1	See Applicable Subpart	See Applicable Subpart
Manufacturing, Nitric Acid	Rule 218 (05/14/99) Rule 1159 (12/06/85)	AQMD TM 100.1	□ Rule 218(e) & (f)
		See Applicable Subpart	See Applicable Subpart
☐ Manufacturing, Plywood & Composite Wood . Products	Rule 1137 (02/01/02) 40 CFR63 SUBPART DDDD	N/A See Applicable Subpart	Rule 1137(e) See Applicable Subpart
Manufacturing, Polymer Industry		See Applicable Subpart	See Applicable Subpart
	40 CFR63 SUBPART W	See Applicable Subpart See Applicable Subpart	See Applicable Subpart See Applicable Subpart
KEY Reg.= AQMD Regulation	App. = Appendix	CFR = Code of Federal Regulations	·
		CCK = California Code of Regulations	Suu-cı Page 10 of 10

ξ ···

Section II - Applicable Requirements, Test Methods, & MRR Requirements	rements	Test Methods, & MRR Requir	ements		, 4
EQUIPMENT/PROCESS		APPLICABLE REQUIREMENT	TEST METHOD	MRR REQUIREMENT	
☐ Manufacturing, Polymeric Cellular Foam	oam	☐ Rule 1175 (05/13/94) ☐ 40 CFR63 SUBPART UUUU	Rule 1175(f) See Applicable Subpart	Rule 1175(e) See Applicable Subpart	
☐ Manufacturing, Products Containing Halon Blends	Halon	U 40 CFR82 SUBPART H	See Applicable Subpart	See Applicable Subpart	
☐ Manufacturing, Products Containing Organic Solvents	Organic	Rule 443.1 (12/05/86)	N/A	N/A	
Manufacturing, Products Containing Ozone Depleting Substances (ODS)	Ozone	40 CFR82 SUBPART A 10 CFR87 STIBPART F	See Applicable Subpart See Applicable Subpart	See Applicable Subpart See Applicable Subpart	
Manufacturing, Reinforced Plastic			See Applicable Subpart	See Applicable Subpart	
Manufacturing, Refractory Products		1 40 CFR63 SUBPART SSSSS	See Applicable Subpart	See Applicable Subpart	
Manufacturing, Resin		☐ Rule 1141 (11/17/00) ☐ 40 CFR63 SUBPART W	Rule 1141(d) See Applicable Subpart	Rule 1141(c) See Applicable Subpart	
Manufacturing, Rubber Tire		40 CFR63 SUBPART XXXX	See Applicable Subpart	See Applicable Subpart	
Manufacturing, Semiconductors	,	Rule 109 (05/02/03)	Rule 109(g)	Rule 109(c)	
		\square Rule 1164 (01/13/95) \square Rule 1171 (11/07/03)	Kule 1164(e) Rule 1171(f)	Kule 1104(c)(5) Rule 1171(c)(6)	
		☐ 40 CFR63 SUBPART BBBBB	See Applicable Subpart	See Applicable Subpart	,
Manufacturing, Solvent		Rule 443 (05/07/76)	N/A	N/A	,
Manufacturing, Suffuric Acid		Rule 469 (02/13/81)	AQMD TM 6.1 or 6.2	Sae Annlicable Subnart	
		40 CFR60 SUBPART Cd	See Applicable Subpart	See Applicable Subpart	\$ *
Manufacturing, Surfactant		Rule 1141.2 (01/11/02)	☐ AQMD TM 25.1		· .
Manufacturing, Synthetic Organic Chemical Manufacturing Industry (SOCMI) Air	hemical ir	☐ 40 CFR60 SUBPART III ☐ 40 CFR60 SUBPART NNN	See Applicable Subpart See Applicable Subpart	See Applicable Subpart See Applicable Subpart	
Manufacturing Industry (SOCMI) Reactor	hemical eactor	40 CFR60 SUBPART RRR	See Applicable Subpart	See Applicable Subpart	τ
Processes Manufacturing Vinyl Chloride		140 CER61 STIBPART F	See Applicable Subpart	See Amilicable Subpart	ŧ,
Manufacturing. Water Heaters			N/A	N/A	
Manufacturing, Wool Fiberglass Insulation	ulation	40 CFR60 SUBPART PPP	See Applicable Subpart	See Applicable Subpart	
Manure Processing Operations		☐ Rule 1127	Rule 1127(h)	Rule 1127(g)	
☐ Marine Tank Vessel Operations		☐ Rule 1142 (07/19/91) ☐ 40 CFR63 SUBPART Y	Rule 1142(e) See Applicable Subpart	Rule 1142(h) See Applicable Subpart	
Mercury Emissions		40 CFR61 SUBPART E	See Applicable Subpart	See Applicable Subpart	
☐ Motor Vehicle Air Conditioners with Ozone	1 Ozone	40 CFR82 SUBPART B	See Applicable Subpart	See Applicable Subpart	•
Depleting Substances (ODS): Repair, Service, Manufacturing, Maintenance, or Disposal	ir,	🔲 40 CFR82 SUBPART F	See Applicable Subpart	See Applicable Subpart	
Municipal Waste Combustors		40 CFR60 SUBPART Cb	See Applicable Subpart	See Applicable Subpart	
KEY Reg. = AQMD Regulation ABBREVIATIONS: Rule = AQMD Rule	Rule	App. = Appendix AQMD TM = AQMD Test Method	CFR = Code of Federal Regulations CCR = California Code of Regulations	AQMD Form Rev. 05/05 500-C1 Page 11 of 11	
	•			N ₁	

	1 40 CFR60 SUBPART Ea	See Applicable Subpart	See Applicable Subpart
	1 40 CFR60 SUBPART ED	See Applicable Subpart	See Applicable Subpart
Negative Air Machines/HEPA, Asbestos	X 40 CFR61 SUBPART M	See Applicable Subpart	See Applicable Subpart
Nickel Electroplating Operation	☐ Rule 1426 (05/02/03)		Rule 1426(e)
Nonmetallic Mineral Processing Plants	Rule 404 (02/07/86)	AQMD TM 5.1, 5.2, or 5.3	
*	Rule 405 (02/07/86)	AQMD TM 5.1, 5.2, or 5.3	
		See Applicable Subpart	See Applicable Subpart
Off-site Waste and Recovery Operation	40 CFR63 SUBPART DD	See Applicable Subpart	See Applicable Subpart
Oil and Gas Well Operation	Rule 1148 (11/05/82) Rule 1148.1 (03/05/04)	AQMD TM 25.1 Rule 1148.1 (g)	Rule 1148 1 (f)
Onshore Natural Gas Processing, SO ₂	40 CFR60 SUBPART LLL	See Applicable Subpart	See Applicable Subpart
Emissions			
Open Fires	Rule 444 (12/21/01)		
Open Storage, Petroleum Coke	Rule 403 (04/02/04)	Rule 403(d)(4)	Rule 403(f)
	Rule 1158 (06/11/99)	Rule 1158(h)	Rule 1158(j)
Open Storage	Rule 403 (04/02/04) Rule 403.1 (04/02/04)	☐ Rule 403(d)(4)	Rule 403(f)
Outer Continental Shelf Platform	Rule 1183 (03/12/93)	1 40 CFR55	40 CFR55
	☐ 40 CFR55	See Applicable Subpart	See Applicable Subpart
Oven, Commercial Bakery	☐ Rule 1153 (01/13/95)	Rule 1153(h)	Rule 1153(g)
Oven, Petroleum Coke	Rule 477 (04/03/81).	AQMD Visible Emissions, AQMD	
		TM 5.1, 5.2, or 5.3	
	40 CFR63 SUBPART L	See Applicable Subpart	See Applicable Subpart
Ozone Depleting Substances (ODS) or Alternative ODS, Use	U 40 CFR82 Subpart G	See Applicable Subpart	See Applicable Subpart
Petroleum Refineries	☐ Rule 218 (05/14/99)	☐ AQMD TM 100.1	
· .	Rule 468 (10/08/76)	AQMD TM 6.1 or 6.2	
	Rule 469 (02/13/81)	AQMD TM 6.1 or 6.2	·
	Rule 1123 (12/07/90)	N/A	Rule 1123(c)
	Kule 1189 (01/21/00)		
-	140 CFK60 SUBPAKI J	See Applicable Subpart	See Applicable Subpart
	1 40 CFK63 SUBPART F	See Applicable Subpart	See Applicable Subpart
		See Applicable Subpart	See Applicable Subpart
	40 CFK63 SUBPAKT H	See Applicable Subpart	See Applicable Subpart
•	40 CFK63 SUBPAKT I	See Applicable Subpart	See Applicable Subpart
	1 40 CFR63 SUBPARI CC	See Applicable Subpart	See Applicable Subpart
	SUBLARI	See Applicable Subpart	See Applicable Subnart
-		The Application Suchair	See Applicable Suppare
X Petroleum Refineries, Fugitive Emissions	Rule 1173 (12/06/02)	Rule 1173(j)	Rule 1173(i)
KEY Reg. = AQMD Regulation	App. = Appendix	CFR = Code of Federal Regulations	AQMD Form Rev. 05/05
ABBREVIATIONS: Rule = AOMD Rule	AOME	CCR = California Code of Regulations	Pa

Section II - Applicable Requirements; Test Methods; & MRR Requirements	, Test Methods, Œ MRR Requirer	nents	
EQUIPMENT/PROCESS	APPLICABLE REQUIREMENT	теѕт метнор	MRR REQUIREMENT
	V D.12 466 (10/07/82)	N p.,1e 466(f)	N D. 12 166(a)
		. Name 400(1)	Nuite 466 1(h)
			Rule 467(e)
		See Applicable Subpart	See Applicable Subpart
		See Applicable Subpart	See Applicable Subpart
	~	See Applicable Subpart	See Applicable Subpart
		See Applicable Subpart .	See Applicable Subpart
•	~	See Applicable Subpart	See Applicable Subpart
	~	See Applicable Subpart	See Applicable Subpart
		See Applicable Subpart	See Applicable Subpart
	40 CFR63 SUBPART CC	See Applicable Subpart	See Applicable Subpart
Petroleum Refineries, Storage Tanks	Rule 463 (05/06/05)	Rule 463(g)	
	\sim		Rule 1178(f) & (h)
	$\overline{}$	See Applicable Subpart	See Applicable Subpart
-	_	See Applicable Subpart	See Applicable Subpart
	_	See Applicable Subpart	See Applicable Subpart
		See Applicable Subpart	See Applicable Subpart
		See Applicable Subpart	See Applicable Subpart
•		See Applicable Subpart	See Applicable Subpart
		See Applicable Subpart	See Applicable Subpart
,		See Applicable Subpart	See Applicable Subpart
		See Applicáble Subpart	See Applicable Subpart
	40 CFR63 SUBPART EEEE	See Applicable Subpart	See Applicable Subpart
Petroleum Refineries, Wastewater Systems	☐ Rule 1176 (09/13/96)	Rule 1176(h)	Rule 1176(f) & (g)
-	\sim	N/A .	
	_	See Applicable Subpart	See Applicable Subpart
	🗌 40 CFR63 SUBPART CC	See Applicable Subpart	See Applicable Subpart
Pharmaceuticals & Cosmetics Manufacturing	☐ Rule 1103 (03/12/99)	Rule 1103(f)	Rule 1103(e)
Polyester Resin Operation	. Rule 109 (05/02/03)	Rule 109(g)	Rule 109(c)
	Rule 1162 (07/09/04)	Rule 1162(f)	Rule 1162(e)
	Rule 1171 (11/07/03)	\square Rule 1171($\widehat{\mathfrak{h}}$	Rule 1171(c)(6)
Primary Magnesium Réfining	40 CFR63 SUBPART TTTT	See Applicable Subpart	See Applicable Subpart
☐ Printing Press	See Coating Operations		
☐ Publicly Owned Treatment Works	Rule 1179 (03/06/92)	☐ Rule 1179(e)	\square Rule 1179(c) & (d)
Operations	☐ 40 CFR60 SUBPART O	See Applicable Subpart	See Applicable Subpart
□ Pumps	See Fugitive Emissions or Petroleum Refineries, Fugitive Emissions	eries, Fugitive Emissions	
Recycling & Recovery Equipment for Ozone	40 CFR82 SUBPART F	See Applicable Subpart	See Applicable Subpart
Depleting Substances (ODS),	- 1		
Refrigerant Reclaimers for Ozone Depleting Substances (ODS)	☐ 40 CFR82 SUBPART F	See Applicable Subpart	See Applicable Subpart
Rendering Plant	Rule 472 (05/07/76)	A/N	Rule 472(b)
Rock Crushing	See Nonmetallic Mineral Processing Plants		
KEY Reg.= AQMD Regulation	App. = Appendix	CFR = Code of Federal Regulations	AQMD Form Rev. 05/05
ABBREVIATIONS: Rute = AQMD Rute	AQMD TM = AQMD Test Method	CCR = California Code of Regulations	Pa

section III - Applicable Kequirements, il est Methods, tra	lest methods, the MKK Requirements	ements	
EQUIPMENT/PROCESS	APPLICABLE REQUIREMENT	TEST METHOD	MRR REQUIREMENT
Semiconductor Manufacturing	See Manufacturing, Semiconductors		
Sewage Treatment Plants	See Publicly Owned Treatment Works Operation	peration	
Site Remediation	1 40 CFR63 SUBPART GGGGG	See Applicable Subpart	See Applicable Subpart
Smelting, Primary Copper	☐ 40 CFR63 SUBPART QQQ	See Applicable Subpart	See Applicable Subpart
Smelting, Secondary Lead	40 CFR60 SUBPART L	See Applicable Subpart	See Applicable Subpart
	40 CFR63 SUBPART X	See Applicable Subpart	See Applicable Subpart
Soil Decontamination	 Rule 1:166 (05/11/01) 40 CFR63 SUBPART GGGGG	Language Rule 1166(e) See Applicable Subpart	\square Rule 1166(¢)(1)(C) See Applicable Subpart
Spray Booth	See Coating Operations	A STATE OF THE STA	
Sterilizer, Ethylene Oxide	40 CFR63 SUBPART O	See Applicable Subpart	See Applicable Subpart
Storage Tank, Degassing Operation	☐ Rule 1149 (07/14/95) ☐ 40 CFR63 SUBPART CC	See Applicable Subpart	See Applicable Subpart
X Storage Tank, Greater Than 19,815 Gallon	X Rule 463 (05/06/05)	□ Rule 463(g)	Rule 463(e)(5)
, Capacity	☐ 40 CFR63 SUBPART F	See Applicable Subpart	See Applicable Subpart
		See Applicable Subpart	See Applicable Subpart
	40 CFR63 SUBPART H	See Applicable Subpart	See Applicable Subpart
		See Applicable Subpart	See Applicable Subpart
	40 CFR60 SUBPART K	See Applicable Subpart	See Applicable Subpart
	1 40 CFR60 SUBPARI Ka	See Applicable Subpart	See Applicable Subpart
	1 40 CFR63 SUBPART R	See Applicable Subpair See Applicable Subpair	See Applicable Subpair See Applicable Subpart
	1 40 CFR63 SUBPART CC	See Applicable Subpart	See Applicable Subpart
Synthetic Fiber Production Facilities		See Applicable Subpart	See Applicable Subpart
Taconite Iron Ore Processing Facilities	40 CFR63 SUBPART RRRRR	See Applicable Subpart	See Applicable Subpart
X Turbine, Stationary Gas-Fired	Rule 1134 (08/08/97)	CEMS Rule 1134(e) & (g)	Rule 1134(d) & (f)
	1	X AQMD TM 5.1, 5.2, or 5.3	
		See Applicable Subpart	See Applicable Subpart
; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ;		See Applicable Subpart	See Applicable Subpart
Turbine, Stationary Oil-Fired	40 CFR63 SUBPART YYYY	See Applicable Subpart	See Applicable Subpart
Valves	_	Petroleum Refineries, Fugitive Emissions	
Vessel, Refinery Process		N/A	Rule 1123(c)
Vessels	See Petroleum Refineries, Fugitive Emissions	lons	
Wastewater, Chemical Plant	Rule 464 (12/07/90)	žΓ	
	1 Nuie II / 9 (99/15/59)	Con Amelianh Submen	$\sum_{S \in \mathcal{S}} A \operatorname{curl}_{S \cap S} (1/O(1) \propto (g)$
		See Applicable Subpart	See Applicable Subpart
		See Applicable Subpart	See Applicable Subpart
		See Applicable Subpart	See Applicable Subpart
	🔲 40 CFR63 SUBPART CC	See Applicable Subpart	See Applicable Subpart
X Wastewater Treatment, Other	X Rule 464 (12/07/90)	N/A Rule 1176(h)	Rule 1176(f) & (e)
Woodworking Operations	Rule 1137 (02/01/02)	N/A	Rule 1137(e)
	App. = Appendix	CFR = Code of Federal Regulations	
ABBREVIATIONS: Rule = AQMD Rule	AQMD TM = AQMD Test Method	CCR = California Code of Regulations	500-C1 Page 14 of 14

Section III – Supplemental Identification of Specific Requirements

Complete this section <u>only</u> if there is a specific requirement (i.e., rule reference, test method, or MRR requirement) that is:

1. Listed for a specific type of equipment or process in Section II of this form & **DOES NOT** pertain to a specific

- 1. Listed for a specific type of equipment or process in Section II of this form & **DOES NOT** pertain to a specific device at your facility*; OR,
- 2. Is **NOT** Listed for a specific type of equipment or process in Section II of this form but it **IS** applicable to a specific device at your facility.

NOTES:

- 1. For any specific requirement, test method, or MRR requirement that is identified as "Remove," attach additional sheets to explain the reasons why the specific requirement does not pertain to the device listed.
- 2. All boxes that are checked in Section II and any additional requirements identified in this section as "Add" will be used to determine the facility's compliance status. This information will be used to verify the certification statements made on Form 500-A2.
- 3. Do not use this section to identify equipment that is exempt from specific rule requirements. Your equipment is automatically considered to be in compliance with the rule that specifically exempts the equipment from those requirements.
- 4. Listing any requirement that does not apply to a specific piece of equipment in this section will not provide the facility with a permit shield unless one is specifically requested by completing Form 500-D and approved by the AOMD.
- * If this section is completed as part of the initial Title V application & there is no device number assigned, refer to the existing permit or application number in this column.

Device No.*	Specific Requirement (Rule Number & Date)	Add (A) or Remove (R) (Check one)	Test Method	Add (A) or Remove (R) (Check one)	MRR Requirement	Add (A) or Remove (R) (Check one)
		□A □R		□A □R		A R
•		□A □R		□A □R		A R
	1	□A□R		□A □R		□ A □ R
* .		□A □R		□A □R		□ A □ R
•	-	□A □R		□A □R		□ A □ R
*	·	□A □R		□A □R		□ A □ R
		$\square A \square R$		□A □R		□ A □ R
		□A □R	-	□A □R		□A□R
		□A □R		□A □R		□ A □ R
•		□A □R		□A □R		□ A □ R
		□A □R		□A □R	-	□ A □ R
		□A □R		□A □R		☐ A ☐ R
	•	$\square A \square R$	†	□A □R	_	· A · R
		$\square A \square R$		□A □R		□ A □ R
		□A □R		□A □R		$\square A \square R$
	-	□A □R		.□A □R		□ A □ R
	:	□A □R		□A □R		. □ A □ R
	,	□A □R		□A □R		□ A □ R
		□A □R		□A □R		□ A □ R
		□A □R		□A □R		□ A □ R
	- 3	□A □R	e w	□A □R	•	□A□R

roved Rules T	hat Are Not	The Most Current AC	MD Rules	
				n new-items.
Adoption/ Amendment Date	Check (✓)	SIP-Approved Rule	Adoption/ Amendment Date	Check (✓) if Applies
08/07/81		1146.2	01/09/98	
03/02/84	X	1162	11/17/00	
12/11/98		1166	07/14/95	1 .
01/15/93	T	1168	10/03/03	×
05/04/90		1171	11/07/03	X
03/11/94		1173	05/13/94	
05/02/80		1186	09/10/99	
05/07/76		2000	05/11/01	
10/08/76		2001		
01/06/84		2002		
	X	2005	04/20/01	
12/10/99		2007	12/05/03	
		 	· · · · · · · · · · · · · · · · · · ·	
			 	
		 		
			•	
		<u> </u>		Tanaarinin na marangan na m
		19911999394-6220022939537723349434229996		
		proved (Continued on		<u> </u>
le as it applies to th		proved (Continued on the blanks at the end of this	form to fill-in new i	<u> </u>
le as it applies to the Adoption/	ne facility. Use	the blanks at the end of this	form to fill-in new i	tems.
le as it applies to the Adoption/ Amendment	check (✓)	the blanks at the end of this Non SIP-Approved	form to fill-in new i Adoption/ Amendment	tems. Check (✓)
le as it applies to the Adoption/ Amendment Date	ne facility. Use	Non SIP-Approved Rule	form to fill-in new i Adoption/ Amendment Date	tems. Check (✓)
le as it applies to the Adoption/ Amendment Date N/A	check (✓)	Non SIP-Approved Rule	form to fill-in new i Adoption/ Amendment Date 05/06/88	tems.
le as it applies to the Adoption/ Amendment Date N/A N/A	check (✓)	Non SIP-Approved Rule 1170 1183	Adoption/ Amendment Date 05/06/88 03/12/93	tems. Check (✓)
le as it applies to the Adoption/ Amendment Date N/A N/A N/A	check (✓)	Non SIP-Approved Rule 1170 1183 1186.1	Adoption/ Amendment Date 05/06/88 03/12/93 06/04/04	tems. Check (✓)
le as it applies to the Adoption/ Amendment Date N/A ' N/A N/A N/A N/A	check (✓)	Non SIP-Approved Rule 1170 1183 1186.1 1191	Adoption/ Amendment Date 05/06/88 03/12/93 06/04/04 06/16/00	tems. Check (✓)
le as it applies to the Adoption/ Amendment Date N/A N/A N/A N/A N/A N/A N/A	check (✓)	the blanks at the end of this Non SIP-Approved Rule 1170 1183 1186.1 1191 1192	Adoption/ Amendment Date 05/06/88 03/12/93 06/04/04 06/16/00 06/16/00	tems. Check (✓)
le as it applies to the Adoption/ Amendment Date N/A N/A N/A N/A N/A N/A N/A N/A N/A 05/14/99	Check (<) if Applies	Non SIP-Approved Rule 1170 1183 1186.1 1191 1192 1193	form to fill-in new i Adoption/ Amendment Date 05/06/88 03/12/93 06/04/04 06/16/00 06/16/00 06/06/03	tems. Check (✓)
le as it applies to the Adoption/Amendment Date N/A N/A N/A N/A N/A N/A N/A 05/14/99 05/07/76	check (✓)	the blanks at the end of this Non SIP-Approved Rule 1170 1183 1186.1 1191 1192 1193 1194	form to fill-in new i Adoption/ Amendment Date 05/06/88 03/12/93 06/04/04 06/16/00 06/16/00 06/06/03 10/20/00	tems. Check (✓)
le as it applies to the Adoption/ Amendment Date N/A N/A N/A N/A N/A N/A 05/14/99 05/07/76 12/21/90	Check (<) if Applies	the blanks at the end of this Non SIP-Approved Rule 1170 1183 1186.1 1191 1192 1193 1194 1195	form to fill-in new i Adoption/ Amendment Date 05/06/88 03/12/93 06/04/04 06/16/00 06/16/00 06/06/03 10/20/00 04/20/01	tems. Check (✓)
le as it applies to the Adoption/ Amendment Date N/A N/A N/A N/A N/A N/A 05/14/99 05/07/76 12/21/90 07/12/96	Check (<) if Applies	the blanks at the end of this Non SIP-Approved Rule 1170 1183 1186.1 1191 1192 1193 1194 1195 1196	form to fill-in new i Adoption/ Amendment Date 05/06/88 03/12/93 06/04/04 06/16/00 06/16/00 06/06/03 10/20/00 04/20/01 06/04/04	Check (✓ if Applies
le as it applies to the Adoption/ Amendment Date N/A N/A N/A N/A N/A N/A 05/14/99 05/07/76 12/21/90	Check (<) if Applies	the blanks at the end of this Non SIP-Approved Rule 1170 1183 1186.1 1191 1192 1193 1194 1195	form to fill-in new i Adoption/ Amendment Date 05/06/88 03/12/93 06/04/04 06/16/00 06/16/00 06/06/03 10/20/00 04/20/01	tems. Check (✓)
	ved Rule as it applications Adoption/ Amendment Date 08/07/81 03/02/84 12/11/98 01/15/93 05/04/90 03/11/94 05/02/80 05/07/76 10/08/76 01/06/84 11/08/96 12/10/99 07/11/97 03/05/04 02/01/80 02/14/97	Adoption/Amendment Date Check (✓) if Applies 08/07/81 □ 03/02/84 ☒ 12/11/98 □ 01/15/93 □ 05/04/90 □ 03/11/94 □ 05/02/80 □ 05/07/76 □ 10/08/76 ☒ 01/06/84 □ 11/08/96 ☒ 12/10/99 □ 07/11/97 ☒ 02/01/80 ☒ 02/14/97 □ □ □ □ □ □ □	Adoption/Amendment Date Check (✓) if Applies SIP-Approved Rule 08/07/81 □ 1146.2 03/02/84 ☒ 1162 12/11/98 □ 1166 01/15/93 □ 1171 03/01/94 □ 1173 05/02/80 □ 1186 05/07/76 □ 2000 10/08/76 ☒ 2001 01/06/84 □ 2005 12/10/99 □ 2007 07/11/97 ☒ 2010 03/05/04 □ 2011 02/01/80 ☒ 2012 02/14/97 □ □ □ □ □ □ □ □ □ □ □	Amendment Date Check (✓) if Applies SIP-Approved Rule Amendment Date 08/07/81 □ 1146.2 01/09/98 03/02/84 ☒ 1162 11/17/00 12/11/98 □ 1166 07/14/95 01/15/93 □ 1168 10/03/03 05/04/90 □ 1171 11/07/03 03/11/94 □ 1173 05/13/94 05/02/80 □ 1186 09/10/99 05/07/76 □ 2000 05/11/01 10/08/76 ☒ 2001 05/11/01 01/06/84 □ 2002 05/11/01 11/08/96 ☒ 2005 04/20/01 12/10/99 □ 2007 12/05/03 07/11/97 ☒ 2010 05/11/01 03/05/04 □ 2011 12/05/03 02/01/80 ☒ 2012 12/05/03 02/14/97 □ □ □ □ □ □ □

1404

1405

1406

1407

1411

1414

1415

1418

1420

1421

1425

1426

04/08/94

04/06/90

01/04/91

07/08/94

07/08/94

03/01/91

05/03/91

10/14/94

09/10/99

09/11/92

12/06/02

03/16/01

05/02/03

04/03/81

10/07/77

11/07/03

08/05/88

10/04/85

11/14/97

10/20/78

02/13/98

08/06/04

03/05/04

10/15/82

01/07/05

06/07/85

477

480

1105.1

1110.1

1110.2

1116.1

1118 1127

1148.1

1150

1157

1163

1109

Section V - AQMD	Rules That Are I	Not SIP-Ap	proved (Contin	ued on F	ollowing Page	
1469	05/02/03		2009.1		05/11/01	
1469.1	. 03/04/05		2020	. 1	05/11/01	
1470	03/04/05		2501		05/09/97	
2009	01/07/05	×	2506		12/10/99	
1						
, .						
						,
* .						
;						

Title V Form 500-H

TH COAST AIR QUALITY MAN EMENT DISTRICT

Applicability Determination for Initial, Renewal, & Significant Permit Revision Title V Applications Compliance Assurance Monitoring (CAM)

This form is required as part of an initial, significant permit revision, or renewal Title V application. If your Title V facility has control devices in use, the CAM rule may apply. Follow the instructions on the reverse side of this form to determine whether your facility is subject to CAM requirements.

Section I = CA	Section I — CAM Status Summary for Emission Units	ssion Units:					
1. Facility Name:	HAYNES GENERATING STATION	IG STATION			Fa	Facility ID (6-Digit): 800074	800074
2. Based on the cri	2. Based on the criteria in the instructions (check one and attach additional pages as necessary):	and attach additio	nal pages as neces	sary):			
a. The emissio	The emission units identified below are subject to the CAM rule and a CAM plan ² is attached for each affected emissions unit:	to the CAM rule ¹ emissions unit:		There are no emission un subject to the CAM rule.	b. X There are no emission units with control devices at this Title V facility that are subject to the CAM rule.	at this Title V facil	ity that are
Emission Unit ³	Equipment	Uncontrolle	led Emissions	Connected to Control Unit	Equipment 4	Controlled Emissions	Emissions
Application, Permit or Device No.	Description ⁴	Pollutant	PTE ⁵ (tons/year)	Application, Permit or Device No.	Description	Pollutant	PTE5 (tons/year)
	-						
					9		
				à			
	,						
		·					
			·				
		-					
				•			
		. •					

Por more detailed information regarding the CAM rule applicability, refer to Title 40, Chapter I, Part 64, Section 64.1 of the Code of Federal Regulations (40 CFR Part 64, Section 64.1). This also can be accessed via the internet at: http://www.access.gpo.gov/nara/cfr/waisidx_99/40cfr64_99.html.

² Only one CAM plan is required for a control device that is common to more than one emissions unit, or if an emissions unit is controlled by more than one control device similar in design and operation. If the control devices are not similar in design and operation, one plan is required for each control device.

³ List all new and existing emission units and the connected control devices either by AQMD application, permit or device number. When the emission unit is new and has not yet been assigned an application number, leave this column blank.

⁴ Provide a brief equipment description of the emission units and control devices by indicating equipment type, make, and model and serial numbers as appropriate.

⁵ Potential to Emit



South Coast Air Quality Management District 21865 East Copley Drive Diamond Bar, CA 91765 (909) 396- 2000

CALIFORNIA ENVIRONMENTAL QUALITY ACT (CEQA) APPLICABILITY FORM 400 - CEQA

The SCAQMD is required by state law, the California Environmental Quality Act (CEQA), to review discretionary permit project applications for potential air quality and other environmental impacts. This form is a screening tool to assist the SCAQMD in clarifying whether or not the project¹ has the potential to generate significant adverse environmental impacts that might require preparation of a CEQA document [CEQA Guidelines §15060(a)].² Refer to the attached instructions for guidance in completing this form.³ For each Form 400-A application, also complete and submit one Form 400-CEQA. If submitting multiple Form 400-A applications for the same project at the same time, only one 400-CEQA form is necessary for the entire project. If you need assistance completing this form, contact Lori Inga at (909) 396-3109.

FA	CILITY	INFO	RMATION CONTROL OF THE PROPERTY OF THE PROPERT				
Fac	ility Na	me:	Haynes Generating Station . Facility ID (6-Digit): 800074				
Pro	ject De	scripti	on: Title V Facility Permit To Operate Renewal.				
-							
			KEMPTION FROM FURTHER CEQA ACTION				
Cile	Yes	No No	as applicable				
A.	IES		Is this application for: 2 - 4 - 4 - 4 - 4 - 4 - 4 - 4 - 4 - 4 -				
В.			Equipment certification or equipment registration?				
c.	+						
.			A CEQA and/or NEPA document previously or currently prepared that specifically evaluates this project? If yes, a permit cannot be issued until a Final CEQA				
<u> </u>	document and Notice of Determination is submitted.						
D.							
E.			A Title V permit renewal (without equipment modifications)?				
F.			A Title V administrative permit revision?				
G.			The conversion of an existing permit into an initial Title V permit?				
Н.			A functionally identical permit unit replacement with no increase in rating or emissions?				
·I.		\square	A change of daily VOC permit limit to a monthly VOC permit limit?				
If "Y Skip	es" is ch to page :	ecked fo 2, "SIGN	or any question above, your application does not require additional evaluation for CEQA applicability. IATURES" and sign and date this form.				
REV	TEW 0	FIMP	ACTS WHICH MAY TRIGGER CEQA				
Comp all "Y	olete Sec es" respo	tions I-\ onses or	/I by checking "Yes" or "No" as applicable. To avoid delays in processing your application(s), explain a separate sheet and attach it to this form.				
<u>.</u>	Yes	No	Section I - General 4 12 4 15 15 15 15 15 15 15 15 15 15 15 15 15				
1.			Has this project generated any known public controversy regarding potential adverse impacts that may be generated by the project? Controversy may be construed as concerns raised by local groups at public meetings; adverse media attention such as negative articles in newspapers or other periodical publications, local news programs, environmental justice issues, etc.				
2.			Is this project part of a larger project?				
			Section II - Air Quality				
3.			Will there be any demolition, excavating, and/or grading construction activities that encompass an area exceeding 20,000 square feet?				
4.			Does this project include the open outdoor storage of dry bulk solid materials that could generate dust? If Yes, include a plot plan with the application package.				

1

A "project" means the whole of an action which has a potential for resulting in physical change to the environment, including construction activities, clearing or grading of land, improvements to existing structures, and activities or equipment involving the issuance of a permit. For example, a project might include installation of a new, or modification of an existing internal combustion engine, dry-cleaning facility, boiler, gas turbine, spray coating booth, solvent cleaning tank, etc.

To download the CEQA guidelines, visit http://ceres.ca.gov/env_law/state.html.

To download this form and the instructions, visit http://www.agmd.gov/ceqa or http://www.agmd.gov/ceqa or http://www.agmd.gov/permit or http://www.agmd.gov/permit or http://www.agmd.gov/ceqa or http://www.agmd.gov/ceqa or <a href="http://www.agmd.go

	Yes	No				
5.			Would this project result in notice not be subject to SCAQMD permit For example, compost materials or other etc.) have the potential to generate odor	requirements types of greenwa	s? aste (i.e., lawn clipping:	s, tree trimminas
6.			Does this project cause an increase and/or airplanes?	se of emission	ns from marine ves	sels, trains
7.			Will the proposed project increase aboveground onsite or transporte greater than or equal to the amou attached Table 1? ⁴	d by mobile v ints associate	ehicle to or from t	he site by
ļ			Section III - Water Resources			
8.			Will the project increase demand 5,000,000 gallons per day? The following examples identify some, but answer to this question: 1) projects that air pollution control equipment; 3) project projects that require new or expansion of water demand exceeds the capacity of the project; and 6) projects that require new	not all, types of generate steam; s that require wa existing sewage local water pur	f projects that may resumed for the projects that use we hater as part of the produced treatment facilities; 5) weyor to supply sufficie	ult in a "yes" ater as part of the uction process; 4) projects where nt water for the
9.			Will the project require constructi Examples of such projects are when water purveyor to supply sufficient water for the facilities such that the project requires nev	r demands excee project, or requ	d the capacity of the lo	cal water wage treatment
			Section IV - Transportation/Ci	rculation 🏄		45 (A)
10.	78		Will the project result in (Check all t			
			a. the need for more than 350 ne		• · · · · · · · · · · · · · · · · · · ·	
			b. an increase in heavy-duty tran- by more than 350 truck round-	sport truck tr	affic to and/or fro	m the facility
	П		c. increase customer traffic by me			
				The clian 700	visits per uay?	
			Section V Noise Noise	<u> </u>		1.4.4.1
11.	L		Will the project include equipment decibels (dB)?	t with a noise	specification GRE	ATER THAN 90
			Section VI - Public Services			
12.			Will the project create a permaner in any of the following areas (Check	nt need for ne k all that apply):	ew or additional pu	blic services
			a. Solid waste disposal? Check "No' generated by the project is less than fi	' if the projected ve tons per day.	potential amount of wa	astes
			 b. Hazardous waste disposal? Che hazardous wastes generated by the pro pounds). 	oject is less than	42 cubic yards per day	/ (or equivalent in
**RE	MINDER:	For eac	h "Yes" checked in the sections above, atta ed quantities volumes, weights, etc. * * * *	ch)all pertinent ii	nformation including bu	it not limited to
	NATU					
IS TR	UE AND (CORRECT	AT ALL INFORMATION CONTAINED HEREIN A TO THE BEST OF MY KNOWLEDGE. I UNDER S THE RIGHT TO CONSIDER OTHER PERTINE	STAND THAT THE	S FORM IS A SCREENING	G TOOL AND THAT
			BLE OFFICIAL OF FIRM:		PONSIBLE OFFICIAL OF FIR	
	ZU	las	tues	Chief Opera	iting Officer - Power Sy	rstem
TYPE (OR PRINT	NAME OF I	RESPONSIBLE OFFICIAL OF FIRM: RES	PONSIBLE OFFICIAL	L'S TELEPHONE NUMBER:	DATE Signed:
Enriq	ue Marti	nez		213-367-4435		10/29/52
SIGNA	TURE OF P	REPARER	, IF PREPARED BY PERSON OTHER THAN RESPONSIBLE OF	FFICIAL OF FIRM:	Environmental Super	visor
TYPE C	R PRINT	IAME OF	PREPARER:	PREPARER'S T	ELEPHONE NUMBER:	DATE Signed:
Timo	thy L. Co	onkin		213-3	67-0443	10/29/12

THIS CONCLUDES FORM 400-CEQA. INCLUDE THIS FORM AND THE ATTACHMENTS WITH FORM 400-A.

23



South Coast Air Quality Management District 21865 E. Copley Drive Diamond Bar, CA 91765 (909) 396-2000

MACT Determination Part 1 Application Form 500-MACT

Sources Subject to Section 112(j) Provisions 40 CFR 63.50 through 63.56

Source Ide	entification	
1) Source Name: Haynes Generating Station	on	
2) Source ID No.: 800074		
Physical	Location	
3) Street Address: 6801 Gast 2 nd Street		
4) City: Long Beach	5) County: Los Angeles	
6) State: CA	7) Zip Code: 90803	
Mailing Address (if differe	ent than physical location)	
8) Address: 111 North Hope Street, Room 1	050	
9) City: Los Angeles	10) County: Los Angeles	
11) State: CA	12) Zip Code: 90012	
Applicability I	Determination	
13) Is your facility a major source of hazardou need not complete the rest of this form. A major source is any contiguous area und has the potential to emit considering controls per year of any single HAP or 25 tons	der common control that emits or ols, in the aggregate, at least 10	☐ Yes ⊠ No
14) Do you own or operate an affected source EPA has not promulgated standards under		□ Vog
If not, you need not complete the rest of this form. (See Table of Promulgated Regulations, Table of Proposed Regulations, and Table of Upcoming Regulations at www.epa.gov/ttn/atw/eparules.html to determine if your standard has not been promulgated.)		
15) Provide a brief description of the major sou	urce and its activities:	

16) Provide a brief des	scription of the affec	ted source(s) in the	he relevant sourc	e category(ies):
,				
,				
			•	
17) Identify any source	es that have MACT c	leterminations un	der section 112(c	
				-
,				
	*			
	•	'.	÷	· .
i	•			
Cert	tification and Sign	ature of Respon	sible Official	
18) I certify that the inbest of my knowledge.	formation contained	in this applicatio	n to be accurate	and true to the
Responsible Official:				

Signature

Chief Operating Office - Power System
Title

Signature

Enrique Martinez

10/29/03 Date

Printed name of Signatory

A responsible official can be:

- The president, vice president, secretary, or treasurer of a corporation that owns the facility or a duly authorized representative that is responsible for the overall operation of the facility.
- An owner of the facility.
- A principal executive officer if the facility is owned by the federal, state, city, or county government.
- A ranking military officer if the facility is located at a military base.
- A general partner of a partnership that owns the facility.

Mail 1st Copy to: South Coast AQMD

Title V Administration 21865 E. Copley Drive Diamond Bar, CA 91765 Mail 2nd Copy to: Mr. Wayne Nastri, Administrator

USEPA, Region IX 75 Hawthorne Street San Francisco, CA 94105

Attn: Ms. Nahid Zoueshtiagh, Permits Office



* 8.0. 50x is or Lee Cote. 11/6/2003

P. O. Box 4944 Diamond Bar, CA 91765 (909) 396-2000

APPLICATION FOR F RMIT TO CONSTRUCT AND PERMIT TO OPENATE

Non-Title V Facilities: This form must be accompanied by one or more 400-E-xx so	eries form(s). Complete NC/NOV NUMBER:
this side of form only. Fitle V Facilities: Complete both sides of this form. Include additional forms as ne	CASSARY THE TOTAL THE TOTA
	INSPECTOR SECTOR ISSUE DATE
Section I - Company Information	the second of th
LEGAL NAME OF OPERATOR	Ø IRS OR □ S. S. NUMBER
Los Angeles Department of Water and I	Power 9 5 6 0 0 0 7 3
PERMIT TO BE ISSUED TO (SEE INSTRUCTIONS) Los Angeles Department of BUSINESS MAILING ADDRESS (A	f Water and Power
111 North Hope Street, Room 10	50. Los Angeles, CA 90012
PERMIT MAILING ADDRESS, IF DIFFERENT FROM BUSINESS MAILING ADDRESS	- 1, 200 mg 0.00, 0.0 0012
Same TYPE OF ORGANIZATION	
Corporation	☑ Government Entity
☐ Individual ☐ General Partnership ARE YOU A SMALL BUSINESS?	Other (Fifl in):
(SEE INSTRUCTIONS) AVERAGE ANNUAL Yes No	WOMAN/MINORITY OWNED?
THIS SECTION IS REQUIRED FOR ALL APPLICATIONS FOR NEW CONSTRUCTIONS FOR NEW CONSTRUCTION	□ Vac W No
ARE ALL MAJOR SOURCES UNDER SAME OWNERSHIP IN CALIFORNIA IN COMPLIANCE WITH	,
ARE YOU THE OWNER OF THE EQUIPMENT UNDER THIS APPLICATION? Yes	☐ No ☐ IRS OR ☐ S. S. NUMBER OF OWNER
IF NO, ENTER THE LEGAL NAME OF OWNER	THIS ON LIST. S. NOMBER OF OWNER
Section II - Facility Information EQUIPMENT ADDRESS/LOCATION	
6301 200 STre	# Haynes Generating Station
NUMBER/STREET	FACILITY ID NUMBER
CITY OR COMMUNITY CIP COLUMN CAN DESCRIBE COLU	8 0 0 7 4
Bruce M. Moore	TITLE OF CONTACT PERSON
TYPE OF BUSINESS AT THIS FACILITY	Manager, Air Quality Group PRIMARY SIC CODE FOR THIS FACILITY NUMBER OF EMPLOYEES AT THIS
Electric Generation	4 9 4 0 FACILITY 48
CONTACT PERSON'S TELEPHONE NUMBER (213) 367 - 3772 CONTACT PERSON'S FAX NUMBER (213) 367 - 4710	CONTACT PERSON'S E-MAIL ADDRESS
Section III - Application Type	bruce.moore@ladwp.com
	PREVIOUS PERMIT
DESCRIPTION OF EQUIPMENT: Facility Equipment Under Title V APPLICATION FOR (SEE INSTRUCTIONS):	PREVIOUS PERMIT Number:
□ NEW CONSTRUCTION □ MODIFICATION □ CHANGE OF PERMITTEES ■ CHANGE O	ARE YOU SUBMITTING MULTIPLE APPLICATIONS FOR EQUIPMENT IDENTICAL TO THAT DESCRIBED ABOVE?
APPLICATION FOR NON-TITLE V EQUIPMENT PERMIT. CHECK THE SUPPLEMENT	u res ⊯ No
400-E-1 • PARTICULATE MATTER (PM ₁₀) CONTROL EQUIPMENT 400-E-2 • VOLATILE ORGANIC COMPOUND (VOC) CONTROL EQUIPMENT	400-E-13 • INTERNAL COMBUSTION EQUIPMENT
400-E-3 ● SCRUBBER400-E-4 ● ABRASIVE BLASTING EQUIPMENT	400-E-14 • OPEN PROCESS TANK 400-E-14a • OPEN PROCESS TANK; PROCESS LINE
400-E-6 ● DEGREASER	400-E-15 • PRINTING EQUIPMENT 400-E-16 • SOLID MATERIALS STORAGE EQUIPMENT
400-E-7 • DRY CLEANING EQUIPMENT 400-E-8 • ETHYLENE OXIDE STERILIZER	400-E-17 • SPRAY BOOTH/OPEN SPRAY 400-E-17a • POWDER SPRAY BOOTH
400-E-9 • EXTERNAL COMBUSTION EQUIPMENT400-E-10 • FOOD BROILER/FRYER	400-E-18 • STORAGE TANK (LIQUID & GASEOUS MAT'L)
400-E-11 ● FUEL DISPENSING AND STORAGE EQUIPMENT	400-E-19 • WAVE SOLDER MACHINE 400-E-20 • ASBESTOS REMOVAL EQUIPMENT
400-E-12 ● GAS TURBINE APPLICATION FOR TITLE V FACILITY PERMIT. PROVIDE INFORMATION REQUEST	NONE & ADDITIONAL INFORMATION AND ADDITIONAL INFORMATIONAL INFORMATION AND ADDITIONAL INFORMATION AND ADDITIONAL INFORMATIONAL INFORMATION AND ADDITIONAL INFORMATION AND ADDITIONAL IN
I HEREBY CERTIFY THAT ALL INFORMATION CONTAINED HEREIN AND THEORY	ED ON REVERSE SIDE OF THIS FORM
SIGNATURE OF RESPONDED OFFICIAL OF FIRM:	TITLE OF RESPONSIBLE OFFICIAL OF FIRM:
TYPE OR PRINT NAME OF RESPONSIBLE OFFICIAL OF FIRM:	RESPONSIBLE OFFICIAL'S TELEPHONE NUMBER DATE SIGNED:
ENRIQUE MARTINEZ	(213) 367 - 4435
I HEREBY CERTIFY THAT ALL INFORMATION CONTAINED HEREIN AND INFORM SIGNATURE OF PREPARER, IF PREPARED BY PERSON OTHER THAN RESPONSIBLE OFFICIAL OF FIRM:	ATION SUBMITTED WITH THIS APPLICATION IS TRUE AND CORRECT. TITLE OF PREPARER:
TYPE OR PRINT NAME OF PREPARER, IF PREPARED BY PERSON OTHER THAN RESPONSIBLE OFFICIA	ENVIRONMENTAL SUPERVISOR 3
1801.	(212) 262 0440
TIMOTHY L. CONKIN	14 21 79
AQMD APPLICATION/TRACKING # PROJECT # TYPE	FOURTH CAPTER OF THE CAPTER OF
USE ONLY 1/217 Cil	D SECULPMENT CATEGORY CODE: FEE SCHEDULE: VALIDATION OF
(31654)	3983/3
(1891)	r. 3127/23

ENG. A R ENG. A R C SS ASSIGNMENT ENF. CHECK/MONEY ORDER AMOUNT DATE DATE IV UNIT ENGINEER SECT. # \$

₹ FORM 400-A, Rev. 10/97

TITLE V APPLICATION CERTIFICATION

- TO BE COMPLETED BY TITLE V FACILITIES ONLY -

, ì		TO BE COM LETED BY THEE VIACIETIES ONE!
9	ectio	on IV - Title V Application
1.	a. ∐ b. ⊠	s an application for a(n) (Check all applicable boxes and provide the requested information as appropriate): Initial Title V Permit Permit Renewal: Provide current permit expiration date:
	.d. □	Other (Complete and attach equipment specific Form 400-E-XX series form(s) to this form if your application involves permit action for new construction, change of location, non-administrative permit revision, alternative operating scenario (AOS), permit shield, streamlined permit conditions, or temporary source permit.)
2.	Is this	facility required to prepare a Risk Management Plan (RMP) for another agency?
S	ectio	n V - Title V Submittal Checklist
1.	Enter	the quantity of each type form submitted in the space provided: '
	1	500-A2 1 500-F1
	1	500-B 0 500-F2
	1_	500-C1 0 500-F3
	0	500-C2 0 500-F4
	0	500-D 1 each _ Other (specify): 400-CEQA, 500-H
2.	Additi	onal information referenced in this application submitted (Check ALL that apply):
	a. 🛛	Existing Facility Permit
	b. 🔲	Preliminary Facility Permit
	с. 🔲	EFB Report for Year
	d 🔲	None
	e. 🔲	Other (Specify):
3.	Supple	emental information included with this application submittal (Check ALL that apply):
	a. 🔲	Facility Plot Plan
	b. □	MSDS Sheet(s)
	c. 🛛	None
	d. 🔲	Other (Specify):

		30 DAY PUBLIC NOTICE		PUBLIC HEARING	45-DAY EPA REVIEW	
	APPLICATION TYPE	START DATE	END DAT	TE DATE	START DATE	END DATE
AQMD	INITIAL, RENEWAL & SIGNIFICANT					
	MINOR & DEMINIMUS	,				
USE	ESTABLISH GENERAL PERMIT					
,	USE THE SECTIONS BELOW FOR TITLE V INITIAL AND RENEWAL APPLICATIONS ONLY:					
ONLY	APPLICATION/TRACKING #	PROJECT #	TYPE E	QUIPMENT CATEGORY CODE:	FEE SCHEDULE:	VALIDATION
			BCD _	5550021	_ \$ ~ _	
ENG. /A)	R ENG. A R	CLASS ASSIGNMEN	SS ASSIGNMENT		CHECK/MONEY ORDER AMOUNT	
DATE 2	11.04 DATE	I III IV UNIT	ENGINEER	SECT.	#	\$

FORM 400-A, Rev. 10/97